

DALI 2.0 Slave Stack for tinyAVR® 1-Series Microcontrollers

Features

- IEC 62386-102 Compliant
- DALI 2 Slave Extended Commands
- DALI 2 Slave Stack Implemented on Microchip tinyAVR[®] 1-Series Microcontrollers

Introduction

Digital Addressable Lighting Interface (DALI) is applied in lighting control systems. The DALI stack follows the DALI standard edition 2.0 of IEC 62386-102 released in 2014. The LED module is demonstrated as the device type defined in standard IEC62386-207.

This application note introduces the DALI stack for the Microchip tinyAVR 1-series microcontroller, including:

- Software Structure
- Stack Functionalities
- Stack API Routines
- Demo System Setup

Table of Contents

Fe	eatures1			
Int	roduction	1		
1.	Relevant Devices			
_	1.1. tinyAVR 1-Series			
2.	. Recommended Reading			
3.	. Software Structure			
4.	Stack Functions			
5.	Stack API	8		
6.	Demo System Setup	10		
	6.1. DALI Master Integrating DALI Power			
7.	DALI Slave Edition 2 Extended and Removed Commands	11		
8.	Get Source Code from Atmel START	12		
9.	Revision History	13		
The Microchip Web Site				
Customer Change Notification Service				
Customer Support				
Mi	Microchip Devices Code Protection Feature			
Le	_egal Notice			
Tra	Frademarks			
Qι	Quality Management System Certified by DNV			
W	Vorldwide Sales and Service			

1. Relevant Devices


This chapter lists the relevant devices for this document.

1.1 tinyAVR 1-Series

The figure below shows the tinyAVR 1-series devices, illustrating pin count variants and memory sizes:

- Vertical migration can be done upwards without code modification, since these devices are pin
 compatible and provide the same or even more features. Downward migration may require code
 modification due to fewer available instances of some peripherals.
- Horizontal migration to the left reduces the pin count, therefore, the available features.

Figure 1-1. tinyAVR® 1-Series Device Overview



Devices with different Flash memory size typically also have different SRAM and EEPROM.

2. Recommended Reading

There are several released Microchip DALI solution documents. It is recommended to read these to get an overall idea about the DALI system.


- AT03922: DALI Slave with XMEGA® E Software User Guide (42177) This document describes
 the DALI slave based on ATxmega32E5. It demonstrates the software architecture and its
 application programming interface (API).
- AT04022: DALI Slave with XMEGA E Hardware User Guide (42174) This document introduces
 DALI slave hardware design including DALI interface, LED driver based on the ATxmega32E5
 device.
- AT06409: DALI Master with ATxmega32E5 User Guide (42224) This document demonstrates
 DALI master reference design based on ATxmega32E5, with the DALI bus power supply
 integrated. It shows the setup process of a DALI system, which is operated via PC software.
- AT01244: DALI Slave Reference Design (42071) This document describes the DALI slave implementation based on a ATmega88PA device.
- AT10828: DALI Slave Stack for SAM D20/D21 (42386) This document shows the DALI slave reference design for SAM D20/21 devices.

The above documents include hardware and software packages which can be downloaded from www.microchip.com. They provide hardware design files, software source code, and PC tools.

3. Software Structure

Opened with IAR Embedded Workbench[®], the DALI2.0 SLAVE STACK example project tree view should look like the screen-shot in the figure below. Refer to Get Source Code from Atmel | START for more details.

Figure 3-1. DALI 2.0 Slave Project Tree



Due to the code size limitation of the MCU, an Atmel Studio package is not created.

The content of the folders are:

- dali_slave:
 - Provides the DALI application and stack files.
 - dali_bit, dali_bod, dali_eeprom and dali_timer
 These folders contain the application files for the DALI stack.
 - dali_bit

DALI bits are decoded and encoded here. EXTINT (External Interrupt) peripheral is used for decoding.

dali_bod

When power-down is detected, DALI slave will shut down PWM and LED to save power before Reset. The BOD interrupt deals with this detection.

- dali_eeprom

When the update flag rises for persistent memory, the EEPROM will update its corresponding contents. A backup page is utilized to avoid incomplete data copy during the system power-down. When the system powers on, the variables will be loaded from EEPROM to SRAM.

dali_timer
 System timers are provided here. They are used for DALI bit, frame, and fade timing,
 PWM and random address seeds.

dali_stack

The DALI stack is located in this folder.

- dali_frame
 Provides the DALI frame process files.
- dali_cmd
 Provides the DALI command implementation files.
- dali_hal
 Hardware abstraction layer, including a complete set of APIs for using hardware
 resources by DALI stack that is convenient for rapid design-in and smooth integration
 with varied peripherals.

4. Stack Functions

For the DALI stack, the process and the flowchart are the same as in the AT03922: DALI Slave with XMEGA E - Software User's Guide (42177). Refer to chapters "Service" and "Service Layer API Introduction" in the AT03922 document for details.

5. Stack API

The input and output of the stack act through functions defined in dali_hal.h.

```
dali_hal_enable_forward_disable_backward()
```

This function is used after the DALI slave has finished sending a backward frame. This will reenable the DALI external input detection and disable the DALI detection timer. The detection timer will be enabled when the DALI Start bit is detected.

```
dali hal disable forward enable backward()
```

This function is used before the DALI slave starts to send a backward frame. This will disable DALI input detection and enable the slave sending timer. It is necessary to disable the input detection because the backward frame signal can route back to the DALI input.

```
dali_hal_get_dali_input_level()
```

This function detects the DALI interface input voltage level used to check the interface failure state

```
dali_hal_update_pwm_output()
```

This function is used to update the PWM output for LED light dimming.

```
dali_hal_get_seed0_value(), dali_hal_get_seed1_value()
```

These two functions generate random address seeds for auto-address allocation. Two different clock sources are used to get a 32-bit random value.

```
dali_hal_save_persistent_variables()
```

This function is called when the "SAVE PERSISTENT VARIABLES" command is executed. It should update variables in the EEPROM immediately.

```
dali hal identify device ( )
```

This function executes the identification by flashing, sound, or other visual or audible means after receiving the "IDENTIFY DEVICE" command.


When the stack variables need executing outside, the below functions offer channels for outside functions to get or set them. These functions are listed in file dali_top.h.

The above two functions should be implemented in the application layer according to the dedicated detection methods by the designer.

6. Demo System Setup

A typical DALI system contains DALI master, DALI slave, and DALI power. To set up this DALI demo system on an ATtiny817 DALI demo board, see the diagram below.

Figure 6-1. DALI Demo System




6.1 DALI Master Integrating DALI Power

Refer to the DALI master document AT06409: DALI Master with ATxmega32E5 User Guide (42224) for details. The PC software communicates with the DALI master to operate a DALI slave.

6.2 DALI Slave

The following figure shows the MCU fuse settings. BOD is enabled with threshold level 3.94V. A 16MHz internal oscillator is selected as the MCU main clock source. The Compare B output is enabled for LED dimming. The PA5 multiplexing TCDOUTB function connects with the on-board LED as lighting demo in this application.

Figure 6-2. Fuse Settings



Pins PB3 and PB4 are used for DALI decoding/encoding in file dali_bit.c. EEPROM data memory in the ATtiny817 device is required to store DALI parameters. There are a total four pages in ATtiny817, the lower three pages store parameters and the last one acts as backup.

7. DALI Slave Edition 2 Extended and Removed Commands

The following tables show extended and removed commands compared with edition 1.

Table 7-1. DALI Slave Edition 2 Extended Commands

Command name	Opcode byte/Address byte
GO TO LAST ACTIVE LEVEL	0x0A
SAVE PERSISTENT VARIABLES	0x22
SET OPERATIONG MODE(DTR0)	0x23
RESET MEMORY BANK(DTR0)	0x24
IDENTIFY DEVICE	0x25
SET EXTENDED FADE TIME(DTR0)	0x30
QUERY OPERATION MODE	0x9D
QUERY LIGHT SOURCE TYPE	0x9F
QUERY MANUFACTURER SPECIFIC MODE	0xA6
QUERY NEXT DEVICE TYPE	0xA7
QUERY EXTENDED FADE TIME	0xA8
QUERY CONTROL GEAR FAILURE	0xAA
PING	0xAD
WRITE MEMORY LOCATION - NO REPLY	0xC9

Table 7-2. DALI Slave Edition 2 Removed Command

Command name	Address byte
PHYSICAL SELECTION	0xBD

8. Get Source Code from Atmel | START

The example code is available through Atmel | START, which is a web-based tool that enables configuration of application code through a Graphical User Interface (GUI). The code can be downloaded for both Atmel Studio 7.0 and IAR Embedded Workbench[®] via the direct example code-link(s) below, or the *BROWSE EXAMPLES* button on the Atmel | START front page.

Atmel | START web page: http://start.atmel.com/

Example Code

AVR42793 DALI2.0 SLAVE STACK (IAR Embedded Workbench ONLY)

 http://start.atmel.com/#example/Atmel%3Aavr42793_dali2_slave%3A0.0.1%3A%3AApplication %3AAVR42793 DALI2 Slave Stack%3A

Press *User guide* in Atmel | START for details and information about example projects. The *User guide* button can be found in the example browser, and by clicking the project name in the dashboard view within the Atmel | START project configurator.

Atmel Studio

Download the code as an .atzip file for Atmel Studio from the example browser in Atmel | START, by clicking *DOWNLOAD SELECTED EXAMPLE*. To download the file from within Atmel | START, click *EXPORT PROJECT* followed by *DOWNLOAD PACK*.

Double-click the downloaded .atzip file and the project will be imported to Atmel Studio 7.0.

IAR Embedded Workbench

For information on how to import the project in IAR Embedded Workbench, open the Atmel | START User guide, select *Using Atmel Start Output in External Tools*, and *IAR Embedded Workbench*. A link to the Atmel | START user guide can be found by clicking *About* from the Atmel | START front page or *Help And Support* within the project configurator, both located in the upper right corner of the page.

9. Revision History

Doc Rev.	Date	Comments	
1	10/2017	 Converted to Microchip format. Replaced Atmel document number 42793 Rev. A with Microchip DS00002539 Rev. A. 	
		 Added "Relevant Devices" and "Get source code from Atmel START" from [COMMON] 	
		 Changed tiny817 references to tinyAVR 1- series where relevant 	
		 Added publication variables resource with direct example code links in Atmel START 	
42793A	10/2016	Initial document release	

The Microchip Web Site

Microchip provides online support via our web site at http://www.microchip.com/. This web site is used as a means to make files and information easily available to customers. Accessible by using your favorite Internet browser, the web site contains the following information:

- Product Support Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- General Technical Support Frequently Asked Questions (FAQ), technical support requests, online discussion groups, Microchip consultant program member listing
- Business of Microchip Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

Customer Change Notification Service

Microchip's customer notification service helps keep customers current on Microchip products. Subscribers will receive e-mail notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, access the Microchip web site at http://www.microchip.com/. Under "Support", click on "Customer Change Notification" and follow the registration instructions.

Customer Support

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Field Application Engineer (FAE)
- Technical Support

Customers should contact their distributor, representative or Field Application Engineer (FAE) for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in the back of this document.

Technical support is available through the web site at: http://www.microchip.com/support

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip devices:

- Microchip products meet the specification contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is one of the most secure families of its kind on the market today, when used in the intended manner and under normal conditions.
- There are dishonest and possibly illegal methods used to breach the code protection feature. All of these methods, to our knowledge, require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Most likely, the person doing so is engaged in theft of intellectual property.
- Microchip is willing to work with the customer who is concerned about the integrity of their code.

 Neither Microchip nor any other semiconductor manufacturer can guarantee the security of their code. Code protection does not mean that we are guaranteeing the product as "unbreakable."

Code protection is constantly evolving. We at Microchip are committed to continuously improving the code protection features of our products. Attempts to break Microchip's code protection feature may be a violation of the Digital Millennium Copyright Act. If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue for relief under that Act.

Legal Notice

Information contained in this publication regarding device applications and the like is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION, INCLUDING BUT NOT LIMITED TO ITS CONDITION, QUALITY, PERFORMANCE, MERCHANTABILITY OR FITNESS FOR PURPOSE. Microchip disclaims all liability arising from this information and its use. Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Trademarks

The Microchip name and logo, the Microchip logo, AnyRate, AVR, AVR logo, AVR Freaks, BeaconThings, BitCloud, CryptoMemory, CryptoRF, dsPIC, FlashFlex, flexPWR, Heldo, JukeBlox, KeeLoq, KeeLoq logo, Kleer, LANCheck, LINK MD, maXStylus, maXTouch, MediaLB, megaAVR, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, Prochip Designer, QTouch, RightTouch, SAM-BA, SpyNIC, SST, SST Logo, SuperFlash, tinyAVR, UNI/O, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

ClockWorks, The Embedded Control Solutions Company, EtherSynch, Hyper Speed Control, HyperLight Load, IntelliMOS, mTouch, Precision Edge, and Quiet-Wire are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, Anyln, AnyOut, BodyCom, chipKIT, chipKIT logo, CodeGuard, CryptoAuthentication, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, EtherGREEN, In-Circuit Serial Programming, ICSP, Inter-Chip Connectivity, JitterBlocker, KleerNet, KleerNet logo, Mindi, MiWi, motorBench, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PureSilicon, QMatrix, RightTouch logo, REAL ICE, Ripple Blocker, SAM-ICE, Serial Quad I/O, SMART-I.S., SQI, SuperSwitcher, SuperSwitcher II, Total Endurance, TSHARC, USBCheck, VariSense, ViewSpan, WiperLock, Wireless DNA, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

Silicon Storage Technology is a registered trademark of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2017, Microchip Technology Incorporated, Printed in the U.S.A., All Rights Reserved.

ISBN: 978-1-5224-2233-4

Quality Management System Certified by DNV

ISO/TS 16949

Microchip received ISO/TS-16949:2009 certification for its worldwide headquarters, design and wafer fabrication facilities in Chandler and Tempe, Arizona; Gresham, Oregon and design centers in California and India. The Company's quality system processes and procedures are for its PIC® MCUs and dsPIC® DSCs, KEELOQ® code hopping devices, Serial EEPROMs, microperipherals, nonvolatile memory and analog products. In addition, Microchip's quality system for the design and manufacture of development systems is ISO 9001:2000 certified.



Worldwide Sales and Service

AMERICAS	ASIA/PACIFIC	ASIA/PACIFIC	EUROPE
Corporate Office	Asia Pacific Office	China - Xiamen	Austria - Wels
2355 West Chandler Blvd.	Suites 3707-14, 37th Floor	Tel: 86-592-2388138	Tel: 43-7242-2244-39
Chandler, AZ 85224-6199	Tower 6, The Gateway	Fax: 86-592-2388130	Fax: 43-7242-2244-393
Tel: 480-792-7200	Harbour City, Kowloon	China - Zhuhai	Denmark - Copenhagen
Fax: 480-792-7277	Hong Kong	Tel: 86-756-3210040	Tel: 45-4450-2828
Technical Support:	Tel: 852-2943-5100	Fax: 86-756-3210049	Fax: 45-4485-2829
http://www.microchip.com/	Fax: 852-2401-3431	India - Bangalore	Finland - Espoo
support	Australia - Sydney	Tel: 91-80-3090-4444	Tel: 358-9-4520-820
Web Address:	Tel: 61-2-9868-6733	Fax: 91-80-3090-4123	France - Paris
www.microchip.com	Fax: 61-2-9868-6755	India - New Delhi	Tel: 33-1-69-53-63-20
Atlanta	China - Beijing	Tel: 91-11-4160-8631	Fax: 33-1-69-30-90-79
Duluth, GA	Tel: 86-10-8569-7000	Fax: 91-11-4160-8632	France - Saint Cloud
Tel: 678-957-9614	Fax: 86-10-8528-2104	India - Pune	Tel: 33-1-30-60-70-00
Fax: 678-957-1455	China - Chengdu	Tel: 91-20-3019-1500	Germany - Garching
Austin, TX	Tel: 86-28-8665-5511	Japan - Osaka	Tel: 49-8931-9700
Tel: 512-257-3370	Fax: 86-28-8665-7889	Tel: 81-6-6152-7160	Germany - Haan
Boston	China - Chongqing	Fax: 81-6-6152-9310	Tel: 49-2129-3766400
Westborough, MA	Tel: 86-23-8980-9588	Japan - Tokyo	Germany - Heilbronn
Tel: 774-760-0087	Fax: 86-23-8980-9500	Tel: 81-3-6880- 3770	Tel: 49-7131-67-3636
Fax: 774-760-0088	China - Dongguan	Fax: 81-3-6880-3771	Germany - Karlsruhe
Chicago	Tel: 86-769-8702-9880	Korea - Daegu	Tel: 49-721-625370
Itasca, IL	China - Guangzhou	Tel: 82-53-744-4301	Germany - Munich
Tel: 630-285-0071	Tel: 86-20-8755-8029	Fax: 82-53-744-4302	Tel: 49-89-627-144-0
Fax: 630-285-0075	China - Hangzhou	Korea - Seoul	Fax: 49-89-627-144-44
Dallas	Tel: 86-571-8792-8115	Tel: 82-2-554-7200	Germany - Rosenheim
Addison, TX	Fax: 86-571-8792-8116	Fax: 82-2-558-5932 or	Tel: 49-8031-354-560
Tel: 972-818-7423	China - Hong Kong SAR	82-2-558-5934	Israel - Ra'anana
Fax: 972-818-2924	Tel: 852-2943-5100	Malaysia - Kuala Lumpur	Tel: 972-9-744-7705
Detroit	Fax: 852-2401-3431	Tel: 60-3-6201-9857	Italy - Milan
Novi, MI	China - Nanjing	Fax: 60-3-6201-9859	Tel: 39-0331-742611
Tel: 248-848-4000	Tel: 86-25-8473-2460	Malaysia - Penang	Fax: 39-0331-466781
Houston, TX	Fax: 86-25-8473-2470	Tel: 60-4-227-8870	Italy - Padova
Tel: 281-894-5983	China - Qingdao	Fax: 60-4-227-4068	Tel: 39-049-7625286
Indianapolis	Tel: 86-532-8502-7355	Philippines - Manila	Netherlands - Drunen
Noblesville, IN	Fax: 86-532-8502-7205	Tel: 63-2-634-9065	Tel: 31-416-690399
Tel: 317-773-8323	China - Shanghai	Fax: 63-2-634-9069	Fax: 31-416-690340
Fax: 317-773-5453	Tel: 86-21-3326-8000	Singapore	Norway - Trondheim
Tel: 317-536-2380	Fax: 86-21-3326-8021	Tel: 65-6334-8870	Tel: 47-7289-7561
Los Angeles	China - Shenyang	Fax: 65-6334-8850	Poland - Warsaw
Mission Viejo, CA	Tel: 86-24-2334-2829	Taiwan - Hsin Chu	Tel: 48-22-3325737
Tel: 949-462-9523	Fax: 86-24-2334-2393	Tel: 886-3-5778-366	Romania - Bucharest
Fax: 949-462-9608	China - Shenzhen	Fax: 886-3-5770-955	Tel: 40-21-407-87-50
Tel: 951-273-7800	Tel: 86-755-8864-2200	Taiwan - Kaohsiung	Spain - Madrid
Raleigh, NC	Fax: 86-755-8203-1760	Tel: 886-7-213-7830	Tel: 34-91-708-08-90
Tel: 919-844-7510	China - Wuhan	Taiwan - Taipei	Fax: 34-91-708-08-91
New York, NY	Tel: 86-27-5980-5300	Tel: 886-2-2508-8600	Sweden - Gothenberg
Tel: 631-435-6000	Fax: 86-27-5980-5118	Fax: 886-2-2508-0102	Tel: 46-31-704-60-40
San Jose, CA	China - Xian	Thailand - Bangkok	Sweden - Stockholm
Tel: 408-735-9110	Tel: 86-29-8833-7252	Tel: 66-2-694-1351	Tel: 46-8-5090-4654
Tel: 408-436-4270	Fax: 86-29-8833-7256	Fax: 66-2-694-1350	UK - Wokingham
Canada - Toronto			Tel: 44-118-921-5800
Tel: 905-695-1980			Fax: 44-118-921-5820
Fax: 905-695-2078			
	I	T. Control of the con	I