**AN 20.2** 

# **USB 2.0 High Speed Interface Design**

## INTRODUCTION

As product form factors continue to shrink, designers are increasingly pushed to find new and innovative ways to incorporate the USB interface into their products. To enable the development of these new system architectures, the Microchip USB Transceiver products are also evolving to address the needs associated with the High Speed USB 2.0 interface.

To enable maximum reliability and flexibility of design in the customer application, Microchip's USB Transceivers offer superior software configurability and hardware integration:

- Programmable Transmitter Amplitude
- · Programmable Receiver Sensitivity
- · Integrated USB Switch
- · Integrated ESD Protection

Optimizing both the Transmitter and Receiver allows for maximum USB transfer speeds and simplifies High Speed USB-IF certification. Through the use of PHYBoost and VariSense technology, Microchip USB Transceivers allow designers maximum flexibility when defining their product while reducing risk and time to market.

Whether you are looking to improve margin on an existing product design or avoid a hardware modification to pass USB-IF certification, Microchip transceivers provide unsurpassed configurability to enable product success.

## References

Universal Serial Bus Specification, Revision 2.0, April 27, 2000 USB-IF 2.0 Electrical Test Specification, Revision 1.2, April 1, 2003 Microchip USB Transceiver Data Sheets:

- USB331x
- USB332x
- USB333x


## **Definitions**

HS = USB 2.0 High Speed

## **DESIGN CHALLENGES**

In many applications, the USB interface design has a minimal number of components, as shown in Figure 1. In this case, the product designer may desire maximum margin on the transmitter and receiver for USB interface performance and certification.

FIGURE 1: COMMON USB ARCHITECTURE FOR MOBILE DEVICE



Successful USB designs require that great attention be paid to the D+ and D- signal routing. The D+ and D- traces must be routed according to the following guidelines:

- · Routed 90 ohm differential
- Length matched within 0.025" (0.635mm) of each other
- Minimize total trace length


Common system elements which negatively impact the USB electrical performance of products include:

- Common Mode EMI Chokes
- ESD Suppression Devices
- External USB Switches
- · Cables between the USB Transceiver and the USB connector
- · Captive (Proprietary) USB Cables

By integrating significant ESD protection and the USB switch, the Microchip USB Transceiver provides design margin for both the USB Transmitter and Receiver.


Figure 2 shows a real-world example of a cell phone which puts a heavy demand on the USB PHY Transmitter and Receiver.

FIGURE 2: EXAMPLE OF COMPLEX CELL PHONE ARCHITECTURE



By integrating the USB Switch and ESD Protection, the Microchip Transceiver improves the transmitter and receiver performance of the product by removing serial and parallel elements from the signal path. Figure 3 shows this refined signal path using the Microchip Transceiver.

FIGURE 3: CELL PHONE BLOCK DIAGRAM WITH MICROCHIP USB TRANSCEIVER



For all of these architectures, an additional lossy element in the system which can cause USB-IF certification issues is the use of a "captive cable". A captive cable is a hard-wired or, more commonly, a custom detachable cable used to connect the USB device to the USB host. All USB-IF certification is required to occur with the captive cable installed, and this means that the USB High Speed Electrical Test measurements for the Transmitter and Receiver are made at the end of the captive cable. This presents additional challenges when trying to meet the requirements of the USB-IF High Speed Electrical Test Specification.

## HIGH SPEED TRANSMITTER


Platforms that place internal cables, EMI components, or other serial lossy elements on DP/DM can experience difficulty in passing the High Speed Eye Diagram tests for USB-IF certification. To overcome the losses associated with these elements, Microchip USB Transceivers offer PHYBoost. PHYBoost, also known as "TX Boost", increases the current drive of the DP/DM transmitters.

# **USB-IF Certification Requirements**

There are five High Speed Electrical Tests associated with the Transmitter: EL\_2, EL\_4, EL\_5, EL\_6, and EL\_7. EL\_5 tests the product's eye diagram.

Figure 4 shows the eye diagram from a Microchip USB Transceiver with the default transmitter settings.





## **Optimizing Transmitter Performance with PHYBoost**


Due to losses in the path of D+ and D- or noise in the platform, the amplitude of the eye diagram may need to be increased.

PHYBoost is technology that enables software to configure the drive strength of the USB High Speed Transmitter. Microchip USB Transceivers can overcome attenuation on the USB transmitter path through the use of PHYBoost. Consult the data sheet for specific Microchip USB Transceivers for a detailed definition of the PHYBoost capabilities.

If the elements which attenuate the eye diagram are primarily frequency dependent (inductive or capacitive), then the designer must take care not to violate the TEST\_J or TEST\_K tests by applying too high of a PHYBoost setting. TEST\_J and TEST\_K are DC tests of the D+ and D- static drive voltages. If PHYBoost is set too high in an effort to overcome AC losses, the TEST\_J and TEST\_K tests can exceed the maximum DC limit for D+ and D-.


In Figure 5, an 11% PHYBoost setting has been applied.

FIGURE 5: TRANSMITTER EYE (11% BOOST)



In Figure 6, a 25% PHYBoost setting has been applied.

FIGURE 6: TRANSMITTER EYE (25% BOOST)



# **HIGH SPEED RECEIVER**

All Microchip USB Transceivers are certified with the USB-IF to meet the USB specification for silicon components. However, the mobile device product must also pass within the same limits. System elements connected to D+ and D- such as common mode chokes, ESD suppression arrays, and external switches serve to reduce the overall Receiver Sensitivity of the USB device and produce higher test values for EL\_17 and EL\_16.

## HS Receiver Sensitivity: EL 17 ("Un-Squelch")

The USB-IF USB 2.0 Electrical Test Specification defines test EL\_17 as:

"A high speed capable device must implement a transmission envelope detector that does not indicate squelch (i.e. reliably receives packets) when a receiver's input exceeds 150 mV differential amplitude."

Since the release of the specification, the USB-IF has issued a waiver which extends this limit to 200mV. Devices or silicon passing with EL\_17 between 150 mV and 200 mV passes with an automatic "waiver". If required, this waiver is automatically granted by the test facility without a need for special application or justification.

# HS Receiver Sensitivity: EL\_16 ("Squelch")

The USB-IF USB 2.0 Electrical Test Specification defines test EL 16 as:

"A high speed capable device must implement a transmission envelope detector that does indicates squelch (i.e. never receives packets) when a receiver's input falls below 100 mV differential amplitude."

## **Optimizing Receiver Sensitivity with VariSense**

Many Microchip USB Transceivers feature VariSense. VariSense is technology that Microchip offers in its USB transceivers to configure the Receiver Sensitivity of the USB Transceiver via software.

For some mobile products, no customizing is necessary and the product will pass USB-IF certification using the default VariSense receiver sensitivity settings. However, as smartphone architectures evolve, a greater number of products require extra help in passing USB-IF certification testing or improving the performance of the USB interface. VariSense makes this possible.

VariSense gives the product designer the ability to lower the threshold of the squelch detector simply by modifying a ULPI register. For a mobile device, this means that a lower amplitude signal received at the USB transceiver will still be detected

Consult the data sheet for specific Microchip USB Transceivers for a detailed definition of each USB Transceiver's Vari-Sense capabilities.

# APPENDIX A: APPLICATION NOTE REVISION HISTORY

# TABLE A-1: REVISION HISTORY

Revision Level & Date	Section/Figure/Entry	Correction
DS00002954A (02-13-19)	Replaces previous SMSC version Rev. 1.0 (11-26-12)	
Rev. 1.0 (11-26-12)	Document co-branded: Microchip logo added, modification to legal disclaimer	
Rev. 1.0 (08-03-09)	Document release	

## Note the following details of the code protection feature on Microchip devices:

- Microchip products meet the specification contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is one of the most secure families of its kind on the market today, when used in the
  intended manner and under normal conditions.
- There are dishonest and possibly illegal methods used to breach the code protection feature. All of these methods, to our knowledge, require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Most likely, the person doing so is engaged in theft of intellectual property.
- Microchip is willing to work with the customer who is concerned about the integrity of their code.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of their code. Code protection does not mean that we are guaranteeing the product as "unbreakable."

Code protection is constantly evolving. We at Microchip are committed to continuously improving the code protection features of our products. Attempts to break Microchip's code protection feature may be a violation of the Digital Millennium Copyright Act. If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue for relief under that Act.

Information contained in this publication regarding device applications and the like is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION, INCLUDING BUT NOT LIMITED TO ITS CONDITION, QUALITY, PERFORMANCE, MERCHANTABILITY OR FITNESS FOR PURPOSE. Microchip disclaims all liability arising from this information and its use. Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

#### **Trademarks**

The Microchip name and logo, the Microchip logo, AnyRate, AVR, AVR logo, AVR Freaks, BitCloud, chipKIT, chipKIT logo, CryptoMemory, CryptoRF, dsPIC, FlashFlex, flexPWR, Heldo, JukeBlox, KeeLoq, Kleer, LANCheck, LINK MD, maXStylus, maXTouch, MediaLB, megaAVR, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, Prochip Designer, QTouch, SAM-BA, SpyNIC, SST, SST Logo, SuperFlash, tinyAVR, UNI/O, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

ClockWorks, The Embedded Control Solutions Company, EtherSynch, Hyper Speed Control, HyperLight Load, IntelliMOS, mTouch, Precision Edge, and Quiet-Wire are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, Anyln, AnyOut, BodyCom, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, EtherGREEN, In-Circuit Serial Programming, ICSP, INICnet, Inter-Chip Connectivity, JitterBlocker, KleerNet, KleerNet logo, memBrain, Mindi, MiWi, motorBench, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, SAM-ICE, Serial Quad I/O, SMART-I.S., SQI, SuperSwitcher, SuperSwitcher II, Total Endurance, TSHARC, USBCheck, VariSense, ViewSpan, WiperLock, Wireless DNA, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

Silicon Storage Technology is a registered trademark of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2009-2019, Microchip Technology Incorporated, All Rights Reserved.

ISBN: 9781522441458

# QUALITY MANAGEMENT SYSTEM CERTIFIED BY DNV = ISO/TS 16949=

Microchip received ISO/TS-16949:2009 certification for its worldwide headquarters, design and wafer fabrication facilities in Chandler and Tempe, Arizona; Gresham, Oregon and design centers in California and India. The Company's quality system processes and procedures are for its PIC® MCUs and dsPIC® DSCs, KEELoQ® code hopping devices, Serial EEPROMs, microperipherals, nonvolatile memory and analog products. In addition, Microchip's quality system for the design and manufacture of development systems is ISO 9001:2000 certified.



# Worldwide Sales and Service

#### **AMERICAS**

Corporate Office 2355 West Chandler Blvd. Chandler, AZ 85224-6199 Tel: 480-792-7200

Fax: 480-792-7200 Fax: 480-792-7277 Technical Support:

http://www.microchip.com/ support

Web Address:

www.microchip.com

Atlanta Duluth, GA

Tel: 678-957-9614 Fax: 678-957-1455

Austin, TX Tel: 512-257-3370

**Boston** 

Westborough, MA Tel: 774-760-0087 Fax: 774-760-0088

Chicago Itasca, IL

Tel: 630-285-0071 Fax: 630-285-0075

Dallas

Addison, TX Tel: 972-818-7423 Fax: 972-818-2924

**Detroit** Novi, MI

Tel: 248-848-4000

Houston, TX

Tel: 281-894-5983 Indianapolis

Noblesville, IN Tel: 317-773-8323 Fax: 317-773-5453 Tel: 317-536-2380

Los Angeles

Mission Viejo, CA Tel: 949-462-9523 Fax: 949-462-9608 Tel: 951-273-7800

**Raleigh, NC** Tel: 919-844-7510

New York, NY Tel: 631-435-6000

**San Jose, CA** Tel: 408-735-9110 Tel: 408-436-4270

**Canada - Toronto** Tel: 905-695-1980 Fax: 905-695-2078

## ASIA/PACIFIC

Australia - Sydney Tel: 61-2-9868-6733

**China - Beijing** Tel: 86-10-8569-7000

**China - Chengdu** Tel: 86-28-8665-5511

China - Chongqing Tel: 86-23-8980-9588

**China - Dongguan** Tel: 86-769-8702-9880

China - Guangzhou Tel: 86-20-8755-8029

China - Hangzhou Tel: 86-571-8792-8115

China - Hong Kong SAR Tel: 852-2943-5100

China - Nanjing Tel: 86-25-8473-2460

China - Qingdao Tel: 86-532-8502-7355

**China - Shanghai** Tel: 86-21-3326-8000

**China - Shenyang** Tel: 86-24-2334-2829

**China - Shenzhen** Tel: 86-755-8864-2200

China - Suzhou Tel: 86-186-6233-1526

China - Wuhan

Tel: 86-27-5980-5300 **China - Xian** Tel: 86-29-8833-7252

China - Xiamen
Tel: 86-592-2388138

**China - Zhuhai** Tel: 86-756-3210040

### ASIA/PACIFIC

India - Bangalore Tel: 91-80-3090-4444

India - New Delhi Tel: 91-11-4160-8631

India - Pune Tel: 91-20-4121-0141

Japan - Osaka

Tel: 81-6-6152-7160

Japan - Tokyo

Tel: 81-3-6880- 3770

Korea - Daegu Tel: 82-53-744-4301

Korea - Seoul Tel: 82-2-554-7200

Malaysia - Kuala Lumpur Tel: 60-3-7651-7906

Malaysia - Penang Tel: 60-4-227-8870

Philippines - Manila Tel: 63-2-634-9065

**Singapore** Tel: 65-6334-8870

**Taiwan - Hsin Chu** Tel: 886-3-577-8366

Taiwan - Kaohsiung Tel: 886-7-213-7830

**Taiwan - Taipei** Tel: 886-2-2508-8600

Thailand - Bangkok Tel: 66-2-694-1351

Vietnam - Ho Chi Minh Tel: 84-28-5448-2100

#### **EUROPE**

Austria - Wels Tel: 43-7242-2244-39 Fax: 43-7242-2244-393

Denmark - Copenhagen Tel: 45-4450-2828

Fax: 45-4485-2829
Finland - Espoo

Tel: 358-9-4520-820 France - Paris

Tel: 33-1-69-53-63-20 Fax: 33-1-69-30-90-79

**Germany - Garching** Tel: 49-8931-9700

**Germany - Haan** Tel: 49-2129-3766400

**Germany - Heilbronn** Tel: 49-7131-67-3636

Germany - Karlsruhe Tel: 49-721-625370

**Germany - Munich** Tel: 49-89-627-144-0 Fax: 49-89-627-144-44

**Germany - Rosenheim** Tel: 49-8031-354-560

Israel - Ra'anana Tel: 972-9-744-7705

Italy - Milan Tel: 39-0331-742611 Fax: 39-0331-466781

Italy - Padova Tel: 39-049-7625286

**Netherlands - Drunen** Tel: 31-416-690399 Fax: 31-416-690340

Norway - Trondheim Tel: 47-7288-4388

**Poland - Warsaw** Tel: 48-22-3325737

**Romania - Bucharest** Tel: 40-21-407-87-50

**Spain - Madrid** Tel: 34-91-708-08-90 Fax: 34-91-708-08-91

**Sweden - Gothenberg** Tel: 46-31-704-60-40

**Sweden - Stockholm** Tel: 46-8-5090-4654

**UK - Wokingham** Tel: 44-118-921-5800 Fax: 44-118-921-5820