AN2798

Using the PIC16F/PIC18F Ground Referenced Temperature Indicator Module

Introduction

Author: Monte Denton, Microchip Technology Inc.

Microchip PIC® microcontrollers have internal temperature indicator solutions.

This application note covers temperature indicators in several families for PIC16F and PIC18F that have the internal temperature indicator referenced to ground. Examples are PIC16F15355 and the PIC18F27K42. This grounded configuration allows more consistent operation with the use of a variable voltage power supply than the previous PIC16F versions that were configured with temperature diodes referenced to V_{DD}. Consult "Using the Temperature Indicator Module" (AN2092) for the use and application of PIC16F devices that utilize the V_{DD} reference temperature indicator.

Acronyms and variables used in this document can be found in section 5.


Table of Contents

Int	roduc	tion	1		
1.	The	ory of Operation for the Temperature Indicator Module	3		
	1.1.	Application Limits			
2.	Single-Point Calibration Method				
	2.1.	Finalizing the Equations	6		
	2.2.	Required Constants	6		
	2.3.	Additional Variables			
	2.4.	Determining V _{REF}			
	2.5.	Determining V _{OUT}			
	2.6.				
	2.7.	Calculating the value of OFFSET	rature Indicator Module		
3.	Two	-Point Calibration Method	3		
	3.1.	Two-Point Calibration Using the DIA	11		
	3.2.	Measuring the Results of Two-Point Calibration with DIA calculated T _C	11		
4.	Add	itional Tips and Tricks for Accurate Temperature Measurement	13		
5.	Acro	onyms and Variables	14		
Th	e Mic	rochip Web Site	15		
Cu	stom	er Change Notification Service	15		
Cu	stom	er Support	15		
Microchip Devices Code Protection Feature					
Le	gal N	otice	16		
Tra	adem	arks	16		
Qι	ality	Management System Certified by DNV	17		
Wo	orldw	de Sales and Service	18		

1. Theory of Operation for the Temperature Indicator Module


The temperature indicator module uses the property that at a constant current the silicon junctions have a nearly linear negative voltage response when subjected to an increasing temperature change. The temperature indicator module has a thermal sensing element that is supplied by a constant current source. The ADC is used to measure the voltage of the temperature sensor. The sensor is enabled by the TSEN Control bit. The sensor also has the TSRNG Control bit that determines whether the voltage output falls within the high or low range. Most applications will use the high range if the supply voltage is between 2.5V and 5.5V. The low-range setting is used for supply voltages between 1.8V and 2.5V. Note that the ADC reference must be tied to $V_{\rm DD}$ in this application mode.

Figure 1-1.



The thermal sensing element is not directly measurable to the end user. Instead, the ADC is used to measure the voltage of the element. Figure 1-2 shows a typical 10-bit ADC response to changing temperature.

Figure 1-2. Average ADC Result



1.1 Application Limits

- The temperature indicator module requires single-point calibration at a minimum. This calibration step can use the calibration information stored in the device.
- This module may not be suitable when an absolute temperature accuracy of less than ±5°C is required.
- Driving high current with output pins can cause variation in the measured temperature due to high die temperature.
- This module is not recommended for use in critical temperature control applications or for thermal safety applications without a suitable backup method of thermal protection.

2. Single-Point Calibration Method

Equation 2-1 is used to convert the measured average integer result recorded from the ADC into an equivalent analog voltage.

Equation 2-1.

$$V_{OUT} = \frac{ADC_{RESULT} * V_{REF}}{RES}$$

The V_{OUT} term is part of the solution to solve the linear equation that establishes the relationship to the temperature using the slope intercept method Y = MX + B.

Substituting V_{OUT} for Y, T_C for M and V_F for B gives Equation 2-2 below.

Equation 2-2.

$$V_{OUT} = (T_C * T_A) + V_F$$

A better definition of the variables will be provided in a later section of this document. Solving for temperature gives Equation 2-3.

Equation 2-3.

$$T_A = \frac{(V_{OUT} - V_F)}{T_C}$$

$$T_A = \left(\frac{V_{OUT}}{T_C}\right) - \left(\frac{V_F}{T_C}\right)$$

Process variation adds uncertainty to the V_F constant providing an uncalibrated temperature that is not useful for most applications. An additional temperature offset term is required. This offset variable will be calculated by subtracting the uncalibrated temperature from the actual ambient temperature as shown in Equation 2-4. Several methods of determining the OFFSET will be covered later in this document.

Equation 2-4.

OFFSET = Actual Temperature - Uncalibrated Temperature

This offset is added to the previous equation to create an equation for actual temperature. The offset can be calculated several ways but it is normally calculated once during the manufacturing process and then added to Equation 2-5 as a constant for each production device.

Equation 2-5.

$$T_A = \left(\frac{V_{OUT}}{T_C}\right) - \left(\frac{V_F}{T_C}\right) = OFFSET$$

Equation 2-5 sets could be further consolidated into one equation but there are advantages to keeping the equations in a sequence for readability, code size reduction, and elimination of floating point math. This complete equation is shown in Equation 2-6.

Equation 2-6.

$$V_{OUT} = \frac{ADC_{RESULT} * V_{REF}}{RES}$$

$$T_A = \left(\frac{V_{OUT}}{T_C}\right) - \left(\frac{V_F}{T_C}\right) + OFFSET$$

2.1 Finalizing the Equations

Data taken on several sample devices from different production lots determines the range of most of the constants to find nominal values. These constants should be sufficient to generate usable temperatures with minimal calibration required. These constants will be defined further in the following sections.

ADC_{RESULT}: Analog-to-Digital Conversion Result

Generally, ADC_{RESULT} is determined by a single conversion of the ADC with the temperature indicator channel selected. This usually gives a temperature reading that is adequate for typical control applications. The ADC_{RESULT} is generated after loading the integer value from the ADRESH and ADRESL registers in Right Justified mode. The combined field ADRES is usually available in the header for Equation 2-7.

Equation 2-7.

$$ADC_{RESULT} = (ADRESH \ll 8) + ADRESL$$

In the application the temperature reading may vary several degrees when at a fixed temperature. This variation can be caused by noise on the FVR and by the internal switching noise generated by the CPU core. The user should utilize oversampling of the ADC_{RESULT} to reduce the variation of the temperature result if higher accuracy is necessary.

Usually, 8X oversampling is adequate to limit the variation but the user may also utilize other noise reduction methods as needed. The calculation for the oversampled result is shown in Equation 2-8.

Equation 2-8.

$$ADC_{SUM} = \sum_{i=0}^{7} ((ADRESH \ll 8) + ADRESL)$$

$$ADC_{RESULT} = ADC_{SUM} \gg 3$$
Or
$$ADC_{SUM} = \sum_{i=0}^{7} ADRES$$

$$ADC_{RESULT} = ADC_{SUM} \gg 3$$

2.2 Required Constants

V_{REF}: Reference voltage of the ADC module

The ADC needs a stable reference to be able to accurately measure the voltage of the temperature sensor. The only two valid references for measuring temperature are the following:

- 2X fixed voltage reference (FVR)
- Supply voltage (V_{DD})

Most applications will use the 2X FVR as the reference. The 2X FVR is nominally 2.048V but can vary ±4% with process variation. The actual voltage of the FVR is recorded in the FVRA2X memory location in the DIA during testing. The DIA has an integer measurement of the FVR voltage in millivolts. Consult the data sheet for additional information on the specifications and reading of the DIA.

V_{DD} will normally only be used when the supply voltage range is between 2.0V and 2.5V. The 2X FVR does not regulate well enough in this range to ensure accurate voltage measurement. The user must

ensure that the supply voltage is well regulated or must provide the means to measure the voltage with the ADC at the point when the temperature calculation is needed.

V_{REF} will be treated as a variable in the equation for these reasons.

RES: Resolution of the ADC

The total integer resolution of the ADC is defined by the equation 2ⁿ-1, where 'n' is the number of bits of resolution of the ADC. The value for RES will be either 1023 for the 10-bit ADC or 4095 for the 12-bit ADC. The user *may* want to keep these values as variables for portability but generally it is simpler to set constants and use different production code for 10-bit or 12-bit solutions.

T_C: Temperature coefficient of the sensor module

The temperature coefficient will be different depending on the setting of the TSRNG bit. The high setting will vary from part to part between -3.5 to -3.9 mV/°C with normal process variation. The low-range setting will vary between -2.2 to -2.6 mV/°C. Almost every application will use the high-range setting. The exception for low range is when the supply voltage is below 2.5V and temperatures are below 0°C. The basic equation will use the midband points of -3.7 mV/°C and -2.4 mV/°C. This number is reasonably critical as this slope is not adjusted with single-point calibration.

V_F: Forward voltage of sensor module at 0°C

The sensor module has a bias established by the constant current flow. This bias was measured on multiple lots at 0°C to establish a range. The voltage ranges from 1.4 to 1.6V at high range and 0.9 to 1.1 on low range. The equations will use 1.5V and 1.0V for convenience. The exact number is not critical at this stage because the temperature calibration step will adjust temperature to accommodate the exact bias of each device.

2.3 Additional Variables

The remaining terms are the variables that will be captured and calculated during the measurement process.

- V_{OUT}: Voltage calculated from the ADC_{RESULT}
- OFFSET: The temperature offset error

The last term is the solution.

T_A: Calculated temperature

2.4 Determining V_{RFF}

The value of V_{REF} is nominally 2.048 volts. Optionally, the user can utilize a Flash read to acquire the value from the DIA in FVRA2X location. The value is in millivolts and will require scaling to get to volts.

The user will need to determine the value of V_{REF} if V_{DD} is in use as the reference.

2.5 Determining V_{OUT}

To simplify the equations, this example will be for the 10-bit ADC. Adding the constants gives Equation 2-9.

Equation 2-9.

$$V_{OUT} = \frac{ADC_{RESULT} * V_{REF}}{1023}$$

2.6 Calculating T_A (Ambient Temperature)

Adding the constants to the second equation gives Equation 2-10.

Equation 2-10.

$$T_A = \left(\frac{V_{OUT}}{-0.0037} \right) - \left(\frac{1.5}{-0.0037} \right) + OFFSET$$

Further refinement gives Equation 2-11.

Equation 2-11.

$$T_A = 405 - (V_{OUT} * 270) + OFFSET$$

2.7 Calculating the Value of OFFSET

Room temperature calibration requires the use of the completed equation sequence with the OFFSET value set to zero. The user then utilizes Equation 2-4 to calculate the OFFSET. The temperature offset error is determined during the calibration process. This offset will vary from device to device and is reasonably constant across all temperatures. The two main methods of calculating the offset are to perform a room temperature calibration or to use information provided in the DIA. Room temperature calibration will generally provide an accurate measurement at or near the calibration point.

Calculating OFFSET Value Using Information Stored in DIA

The DIA calibration value is the actual ADC value captured at 90°C during production testing. The DIA value will generally be better when the high temperature error needs to be limited. The user calculates a value for the OFFSET by utilizing the DIA information stored in TSLR2 or TSHR2 (see Equation 2-12).

Equation 2-12.

$$V_{OUT} = \frac{TSHR2 * V_{REF}}{2^n - 1}$$

Or

$$V_{OUT} = \frac{TSLR2 * V_{REF}}{2^n - 1}$$

$$OFFSET = 90 - (405 - (V_{OUT} * 270))$$

Using the DIA data will generate a slightly different offset from the room temperature calibration. The error is dependent on the error in the temperature slope. Either of these methods to calculate the OFFSET is acceptable but it is generally better to use the value that is nearest to the critical application temperature to determine the best method for calibration.




Figure 2-1. Typical Performance for Single-Point Calibration

3. Two-Point Calibration Method

The previous section mentioned that the slope of the internal temperature sensor could vary between -3.5 to -3.9 mV/°C in high range or between -2.2 to -2.6 mV/°C in low range. Slight variations in semiconductor processing cause this difference in slope. Two-point calibration permits the user to compensate for this variation in slope to allow better temperature measurement performance over a wider range. Two-point calibration requires additional effort during the production process because of the need to acquire an additional data point. Generally, it is recommended that the two data points bracket the needed temperature range, but an argument can be made to keep one of the data points at room temperature for an easier calibration process. The second data point needs to be removed from the first data point to get the highest confidence in the calculated slope.

Section 2. Single-Point Calibration Method gave Equation 3-1 for the output voltage of the sensor.

Equation 3-1.

$$V_{OUT} = (T_C * T_A) + V_F$$

Solving for ambient temperature provides Equation 3-2.

Equation 3-2.

$$T_A = \frac{(V_{OUT} - V_F)}{T_C}$$

The typical solution would be to solve for the slope using Equation 3-3 to get the voltage slope in mV, the same as utilized in the single-point method.

Equation 3-3.

$$T_C = \frac{V_{OUT2} - V_{OUT1}}{T_{A2} - T_{A1}}$$

A better alternative is to directly use two ADC_{RESULT} readings to determine the slope of the ADC output, as shown in Equation 3-4.

Equation 3-4.

$$ADC_{TC} = \frac{ADC_{RESULT2} - ADC_{RESULT1}}{T_{A2} - T_{A1}}$$

The main advantage is that the ADC_{RESULT} terms are integer numbers, simplifying the 8-bit math. The slope for the temperature equation is then determined with Equation 3-5.

Equation 3-5.

$$T_C = \frac{ADC_{TC} * V_{REF}}{RES}$$

Inserting the slope equation into temperature equation condenses to Equation 3-6.

Equation 3-6.

$$T_A = \frac{(V_{OUT} - V_F) * RES}{ADC_{TC} * V_{REF}}$$

This method will produce a large whole number in the numerator and a small integer number in the denominator simplifying the math on an 8-bit device. The temperature calculated from this equation will still have some temperature offset error. This offset error is because the forward voltage term V_F is a process average and each individual device will vary slightly from the process average. As in the single-point method, add offset correction term to Equation 3-7.

Equation 3-7.

$$T_A = \left(\frac{(V_{OUT} - V_F) * RES}{ADC_{TC} * V_{REF}}\right) + OFFSET$$

The offset term is like the offset in the single-point calibration process in Equation 2-4. Make use of one of the two temperatures utilized to calculate the temperature coefficient to calculate the offset. In general, use the temperature that is the closest to the critical application temperature.

3.1 Two-Point Calibration Using the DIA

As stated previously, the two-point calibration method gives a more accurate slope term for the temperature calculation at the expense of a more complicated calibration process. A variation of the two-point method is to use either the TSHR2 or TSLR2 calibration value as a 90°C data point. The data from the DIA memory are loaded into equation Equation 3-4 replacing the terms for $ADC_{RESULT2}$ and T_{A2} to get Equation 3-8.

Equation 3-8.

$$ADC_{TC} = \frac{DIA_{VALUE} - ADC_{RoomTemp}}{90 - RoomTemp}$$

The only calibration step needed will be the room temperature calibration process, as described in section 2. Single-Point Calibration Method. This operation only works if the 2X FVR is used for V_{REF} because the DIA (TSHR2 or TSLR2) is captured at the 2X setting. This method should produce a result that is almost as good as the two-point calibration but only limited by application specific conditions. As with the single-point method, oversampling may be needed to limit the affects of internal noise in the conversion. The temperature offset term will still need to be added for this calculation. The offset can be calculated either from the room temperature calibration or from the ADC count recorded in the DIA value.

3.2 Measuring the Results of Two-Point Calibration with DIA calculated T_C

The results presented in the following graph show that the overall temperature error is less than a singlepoint calibration process with some additional code overhead. Individual results may vary depending on user conditions.




Figure 3-1. Typical Performance for Two-Point Calibration

4. Additional Tips and Tricks for Accurate Temperature Measurement

- Insert a minimum of 50 µs delay when switching from a different ADC channel or if the temperature indicator has not been used for several milliseconds.
- Select the V_{SS} channel of the ADC right before selecting the temperature channel if the ADC was used to measure a signal level higher than 1.5V.
- The ADC conversion can be performed in Sleep to reduce system noise generated by the CPU clock.
- Oversampling and averaging the temperature indicator results reduces the temperature error in noisy environments.
- Perform the ADC measurement of the temperature indicator in repeatable conditions whenever possible.
- Perform the conversion with the same F_{OSC} and Sleep mode used in calibration to limit temperature skew due to localized die heating.
- Build the calibration routine into the production code if possible.

5. Acronyms and Variables

TSEN: Temperature Indicator Control bit

TSRNG: Temperature Indicator Range Selection bit

V_{OUT}: Voltage output of thermal sensing element; V_{DD}: Supply voltage

ADC: Analog-to-Digital Converter

ADC_{RESULT}: Combined digital output of both ADC conversion registers

ADRESH: Upper byte of ADC conversion; ADRESL: Lower byte of ADC conversion

V_{REF}: Reference voltage used by ADC

FVR: Fixed Voltage Reference

RES: Total resolution as calculated by 2ⁿ-1

T_C: Temperature coefficient; T_A: Variable ambient temperature

V_F: Constant forward voltage of typical temperature sense element at 0°C

OFFSET: Constant for a temperature correction calculated at calibration

ADC_{SUM}: Combined value of several consecutive ADC conversions

DIA: Device Information Area location in memory with tested constant information

TSHR2: Temperature indicator high-range ADC_{RESULT} at 90°C

TSLR2: Temperature indicator low-range ADC_{RESULT} at 90°C

FVRA2X: ADC FVR1 output voltage for 2X setting

The Microchip Web Site

Microchip provides online support via our web site at http://www.microchip.com/. This web site is used as a means to make files and information easily available to customers. Accessible by using your favorite Internet browser, the web site contains the following information:

- Product Support Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- General Technical Support Frequently Asked Questions (FAQ), technical support requests, online discussion groups, Microchip consultant program member listing
- Business of Microchip Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

Customer Change Notification Service

Microchip's customer notification service helps keep customers current on Microchip products. Subscribers will receive e-mail notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, access the Microchip web site at http://www.microchip.com/. Under "Support", click on "Customer Change Notification" and follow the registration instructions.

Customer Support

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Field Application Engineer (FAE)
- Technical Support

Customers should contact their distributor, representative or Field Application Engineer (FAE) for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in the back of this document.

Technical support is available through the web site at: http://www.microchip.com/support

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip devices:

- Microchip products meet the specification contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is one of the most secure families of its kind on the market today, when used in the intended manner and under normal conditions.
- There are dishonest and possibly illegal methods used to breach the code protection feature. All of these methods, to our knowledge, require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Most likely, the person doing so is engaged in theft of intellectual property.
- Microchip is willing to work with the customer who is concerned about the integrity of their code.

 Neither Microchip nor any other semiconductor manufacturer can guarantee the security of their code. Code protection does not mean that we are guaranteeing the product as "unbreakable."

Code protection is constantly evolving. We at Microchip are committed to continuously improving the code protection features of our products. Attempts to break Microchip's code protection feature may be a violation of the Digital Millennium Copyright Act. If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue for relief under that Act.

Legal Notice

Information contained in this publication regarding device applications and the like is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION, INCLUDING BUT NOT LIMITED TO ITS CONDITION, QUALITY, PERFORMANCE, MERCHANTABILITY OR FITNESS FOR PURPOSE. Microchip disclaims all liability arising from this information and its use. Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Trademarks

The Microchip name and logo, the Microchip logo, AnyRate, AVR, AVR logo, AVR Freaks, BitCloud, chipKIT, chipKIT logo, CryptoMemory, CryptoRF, dsPIC, FlashFlex, flexPWR, Heldo, JukeBlox, KeeLoq, Kleer, LANCheck, LINK MD, maXStylus, maXTouch, MediaLB, megaAVR, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, Prochip Designer, QTouch, SAM-BA, SpyNIC, SST, SST Logo, SuperFlash, tinyAVR, UNI/O, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

ClockWorks, The Embedded Control Solutions Company, EtherSynch, Hyper Speed Control, HyperLight Load, IntelliMOS, mTouch, Precision Edge, and Quiet-Wire are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, Anyln, AnyOut, BodyCom, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, EtherGREEN, In-Circuit Serial Programming, ICSP, INICnet, Inter-Chip Connectivity, JitterBlocker, KleerNet, KleerNet logo, memBrain, Mindi, MiWi, motorBench, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, SAM-ICE, Serial Quad I/O, SMART-I.S., SQI, SuperSwitcher, SuperSwitcher II, Total Endurance, TSHARC, USBCheck, VariSense, ViewSpan, WiperLock, Wireless DNA, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

Silicon Storage Technology is a registered trademark of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2018, Microchip Technology Incorporated, Printed in the U.S.A., All Rights Reserved.

ISBN: 978-1-5224-3561-7

Quality Management System Certified by DNV

ISO/TS 16949

Microchip received ISO/TS-16949:2009 certification for its worldwide headquarters, design and wafer fabrication facilities in Chandler and Tempe, Arizona; Gresham, Oregon and design centers in California and India. The Company's quality system processes and procedures are for its PIC® MCUs and dsPIC® DSCs, KEELOQ® code hopping devices, Serial EEPROMs, microperipherals, nonvolatile memory and analog products. In addition, Microchip's quality system for the design and manufacture of development systems is ISO 9001:2000 certified.



Worldwide Sales and Service

AMERICAS	ASIA/PACIFIC	ASIA/PACIFIC	EUROPE
Corporate Office	Australia - Sydney	India - Bangalore	Austria - Wels
2355 West Chandler Blvd.	Tel: 61-2-9868-6733	Tel: 91-80-3090-4444	Tel: 43-7242-2244-39
Chandler, AZ 85224-6199	China - Beijing	India - New Delhi	Fax: 43-7242-2244-393
Tel: 480-792-7200	Tel: 86-10-8569-7000	Tel: 91-11-4160-8631	Denmark - Copenhagen
Fax: 480-792-7277	China - Chengdu	India - Pune	Tel: 45-4450-2828
Technical Support:	Tel: 86-28-8665-5511	Tel: 91-20-4121-0141	Fax: 45-4485-2829
http://www.microchip.com/	China - Chongqing	Japan - Osaka	Finland - Espoo
support	Tel: 86-23-8980-9588	Tel: 81-6-6152-7160	Tel: 358-9-4520-820
Web Address:	China - Dongguan	Japan - Tokyo	France - Paris
www.microchip.com	Tel: 86-769-8702-9880	Tel: 81-3-6880- 3770	Tel: 33-1-69-53-63-20
Atlanta	China - Guangzhou	Korea - Daegu	Fax: 33-1-69-30-90-79
Duluth, GA	Tel: 86-20-8755-8029	Tel: 82-53-744-4301	Germany - Garching
Tel: 678-957-9614	China - Hangzhou	Korea - Seoul	Tel: 49-8931-9700
Fax: 678-957-1455	Tel: 86-571-8792-8115	Tel: 82-2-554-7200	Germany - Haan
Austin, TX	China - Hong Kong SAR	Malaysia - Kuala Lumpur	Tel: 49-2129-3766400
Tel: 512-257-3370	Tel: 852-2943-5100	Tel: 60-3-7651-7906	Germany - Heilbronn
Boston	China - Nanjing	Malaysia - Penang	Tel: 49-7131-67-3636
Westborough, MA	Tel: 86-25-8473-2460	Tel: 60-4-227-8870	Germany - Karlsruhe
Tel: 774-760-0087	China - Qingdao	Philippines - Manila	Tel: 49-721-625370
Fax: 774-760-0088	Tel: 86-532-8502-7355	Tel: 63-2-634-9065	Germany - Munich
Chicago	China - Shanghai	Singapore	Tel: 49-89-627-144-0
Itasca, IL	Tel: 86-21-3326-8000	Tel: 65-6334-8870	Fax: 49-89-627-144-44
Tel: 630-285-0071	China - Shenyang	Taiwan - Hsin Chu	Germany - Rosenheim
Fax: 630-285-0075	Tel: 86-24-2334-2829	Tel: 886-3-577-8366	Tel: 49-8031-354-560
Dallas	China - Shenzhen	Taiwan - Kaohsiung	Israel - Ra'anana
Addison, TX	Tel: 86-755-8864-2200	Tel: 886-7-213-7830	Tel: 972-9-744-7705
Tel: 972-818-7423	China - Suzhou	Taiwan - Taipei	Italy - Milan
Fax: 972-818-2924	Tel: 86-186-6233-1526	Tel: 886-2-2508-8600	Tel: 39-0331-742611
Detroit	China - Wuhan	Thailand - Bangkok	Fax: 39-0331-466781
Novi, MI	Tel: 86-27-5980-5300	Tel: 66-2-694-1351	Italy - Padova
Tel: 248-848-4000	China - Xian	Vietnam - Ho Chi Minh	Tel: 39-049-7625286
Houston, TX	Tel: 86-29-8833-7252	Tel: 84-28-5448-2100	Netherlands - Drunen
Tel: 281-894-5983	China - Xiamen		Tel: 31-416-690399
Indianapolis	Tel: 86-592-2388138		Fax: 31-416-690340
Noblesville, IN	China - Zhuhai		Norway - Trondheim
Tel: 317-773-8323	Tel: 86-756-3210040		Tel: 47-72884388
Fax: 317-773-5453			Poland - Warsaw
Tel: 317-536-2380			Tel: 48-22-3325737
Los Angeles			Romania - Bucharest
Mission Viejo, CA			Tel: 40-21-407-87-50
Tel: 949-462-9523			Spain - Madrid
Fax: 949-462-9608			Tel: 34-91-708-08-90
Tel: 951-273-7800			Fax: 34-91-708-08-91
Raleigh, NC			Sweden - Gothenberg
Tel: 919-844-7510			Tel: 46-31-704-60-40
New York, NY			Sweden - Stockholm
Tel: 631-435-6000			Tel: 46-8-5090-4654
San Jose, CA			UK - Wokingham
Tel: 408-735-9110			Tel: 44-118-921-5800
Tel: 408-436-4270			Fax: 44-118-921-5820
Canada - Toronto			
Tel: 905-695-1980			
Fax: 905-695-2078			