


1N6842
**60 VOLTS, 10 AMP
DUAL SCHOTTKY
COMMON CATHODE
CENTERTAP RECTIFIER**
DESIGNER'S DATA SHEET
FEATURES:

- Low Profile Ceramic SMD
- High Surge Rating
- Low Reverse Leakage Current
- Low Forward Voltage
- Seam Welded Package
- Low Capacitance
- Ultrasonic Aluminum Wire Bonds

SMD-0.5

MAXIMUM RATINGS (per leg)


RATING	SYMBOL	VALUE	UNIT
Peak Repetitive Reverse and DC Blocking Voltage 1N6842	V_{RRM} V_{RWN} V_R	 60	 Volts
Average Rectified Forward Current (Resistive Load, 60Hz, Sine Wave, $T_A = 25^{\circ}\text{C}$)	 I_o	 10	 Amps
Peak Surge Current (8.3 ms Pulse, $T_A = 25^{\circ}\text{C}$, per leg)	 I_{FSM}	 200	 Amps
Operating & Storage Temperature	T_{op} & T_{stg}	-55 to +150	$^{\circ}\text{C}$
Maximum Thermal Resistance Junction to Case, each individual diode Junction to Case <i>Note 1</i>	 $R_{\theta JC}$	 2.8 1.7	 $^{\circ}\text{C} / \text{W}$

Note 1: Both legs tied together
11/1199

ELECTRICAL CHARACTERISTICS (per leg)

CHARACTERISTICS	SYMBOL	MAX.	UNIT
Instantaneous Forward Voltage Drop ($I_F = 3 \text{ Adc}$, $T_A = 25^\circ\text{C}$, 300 μs Pulse) ($I_F = 10 \text{ Adc}$, $T_A = 25^\circ\text{C}$, 300 μs Pulse) ($I_F = 15 \text{ Adc}$, $T_A = 25^\circ\text{C}$, 300 μs Pulse)	V_F	0.62 0.78 0.90	Vdc
Instantaneous Forward Voltage Drop ($I_F = 10 \text{ Adc}$, $T_A = 100^\circ\text{C}$, 300 μs Pulse) ($I_F = 15 \text{ Adc}$, $T_A = 100^\circ\text{C}$, 300 μs Pulse)	V_F	0.70 0.80	Vdc
Reverse Leakage Current (Rated V_R , $T_A = 25^\circ\text{C}$, 300 μs pulse minimum)	I_R	50	μA
Reverse Leakage Current (Rated V_R , $T_A = 100^\circ\text{C}$, 300 μs pulse minimum)	I_R	10	mA
Junction Capacitance ($V_R = 10\text{Vdc}$, $T_A = 25^\circ\text{C}$, $f = 1 \text{ MHz}$)	C_J	400	Pf

CASE OUTLINE: SMD-0.5



TYPICAL OPERATING CURVES
($T_A = 25^\circ\text{C}$ Unless otherwise specified)

