

Product Overview

The SG1548 is an integrated circuit capable of monitoring up to four positive DC supply voltages simultaneously for overvoltage and undervoltage fault conditions. An on-chip inverting op amp also allows monitoring one negative DC voltage. The fault tolerance window is accurately programmable from $\pm 5\%$ to $\pm 40\%$ using a simple divider network on the 2.5V reference. A single external capacitor sets the fault indication delay, eliminating false outputs due to switching noise, logic transition current spikes, and short-term AC line interruptions.

An additional comparator referenced to 2.5V allows the AC line to be monitored for undervoltage conditions or for generation of a line clock. The comparator can also be used for programmable undervoltage lockout in a switching power supply. Uncommitted collector and emitter outputs permit both inverting and non-inverting operation. External availability of the precision 2.5V reference and open-collector logic outputs permit expansion to monitor additional voltage using available open-collector quad comparators.

Features

- Monitors four DC voltages and the AC line
- Precision 2.5V $\pm 1\%$ low-drift reference
- Fault tolerance adjustable from $\pm 5\%$ to $\pm 40\%$
- $\pm 3\%$ Trip threshold tolerance over temperature
- Separate 10 mA, 40V overvoltage, undervoltage, and AC line fault outputs
- Fault delay programmable with a single capacitor
- 30 mV comparator hysteresis to prevent oscillations
- On-chip inverting op-amp for negative voltage
- Open-collector output logic or expandability
- Operation from 4.5V to 40V supply

High Reliability Features

Following are the high reliability features of SG1548:

- Available to MIL-STD-883, ¶ 1.2.1
- Radiation TID is available upon request
- Level "S" processing available

Figure 1. Block Diagram




Table of Contents

Product Overview.....	1
1. Connection Diagrams and Ordering Information.....	3
2. Absolute Maximum Ratings.....	4
3. Thermal Data.....	5
4. Recommended Operating Conditions.....	6
5. Electrical Characteristics.....	7
6. Application Information.....	9
6.1. Setting the Fault Tolerance Window.....	9
6.2. Scaling the Monitored Supply Voltages.....	9
6.3. Monitoring a Negative Voltage.....	9
6.4. Setting the Fault Delay.....	9
6.5. AC Line Monitoring.....	9
6.6. Application Example.....	9
7. Package Outline Dimensions.....	11
8. Revision History.....	14
Microchip Information.....	15
The Microchip Website.....	15
Product Change Notification Service.....	15
Customer Support.....	15
Microchip Devices Code Protection Feature.....	15
Legal Notice.....	15
Trademarks.....	16
Quality Management System.....	17
Worldwide Sales and Service.....	18

1. Connection Diagrams and Ordering Information

Table 1-1. Connection Diagrams and Ordering Information¹⁻³

Ambient Temperature	Type	Package	Part Number	Packaging Type	Connection Diagram
-55 °C to 125 °C	J	16-Pin ceramic dip	SG1548J-883B SG1548J	CERDIP	LOWER THRESHOLD 1 16 INV. OUTPUT GROUND 2 15 INV. INPUT V_{REF} 3 14 SENSE 4 +V_{IN} 4 13 SENSE 3 LINE SENSE 5 12 SENSE 2 EMITTER OUTPUT 6 11 SENSE 1 COLLECTOR OUTPUT 7 10 U.V. FAULT DELAY 8 9 O.V. FAULT N package: Pb-free / RoHS 100% Matte Tin Lead Finish
-25 °C to 85 °C 0 °C to 70 °C	N	16-Pin plastic dip	SG2548N ⁴ SG3548N ⁴	PDIP	
-25 °C to 85 °C 0 °C to 70 °C	DW	16-pin small-outline wide body	SG2548DW ⁴ SG3548DW ⁴	SOWB	LOWER THRESHOLD 1 16 INV. OUTPUT GROUND 2 15 INV. INPUT V_{REF} 3 14 SENSE 4 +V_{IN} 4 13 SENSE 3 LINE SENSE 5 12 SENSE 2 EMITTER OUTPUT 6 11 SENSE 1 COLLECTOR OUTPUT 7 10 U.V. FAULT DELAY 8 9 O.V. FAULT DW package: Pb-free / RoHS 100% Matte Tin Lead Finish
-55 °C to 125 °C	L	20-Pin ceramic (LCC)	SG1548L-883B SG1548L	CLCC	1. N.C. 3 2 1 20 19 11. N.C. 2. LOWER THRESHOLD 4 18 12. O.V. FAULT 3. GROUND 5 17 13. U.V. FAULT 4. V_{REF} 6 16 14. SENSE 1 5. +V_{IN} 7 15 15. SENSE 2 6. N.C. 8 14 16. N.C. 7. LINE SENSE 9 13 17. SENSE 3 8. EMITTER OUTPUT 10 12 18. SENSE 4 9. COLLECTOR OUTPUT 11 11 19. INV. INPUT 10. DELAY 12 10 20. INV. OUTPUT

Notes:

1. Contact factory for DESC product availability.
2. All parts are viewed from the top.
3. Hermetic packages J and L use Pb37/Sn63 hot solder lead finish, contact factory for availability of RoHS versions.
4. RoHS compliant.

2. Absolute Maximum Ratings

Table 2-1. Absolute Maximum Ratings¹⁻²

Parameter	Value	Units
Supply voltage (+V _{IN})	40	V
Fault output collector voltage	40	V
Sense input voltage range	-0.3V to 6.0V	V
Fault output sink current	20	mA
Line sense input current	±1	mA
Inverting op amp input current	-5	mA
Inverting op amp output current	25	mA
Operating Junction Temperature		
Hermetic (J, L packages)	150	°C
Plastic (N, DW packages)	150	°C
Storage temperature range	-65 to 150	°C
Lead temperature	300	°C

Notes:

1. Values beyond which damage may occur
2. Pb-free/RoHS peak package solder reflow temp. (40 second max. exposure). 260 °C (+0, -5).

3. Thermal Data

Table 3-1. Thermal Data¹⁻²

Parameter	Value	Units
J Package		
Thermal resistance-junction to case, θ_{JC}	30	°C/W
Thermal resistance-junction to ambient, θ_{JA}	80	°C/W
N Package		
Thermal resistance-junction to case, θ_{JC}	40	°C/W
Thermal resistance-junction to ambient, θ_{JA}	65	°C/W
DW Package		
Thermal resistance-junction to case, θ_{JC}	40	°C/W
Thermal resistance-junction to ambient, θ_{JA}	95	°C/W
L Package		
Thermal resistance-junction to case, θ_{JC}	35	°C/W
Thermal resistance-junction to ambient, θ_{JA}	120	°C/W

Notes:

1. Junction temperature calculation: $T_J = T_A + (P_D \times \theta_{JA})$
2. The above numbers for θ_{JC} are maximums for the limiting thermal resistance of the package in a standard mounting configuration. The θ_{JA} numbers are meant to be guidelines for the thermal performance of the device/pc-board system. All of the above assume no ambient airflow.

4. Recommended Operating Conditions

Table 4-1. Recommended Operating Conditions¹

Supply Voltage Range	Value	Units
±25% Maximum fault window ²	4.5 to 35	V
±40% Maximum fault window	5.0 to 35	V
Lower threshold input range	1.5 to 2.45	V
Fault tolerance window range	±5 to ±40	%
Fault output sink current range	0 to 10	mA
Line sense output current range	0 to 10	mA
Voltage reference output current	0 to 10	mA
Operating Ambient Temperature Range		
SG1548	-55 to 125	°C
SG2548	-25 to 85	°C
SG3548	0 to 70	°C

Notes:

1. Range over which the device is functional
2. Limited by inverter amplifier positive swing at -55 °C

5. Electrical Characteristics

Unless otherwise specified, these specifications apply over the operating ambient temperatures for SG1548 with $-55\text{ }^{\circ}\text{C} \leq T_A \leq 125\text{ }^{\circ}\text{C}$, SG2548 with $-25\text{ }^{\circ}\text{C} \leq T_A \leq 85\text{ }^{\circ}\text{C}$, SG3548 with $0\text{ }^{\circ}\text{C} \leq T_A \leq 70\text{ }^{\circ}\text{C}$, and $+V_{IN} = 15\text{V}$. Low duty cycle pulse testing techniques are used which maintains junction and case temperatures equal to the ambient temperature.

Parameter	Test Conditions	SG1548/2548			SG3548			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
Supply Section								
Supply current	+V _{IN} = 40V	—	4.8	10	—	4.8	10	mA
Reference Section ¹								
Output voltage	T _J = 25 °C	2.475	2.500	2.525	2.475	2.500	2.525	V
	Over temperature	2.450	—	2.550	2.450	—	2.550	V
Line regulation	+V _{IN} = 4.5V to 35V	—	1	5	—	1	5	mV
Load regulation	I _L = 0 to 10 mA	—	3	10	—	3	10	mV
Short circuit current	V _{REF} = 0V	10	25	50	10	25	50	mA
Fault Window Generator Section								
Input bias current	V _{PIN 1} = 1.5V to 2.45V	—	-0.4	-2.0	—	-0.4	-2.0	μA
DC Sense Inputs Section								
Overvoltage threshold	V _{PIN 1} = 0.95 × V _{REF}	2.547	2.625	2.704	2.547	2.625	2.704	V
	V _{PIN 1} = 0.60 × V _{REF}	3.396	3.500	3.606	3.396	3.500	3.606	V
Undervoltage threshold	V _{PIN 1} = 0.95 × V _{REF}	2.304	2.375	2.447	2.304	2.375	2.447	V
	V _{PIN 1} = 0.60 × V _{REF}	1.455	1.500	1.545	1.455	1.500	1.545	V
Input bias current	V _{SENSE} = 1.5V to 3.5V	—	±0.6	±2.0	—	±0.6	±2.0	μA
Threshold supply rejection	+V _{IN} = 4.5V to 35V	60	100	—	60	100	—	dB
Fault Delay Section								
Comparator threshold	—	1.200	1.250	1.300	1.200	1.250	1.300	V
Comparator hysteresis	—	—	25	—	—	25	—	mV
Delay charging current	V _{PIN 8} = 0V	32.5	50	67.5	32.5	50	67.5	μA
On saturation voltage	I _{PIN 8} = 0 mA	—	0.1	0.2	—	0.1	0.2	V
Off clamp voltage	I _{PIN 8} = 0 mA	—	+3.2	+3.6	—	+3.2	+3.6	V
Inverting Op Amp Section ²								
Input offset voltage	—	—	2	15	—	2	15	mV
Input bias current	—	—	-0.3	-1.0	—	-0.3	-1.0	μA
Output high voltage	I _{SOURCE} = 5 mA	3.2	3.5	—	3.2	3.5	—	V
Output low voltage	I _{SINK} = 5 mA	—	1.0	1.9	—	1.0	1.9	V
Large signal voltage gain	R _L = 10k	72	100	—	72	100	—	dB

.....continued

Parameter	Test Conditions	SG1548/2548			SG3548			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
Output source current	—	5	15	25	5	15	25	mA
Power supply rejection ratio	+V _{IN} = 4.5V to 35V	72	100	—	72	100	—	dB
AC Line Sense Section								
Comparator threshold	V _{PIN 5} = low to high	2.440	2.500	2.560	2.440	2.500	2.560	V
Comparator hysteresis	—	—	25	—	—	25	—	mV
Input bias current	V _{PIN 5} = 2.5V	—	1	2	—	1	2	μA
Collector leakage current	V _{CE} = 40V	—	1	10	—	1	10	μA
Collector saturation voltage	I _C = 10 mA	—	0.2	0.5	—	0.2	0.5	V
Emitter output voltage	I _E = 10 mA	12	13	—	12	13	—	V
Diode clamp voltage	I _{PIN 5} = 1 mA	6.0	—	7.5	6.0	—	7.5	V
	I _{PIN 5} = -1 mA	-0.3	—	-1.0	-0.3	—	-1.0	V
Fault Logic Outputs (Each output)								
Collector leakage current	V _C = 40V	—	1	10	—	1	10	μA
Collector saturation voltage	I _C = 10 mA	—	0.2	0.5	—	0.2	0.5	V

Notes:

1. I_L = 0 mA
2. +V_{IN} = 4.5V

6. Application Information

6.1 Setting the Fault Tolerance Window

The fault tolerance window is set by applying a voltage less than the +2.50V reference to the Lower Threshold input (Pin 1). The voltage is obtained by a resistor divider from the reference (Pin 3) to ground. If $\pm 5\%$ tolerance is desired, then 95% of the reference (+2.375V) is applied to Pin 1. If $\pm 40\%$ is wanted, then 60% of the reference (+1.50V) is applied. In the application example in [Figure 6-1](#), the tolerance is $\pm 5\%$. The nominal overvoltage and undervoltage thresholds are centered about the reference at +2.625V and +2.375V (+2.500V ± 0.125 V).

6.2 Scaling the Monitored Supply Voltages

Each positive voltage to be monitored is divided down to +2.50V with a resistor network and connected to one of the Sense inputs. Unused Sense inputs should be connected to the reference and will not increase the bias current. A variation of the monitored voltages out of the programmed tolerance range will cause the appropriate overvoltage or undervoltage fault output to switch LOW. The effective tolerance on any input may be broadened with an additional resistor to the voltage reference. The application example in [Figure 6-1](#) shows a $\pm 10\%$ tolerance on the +5V supply although the SG1548 is programmed for a $\pm 5\%$ tolerance. The procedure for calculating the resistor value is found in the SG1548 Application Note.

6.3 Monitoring a Negative Voltage

A negative voltage can be converted to a positive one and simultaneously scaled to +2.50V by using the internal operational amplifier as an inverter. Only an input resistor and feedback resistor are required.

6.4 Setting the Fault Delay

A single capacitor at the Delay pin sets the time an out-of tolerance fault must persist before a fault is actually declared. This feature allows switching noise on the supplies to be rejected. The delay time is given by: Delay = 25 ms/ μ F.


6.5 AC Line Monitoring

The AC line voltage can be monitored for single-cycle dropouts with the few components shown in the example. A half-wave rectifier charges the capacitor on positive line cycles. After the positive peak and during the negative line cycle, the capacitor discharges from a fixed voltage controlled by the internal Zener diode. If a positive cycle is missing, the capacitor discharges to below the +2.5V trip point of the comparator, causing the output transistor to turn on.

6.6 Application Example

In this example, the SG1548 simultaneously monitors four DC voltages: +5V, +24V, and ± 15 V. Three different fault tolerances are programmed: $\pm 5\%$ on the two 15V supplies, $\pm 10\%$ on the +5V supply, and $\pm 20\%$ on the +24V supply. The 5 μ F delay capacitor provides 125 milliseconds of fault delay.


Figure 6-1. Application Example



7. Package Outline Dimensions

Controlling dimensions are in inches; metric equivalents are shown for general information.

Figure 7-1. J 16-Pin Ceramic Dip




Dim. ¹	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	—	5.08	—	0.200
b	0.38	0.51	0.015	0.020
b2	1.04	1.65	0.045	0.065
c	0.20	0.38	0.008	0.015
D	19.30	19.94	0.760	0.785
E	5.59	7.11	0.220	0.280
e	2.54 BSC		0.100 BSC	
eA	7.37	7.87	0.290	0.310
H	0.63	1.78	0.025	0.070
L	3.18	5.08	0.125	0.200
α	—	15°	—	15°
Q	0.51	1.02	0.020	0.040

Note:

1. Dimensions do not include protrusions; these shall not exceed 0.155 mm (.006") on any side. Lead dimension shall not include solder coverage.

Figure 7-2. N 16-Pin Plastic Dip




Dim. ¹	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	—	5.33	—	0.210
A1	0.38	—	0.015	—
A2	3.30 Typ.		0.130 Typ.	
b	0.36	0.56	0.014	0.022
b1	1.14	1.78	0.045	0.070
c	0.20	0.36	0.008	0.014
D	18.67	19.69	0.735	0.775
e	2.54 BSC		0.100 BSC	
E	7.62	8.26	0.300	0.325
E1	6.10	7.11	0.240	0.280
L	2.92	0.381	0.115	0.150
θ	—	15°	—	15°

Note:

1. Dimensions do not include mold flash or protrusions; these shall not exceed 0.155 mm (.006") on any side. Lead dimension shall not include solder coverage.

Figure 7-3. DW 16-Pin Plastic Wide-Body SOIC




Dim. ^{1,2}	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	2.06	2.65	0.081	0.104
A1	0.10	0.30	0.004	0.012
A2	2.03	2.55	0.080	0.100
B	0.33	0.51	0.013	0.020
c	0.23	0.32	0.009	0.013
D	10.08	10.50	0.397	0.413
E	7.40	7.60	0.291	0.299
e	1.27 BSC		0.05 BSC	
H	10.00	10.65	0.394	0.419
L	0.40	1.27	0.016	0.050
θ	0°	8°	0°	8°
LC ³	—	0.10	—	0.004

Notes:

1. Controlled dimensions are in mm; inches are for reference only.
2. Dimensions do not include mold flash or protrusions; these shall not exceed 0.155 mm (.006") on any side. Lead dimension shall not include solder coverage.
3. Lead coplanarity

Figure 7-4. 20-Pin Ceramic Leadless Chip Carrier



Dim. ¹	Millimeters		Inches	
	Min.	Max.	Min.	Max.
D/E	8.64	9.14	0.340	0.360
E3	—	8.128	—	0.320
e	1.270 BSC		0.050 BSC	
B1	0.635 TYP		0.025 TYP	
L	1.02	1.52	0.040	0.060
A	1.626	2.286	0.064	0.090
h	1.016 TYP		0.040 TYP	
A1	1.372	1.68	0.054	0.066
A2	—	1.168	—	0.046
L2	1.91	2.41	0.075	0.95
B3	0.203R		0.008R	

Note:

1. All exposed metalized area shall be gold plated 60 micro-inch minimum thickness over nickel plated unless otherwise specified in purchase order.

8. Revision History

The revision history describes the changes that were implemented in the document. The changes are listed by revision, starting with the most current publication.

Revision	Date	Description
B	07/2024	Updated Figure 1 .
A	11/2023	Initial revision.

Microchip Information

The Microchip Website

Microchip provides online support via our website at www.microchip.com/. This website is used to make files and information easily available to customers. Some of the content available includes:

- **Product Support** – Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- **General Technical Support** – Frequently Asked Questions (FAQs), technical support requests, online discussion groups, Microchip design partner program member listing
- **Business of Microchip** – Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

Product Change Notification Service

Microchip's product change notification service helps keep customers current on Microchip products. Subscribers will receive email notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, go to www.microchip.com/pcn and follow the registration instructions.

Customer Support

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Embedded Solutions Engineer (ESE)
- Technical Support

Customers should contact their distributor, representative or ESE for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in this document.

Technical support is available through the website at: www.microchip.com/support

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
- Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip product is strictly prohibited and may violate the Digital Millennium Copyright Act.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is "unbreakable". Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.

Legal Notice

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure

that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at www.microchip.com/en-us/support/design-help/client-support-services.

THIS INFORMATION IS PROVIDED BY MICROCHIP "AS IS". MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP'S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Trademarks

The Microchip name and logo, the Microchip logo, Adaptec, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, CryptoMemory, CryptoRF, dsPIC, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Kleer, LANCheck, LinkMD, maXStylus, maXTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AgileSwitch, ClockWorks, The Embedded Control Solutions Company, EtherSynch, Flashtec, Hyper Speed Control, HyperLight Load, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, Quiet-Wire, SmartFusion, SyncWorld, TimeCesium, TimeHub, TimePictra, TimeProvider, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, Augmented Switching, BlueSky, BodyCom, Clockstudio, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, Espresso T1S, EtherGREEN, EyeOpen, GridTime, IdealBridge, IGaT, In-Circuit Serial Programming, ICSP, INICnet, Intelligent Paralleling, IntelliMOS, Inter-Chip Connectivity, JitterBlocker, Knob-on-Display, MarginLink, maxCrypto, maxView, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, mSiC, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, Power MOS IV, Power MOS 7, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, RTAX, RTG4, SAM-ICE, Serial Quad I/O, simpleMAP, SimpliPHY, SmartBuffer, SmartHLS, SMART-I.S., storClad, SQL, SuperSwitcher, SuperSwitcher II, Switchtec, SynchroPHY, Total Endurance, Trusted Time, TSHARC, Turing, USBCheck, VariSense, VectorBlox, VeriPHY, ViewSpan, WiperLock, XpressConnect, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, and Symmcom are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2014-2023, Microchip Technology Incorporated and its subsidiaries. All Rights Reserved.

ISBN: 978-1-6683-0036-7

Quality Management System

For information regarding Microchip's Quality Management Systems, please visit www.microchip.com/quality.

Worldwide Sales and Service

AMERICAS	ASIA/PACIFIC	ASIA/PACIFIC	EUROPE
Corporate Office 2355 West Chandler Blvd. Chandler, AZ 85224-6199 Tel: 480-792-7200 Fax: 480-792-7277 Technical Support: www.microchip.com/support Web Address: www.microchip.com	Australia - Sydney Tel: 61-2-9868-6733 China - Beijing Tel: 86-10-8569-7000 China - Chengdu Tel: 86-28-8665-5511 China - Chongqing Tel: 86-23-8980-9588 China - Dongguan Tel: 86-769-8702-9880 China - Guangzhou Tel: 86-20-8755-8029 China - Hangzhou Tel: 86-571-8792-8115 China - Hong Kong SAR Tel: 852-2943-5100 China - Nanjing Tel: 86-25-8473-2460 China - Qingdao Tel: 86-532-8502-7355 China - Shanghai Tel: 86-21-3326-8000 China - Shenyang Tel: 86-24-2334-2829 China - Shenzhen Tel: 86-755-8864-2200 China - Suzhou Tel: 86-186-6233-1526 China - Wuhan Tel: 86-27-5980-5300 China - Xian Tel: 86-29-8833-7252 China - Xiamen Tel: 86-592-2388138 China - Zhuhai Tel: 86-756-3210040	India - Bangalore Tel: 91-80-3090-4444 India - New Delhi Tel: 91-11-4160-8631 India - Pune Tel: 91-20-4121-0141 Japan - Osaka Tel: 81-6-6152-7160 Japan - Tokyo Tel: 81-3-6880-3770 Korea - Daegu Tel: 82-53-744-4301 Korea - Seoul Tel: 82-2-554-7200 Malaysia - Kuala Lumpur Tel: 60-3-7651-7906 Malaysia - Penang Tel: 60-4-227-8870 Philippines - Manila Tel: 63-2-634-9065 Singapore Tel: 65-6334-8870 Taiwan - Hsin Chu Tel: 886-3-577-8366 Taiwan - Kaohsiung Tel: 886-7-213-7830 Taiwan - Taipei Tel: 886-2-2508-8600 Thailand - Bangkok Tel: 66-2-694-1351 Vietnam - Ho Chi Minh Tel: 84-28-5448-2100	Austria - Wels Tel: 43-7242-2244-39 Fax: 43-7242-2244-393 Denmark - Copenhagen Tel: 45-4485-5910 Fax: 45-4485-2829 Finland - Espoo Tel: 358-9-4520-820 France - Paris Tel: 33-1-69-53-63-20 Fax: 33-1-69-30-90-79 Germany - Garching Tel: 49-8931-9700 Germany - Haan Tel: 49-2129-3766400 Germany - Heilbronn Tel: 49-7131-72400 Germany - Karlsruhe Tel: 49-721-625370 Germany - Munich Tel: 49-89-627-144-0 Fax: 49-89-627-144-44 Germany - Rosenheim Tel: 49-8031-354-560 Israel - Hod Hasharon Tel: 972-9-775-5100 Italy - Milan Tel: 39-0331-742611 Fax: 39-0331-466781 Italy - Padova Tel: 39-049-7625286 Netherlands - Drunen Tel: 31-416-690399 Fax: 31-416-690340 Norway - Trondheim Tel: 47-72884388 Poland - Warsaw Tel: 48-22-3325737 Romania - Bucharest Tel: 40-21-407-87-50 Spain - Madrid Tel: 34-91-708-08-90 Fax: 34-91-708-08-91 Sweden - Gothenberg Tel: 46-31-704-60-40 Sweden - Stockholm Tel: 46-8-5090-4654 UK - Wokingham Tel: 44-118-921-5800 Fax: 44-118-921-5820