

# File Transfer Protocol Using MPLAB Harmony v3 TCP/IP Stack for SAM E54 MCU

#### Introduction

The File Transfer Protocol (FTP) is a standard internet protocol provided by TCP/IP for transmitting files from one device to another. It is an application layer protocol within the TCP/IP stack layers. An embedded FTP client/server is an excellent addition to any network-enabled device. The FTP client module will enable your application to upload and download files from any FTP server. This protocol enables data transfer reliably and efficiently between different devices without worrying about the file storage systems of a Host.

This document focuses on the FTP implementation of the MPLAB<sup>®</sup> Harmony v3 TCP/IP stack. It also provides a combined FTP client and FTP server demonstration using the SAM E54 microcontroller. The FTP client application has an Ethernet bootloader that downloads the application binary from the FTP server and updates the firmware by self-programming.

#### **Abbreviations**

- · FTP: File Transfer Protocol
- HTTP: Hypertext Transfer Protocol
- TCP/IP: Transmission Control Protocol/Internet Protocol
- · DHCP: Dynamic Host Configuration Protocol
- DFP: Device Family Pack
- · MCC: MPLAB Code Configurator

# **Table of Contents**

troduction	1
FTP Overview	3
Application Overview	4
Hardware and Software Requirements	5
FTP in MPLAB Harmony v3	6
4.1. TCP/IP Configurator	6
4.2. FTP Server Module	7
4.3. FTP Client Module	7
FTP Client and Server: Application Implementation	10
5.1. MPLAB Harmony v3 Configuration	10
5.2. TCP/IP MPLAB Harmony v3 Configuration	10
5.3. Running the Application	
Appendix	19
6.1. Generating Application Binary Files (Test Application Configurations)	19
6.2. Self-Programming of Downloaded Binary	21
6.3. Application Code Entry	22
References	23
icrochip Information	24
The Microchip Website	24
•	
• •	
Legal Notice	
Trademarks	
Quality Management System	
Worldwide Sales and Service	
	FTP Overview

#### 1. FTP Overview

FTP is built on a client/server model architecture using separate control and data connections between the client and the server. An FTP client establishes a connection between a Host and a remote FTP server, providing dual-direction data transfer and files between two computers over TCP. It works when the client connects to the FTP server by specifying the domain, IP address, port, username, and password. After user authentication, a connection is established between both systems, and the Host computer can upload data onto the FTP server. There could be access restrictions, which the FTP server administrator determines for downloading the various files and folders residing on the FTP server.

The FTP relies on two connections between the client and server: a control connection for controlling the conversation and a data connection for transmitting file content. When an FTP session is started between a client and a server, the client initiates a control TCP connection with the server side. The client sends the control information over this. When the server receives the control information, it initiates a data connection to the client side. FTP sessions work in active or passive mode, determining how the data connection is established and whether the client/server initiates the transfer. Additional information on FTP modes and connections can be found in the FTP document AN3475.

# 2. Application Overview

This document demonstrates the use of an FTP server and an FTP client in a network by using two SAM E54 Xplained Pro Evaluation Kits, where one will be the FTP server and the other evaluation board will be the FTP client. Each FTP client and FTP server has its own file system media. The SD card on the IO1 Xpro board acts as the storage medium for the file system and is used by the client/server boards for the file transfer. This application mainly focuses on the FTP network where the client logs into the server and downloads the application binary file to load the application.

Figure 2-1. SAM E54 as Client and Server Model





Figure 2-2. Memory for Application and Bootloader



# 3. Hardware and Software Requirements

This section describes the hardware and software prerequisites used for this application.

#### Hardware:

- SAM E54 Xplained Pro Evaluation Kit 2 Nos
- IO1 Xplained Pro 2 Nos
- Micro SD card 2 Nos
- Ethernet cable (RJ45) 1 No
- USB cable 2 Nos

#### Software:

- MPLAB X IDE (v6.00)
- MPLAB XC32 compiler (v4.10)
- MPLAB Code Configurator (v5.1.17)
  - Harmony bsp repository v3.13.0 (Github bsp)
  - Harmony csp repository v3.13.1 (Github csp)
  - Harmony core repository v3.11.1 (Github core)
  - Harmony dev\_packs repository v3.13.0 (Github dev\_packs)
  - Harmony net repository v3.8.0 (Github net)
  - Harmony Crypto repository v3.7.6 (Github crypto)


# 4. FTP in MPLAB Harmony v3

The MPLAB Harmony v3 TCP/IP Stack Library provides the API of the FTP module with a convenient 'C' language interface. It supports the FTP server and client, which facilitates the upload and download of files.

### 4.1 TCP/IP Configurator


MPLAB Harmony v3 configuration uses an easy-to-use GUI, the MPLAB Code Configurator (MCC), which simplifies device setup, library selection, configuration, and application development. A TCP/IP Configurator plugin is available for the TCP/IP Configuration. This enables a user to graphically add or remove TCP/IP functionality to the MPLAB Harmony v3 project and configure each component per the application demand. The TCP/IP Configurator plugin can be selected from the Plugins drop-down list in the Project Graph window.

Figure 4-1. TCP/IP Configurator



The TCP/IP Configurator window initializes with a graphical overview of the different TCP/IP layers. Selecting each layer displays the available components. Choose the component needed for the application from the 'Available Components' list by clicking '+' or dragging and dropping to add selected components. A pop-up window will be shown for adding any unsatisfied dependencies on the component being selected. Select any added TCP/IP component and add the configuration in the 'Configuration Options' in the project Graph.

Figure 4-2. TCP/IP Configurator Overview




**Note:** The 'docs' folder in the local repository of 'net' contains more information on the configurator.

#### 4.2 FTP Server Module

The FTP server capability facilitates the uploading and downloading of files from an embedded device. The FTP TCP/IP stack library interface is defined in the ftp.h header file. To use the FTP server, the project requires using the TCP/IP stack and a file system (FAT FS in this project).

The FTP server can be enabled in the MPLAB Harmony v3 TCP/IP project using the MCC: *Project Graph > Plugin > TCP/IP Configuration > Application Layer > Add FTP Server.* 

Figure 4-3. FTP Server in TCP/IP Configurator



**Table 4-1. FTP Server Module Files** 


File	Description
ftp.h	Interface to the FTP server TCP/IP Stack library
ftp.c	Implementation of FTP server

#### 4.3 FTP Client Module

The FTP client module enables the transfer of data reliably and efficiently between different devices without worrying about the different file storage systems among Hosts. The FTP client TCP/IP stack library interface is defined in the ftpc.h header file.

The FTP client can be enabled in the MPLAB Harmony v3 TCP/IP project using the MCC: *Project Graph > Plugin > TCP/IP Configuration > Application Layer > Add FTP Client*.

Figure 4-4. FTP Client in TCP/IP Configurator



**Table 4-2. FTP Client Module Files** 

File	Description
ftpc.h	Interface to the FTP client TCP/IP stack library
ftpc.c	Implementation of the FTP client protocol

The following table displays the FTP commands supported by the FTPC module.

Table 4-3. FTP Commands Supported by the FTPC Module

FTP COMMAND	STACK COMMAND TYPE	FUNCTION NAME
USER: Send username	TCPIP_FTPC_CMD_USER	TCPIP_FTPC_Login
PASS: Send password	TCPIP_FTPC_CMD_PASS	TCPIP_FTPC_Login
ACCT: Send account information	TCPIP_FTPC_CMD_ACCT	TCPIP_FTPC_Login
TYPE: Set transfer type	TCPIP_FTPC_CMD_TYPE	TCPIP_FTPC_SetType
STRU: Set file transfer structure	TCPIP_FTPC_CMD_STRU	TCPIP_FTPC_SetStruct
MODE: Set transfer mode	TCPIP_FTPC_CMD_MODE	TCPIP_FTPC_SetMode
PASV: Enter passive mode	TCPIP_FTPC_CMD_PASV	TCPIP_FTPC_SetPassiveMode
PORT: Open a data port	TCPIP_FTPC_CMD_PORT	TCPIP_FTPC_Connect
RETR: Retrieve a remote file	TCPIP_FTPC_CMD_GET	TCPIP_FTPC_GetFile
STOR: Store a file on the remote host	TCPIP_FTPC_CMD_PUT	TCPIP_FTPC_PutFile
NLST: Name list of remote directories	TCPIP_FTPC_CMD_NLST	TCPIP_FTPC_NameList
LIST: List remote files	TCPIP_FTPC_CMD_LIST	TCPIP_FTPC_List
DELE: Delete a remote file	TCPIP_FTPC_CMD_DELE	TCPIP_FTPC_DeleteFile
CWD: Change working directory	TCPIP_FTPC_CMD_CWD	TCPIP_FTPC_Change_Dir
<b>CDUP:</b> CWD to the parent of the current directory	TCPIP_FTPC_CMD_CDUP	TCPIP_FTPC_ChangeToParentDir

continued			
FTP COMMAND	STACK COMMAND TYPE	FUNCTION NAME	
MKD: Make a remote directory	TCPIP_FTPC_CMD_MKD	TCPIP_FTPC_MakeDir	
RMD: Remove a remote directory	TCPIP_FTPC_CMD_RMD	TCPIP_FTPC_RemoveDir	
PWD: Print working directory	TCPIP_FTPC_CMD_PWD	TCPIP_FTPC_Get_WorkingDir	
QUIT: Terminate the connection	N/A	TCPIP_FTPC_Logout	

In addition to implementing the FTP commands, the client module provides a user interface through the USART terminal. This enables users to provide the required FTP command by entering the terminal. All FTP client commands start with the keyword 'ftpc', for example, ftpc login <username> cusername> cuserna


# 5. FTP Client and Server: Application Implementation

This section covers the prerequisites for creating the application.

### 5.1 MPLAB Harmony v3 Configuration

- To create a 32-bit MPLAB Harmony v3 project for the SAME54P20A using MPLAB X IDE, refer to https://microchipdeveloper.com/harmony3:same54-getting-started-training-module.
- By default, the Device Family Pack (DFP), System, CMSIS Pack, NVMCTRL and EVSYS will be present when the configuration is launched.
- The SD Card (SPI) Driver is added to provide the interface for the SD Card from the IO1 Xplained Pro Board.
- The System services, including the CONSOLE, COMMAND, DEBUG, TIME, File System, and TCP/IP features, must be added along with the required satisfiers as shown below.

Figure 5-1. FTP Client/Server Project Graph




### 5.2 TCP/IP MPLAB Harmony v3 Configuration

To configure TCP/IP Basic Configurator for client and server, use the following steps:


1. The TCP/IP Configurator will open a window as mentioned in the TCP/IP Configurator section. Once the selected contents are added, a view can be observed through the TCP/IP Configurator or the Project Graph. Different views can be selected through the Project Graph as shown in the following figure:

Figure 5-2. Selecting Views



2. In the Basic Configuration view, TCPIP CMD and TCPIP CORE components are enabled.

Figure 5-3. Basic Configurator



**Note:** In the TCP/IP CORE configuration options, the TCP/IP Stack Dynamic RAM size can be adjusted per the application requirement.

3. The network interface is configured to the necessary PHY connection in the Data Link configuration options. Ensure that the required network details, such as IP address and gateway address, are configured for both the client and the server. The internal ethernet driver (GMAC) is enabled with the KSZ8091 PHY driver for the SAME54 demonstration. The SAME54 Xplained Pro Evaluation Kit has the KSZ8091 present. The MIIM Driver supports asynchronous read/write and scan operations for accessing the external PHY registers and notifications when the MIIM operations have been completed.

Figure 5-4. Data Link Configuration





Figure 5-5. NETCONFIG Options



**Note:** This configuration of the network components can be done either by clicking the components on the project graph, or clicking the components in the TCP/IP configuration plugin. This is also applicable to other TCP/IP network components of the MPLAB Code Configurator's graphical user interface (GUI).


#### 5.2.1 FTP Server Configurations

#### **TCP/IP Application Layer Configuration**

Follow these steps to configure the TCP/IP Application Layer:


- In the TCP/IP Configuration window, under TCP/IP Layers, click "Application".
- In the Application Layer view, the TCP/IP Application Layer Configurator enables the following components: ANNOUNCE, FTP SERVER, DHCP Server, SNTP and DNS CLIENT.
- The ANNOUNCE module facilitates device discovery on the DHCP-enabled networks, while the DHCP CLIENT module allows the application to dynamically obtain an IP address from a DHCP server on the network.
   Note: The addition of the FTP server component would be sufficient for an FTP server project and the FTP client component would be sufficient for an FTP client project along with DNS. Those mentioned above are additional network protocols.

Figure 5-6. FTP Server Application Layer Configuration



 The FTP server uses the FAT FS to access files from SDCARD media. In the FTP SERVER configuration, configure the FTP server root directory path as shown in the following figure:

#### Figure 5-7. FTP Server Configuration



# 5.2.2 FTP Client Configuration

### **TCP/IP Application Layer Configuration**

Follow these steps to configure the TCP/IP Application Layer:

 For client, in the TCP/IP Application Layer Configurator, the ANNOUNCE, FTP CLIENT, and DHCP CLIENT components are enabled:

Figure 5-8. FTP Client Application Layer Configurator View



 In the FTP CLIENT Configuration, the Enable console commands option allows users to interact with the FTP client through a serial terminal. The transmit and receive buffer size can be increased as required (up to 1,024 bytes).

TCP/IP Configuration - beta + FTP CLIENT Overview **Available Components** Maximum number of simultaneous client Default Data Socket Transmit Buffer Size 1,024 Default Data Socket Receive Buffer Size 1,024 TCP/IP Layers Enable Console Commands **S** Application Advanced Settings -- FTPC Tick Rate (in msec) 5 💠 -FTP Request Time-out (in sec) 2 🛊 Presentation □ Data Link **Active Components** 

Figure 5-9. FTP Client Configuration

# 5.3 Running the Application

#### 5.3.1 Hardware Setup

Follow these steps to setting up the hardware:

- 1. Attach the IO1 Xpro board to the EXT1 of the SAME54 Xplained Pro Evaluation Kit.
- 2. Insert the Micro SD card into the Micro SD card slot on the backside of the IO1 Xpro boards. Ensure that the SD Card in the FTP Server contains the binary (test.bin) to be downloaded by the FTP Client.
- 3. Connect the micro-USB cable from the computer to the DEBUG USB connector on the SAM E54 Xplained Pro Evaluation Kit.
- 4. Connect the RJ45 ports of both SAM E54 Xplained Pro Evaluation Kits through the RJ45 cable, as shown in the following figure:



Figure 5-10. SAM E54 Client/Server Connection

#### 5.3.2 Programming the MCU

Follow these steps to program the MCU:

- 1. Download the FTP client and FTP server projects (provided with this document, alternatively users can download it here FTP Client and FTP Server).
- Open the project in MPLAB X IDE (File > Open Project and then browse to same54\_ftp\_client\firmware\ftp\_client\_sam\_e54\_xpro.X and same54\_ftp\_server\firmware\ftp\_server\_sam\_e54\_xpro.X).
- 3. Build and program the project to the target board by clicking (make and program device icon) for both boards, the client project (ftp\_client\_sam\_e54\_xpro) in one SAM E54 Xplained Pro Evaluation Kit board, and the server project (ftp\_server\_sam\_e54\_xpro) in the other.

#### 5.3.3 Connecting FTP Server

Follow these steps to connecting the FTP server:

- 1. Power up the FTP Server board through the Debug USB port.
- 2. Flash the FTP Server project in the SAM E54 Xplained Pro Evaluation Kit FTP Server Board and open the terminal (Tera Term) same54\_ftp\_server\firmware\ftp\_server\_sam\_e54\_xpro.X.
- 3. After Flashing, the FTP Server will complete the initialization and the console will print the server IP address as shown in the following figure.

Figure 5-11. FTP Server Console Output

```
COM12-Tera Term VT

File Edit Setup Control Window Help

TCP/IP Stack: Initialization Started

TCP/IP Stack: Initialization Ended - success

SYS_Initialize: The FATFS File System is mounted

Interface GMAC on host MCHPBOARD_C - NBNS disabled

GMAC IP Address: 192.168.100.12
```

**Note:** Before connecting to the SAM E54 FTP client project (Ethernet bootloader), copy the application binary file (same54\_ftp\_client/utilities/test.bin) to the MicroSD Card in the IO1 Xpro extension of the FTP Server board. This binary will be downloaded by the client and performs the bootloading.

#### 5.3.4 Connecting FTP Client

The user application for an FTP client must initiate the FTP connection request. Based on the server's response to the request, the client must provide the username and password for logging in. Data can be transferred between the server and the client when the FTP client is successfully logged in. (The user's own client/server, such as Windows Client, Embedded Server/Embedded Client, or Linux server, and so on can be used for the application).

In this application, the client downloads a binary file from the server and the downloaded file will be stored on an SD card on the IO1 Xpro of the client board. The binary is then programmed to the microcontroller.




Figure 5-12. Flow Diagram of FTP Bootloader in the FTP Client

Use the following steps to connect to the FTP client:

From a serial terminal window application (Tera Term), connect to the COM port enumerated by the SAM E54
Xplained Pro Evaluation Kit.

Reset

- 2. Restart the application (reset the SAM E54 Xplained Pro Evaluation Kit).
- 3. The IP address will be displayed on the terminal as shown in the following figure.

### Figure 5-13. FTP Client Initialization

```
COM11-Tera Term VT

File Edit Setup Control Window Help

TCP/IP Stack: Initialization Started

TCP/IP Stack: Initialization Ended - success

SYS Initialize: The FATFS File System is mounted

Interface GMAC on host MCHPBOARD_C - NBNS enabled

GMAC IP Address: 192.168.100.11

Connect to FTP server using ftpc commands

FG: ftpc connect 10.40.32.94
```

4. The user can then connect to the FTP server by typing: ftpc connect <server ip address>.

- 5. Upon successful connection, enter the login details: ftpc login <username> <password>.
- 6. Once logged in, use the following ftpc to get the command to download a binary from the server: ftpc get -a -a <test.bin>. The 'Command Success' indicates the binary is successfully downloaded.
- 7. Once the 'Command Success' message is received, enter the command 'boot'. The 'boot' is the command defined to start the bootloading of the downloaded binary.
- 8. The MCU is reset after the programming is complete and the application code starts executing.

#### Notes:

- The Binary files must be used for downloading and bootloading.
- The source code contains a same 54\_ftp\_client/utilities/test.bin for LED Flashing. This binary must be saved in the SD Card of the SAM E54 Xplained Pro Evaluation Kit programmed with the SAME54 FTP server project.

#### Figure 5-14. Output

```
COM11 - Tera Term VT
<u>F</u>ile <u>E</u>dit <u>S</u>etup C<u>o</u>ntrol <u>W</u>indow <u>H</u>elp
                                                             mounted
- NBNS enabled
                      red in
mmand to download binary
—a test.bin
              nand 'boot' after receiving 'Command Success' message
-a -a test.bin
       – Command Started
Command Ok
ORT 192,168,100,11,202,221
200 Command Ok
Length = 16
     File status okay; about to open data connection
                   512
340
Complete
Buffer Count: 3
 ommand Success
   pening file...
ad was successful. Now bootload
  ad was successful. Now bootload
le flashed
setting MCU to run application in 2
```

# 6. Appendix

### 6.1 Generating Application Binary Files (Test Application Configurations)

Typically, the embedded firmware has the bootloader programmed at the base address of the Flash memory. The application image follows the bootloader code in the Flash memory. To generate the binary file of an application project in MPLAB X IDE, perform the steps as shown in the following sections.

#### 6.1.1 Disable Generate Fuse Settings


Generally, the fuse configuration settings of the SAM MCU are programmed through the programming tool. The fuse settings are disabled in the test application, as the application is being programmed through the bootloader. Enabling the fuse settings increases the size of the binary file.

#### 6.1.2 Modify Application Start Address (Hex)

The application start address value must be equal to or greater than the Flash base address + bootloader size. It must match the value provided to the bootloader code during the generation. The bootloader will use the application start address value to jump to the application at the device reset.


The fuse settings and the application start address can be modified using the MCC. Launch the MCC and configure the 'System' component as shown in the following figure.

Figure 6-1. System Setting Configuration in MCC



To change the application's start address, navigate to *Project Properties > xc32-ld > Option categories: Symbols & Macros.* Users need to define the ROM\_ORIGIN and ROM\_LENGTH macros.

Figure 6-2. Project Properties




### 6.1.3 Generate the Binary File in MPLAB X IDE

To generate the binary file, follow these steps:

- 1. Go to Project Properties > Building.
- 2. Select Execute this line after build option, and then insert the following command:

```
${MP_CC_DIR}\xc32-objcopy -I ihex -O binary "${DISTDIR}/${PROJECTNAME}.$
{IMAGE_TYPE}.hex"
"${DISTDIR}/${PROJECTNAME}.${IMAGE_TYPE}.bin"
```


Figure 6-3. Bin File Generation



### 6.2 Self-Programming of Downloaded Binary

Users can download the required application binary from any FTP server (any FTP server can be used) using the FTP client application demonstrated in this document. Once the binary file is downloaded into the client file system, it can be programmed to the MCU's Flash memory, as shown in the following flow chart. Implementation of erasing and programming the Flash sector can be found in the  $APP_Flash_Task()$  function ( $same54_ftp_client\\firmware\\src\\app.c)$  in the source code of this application.

Figure 6-4. Programming the Binary



### 6.3 Application Code Entry

Upon every reset, the bootloader code checks for the following:

- User button press (SW0)
- A valid application code in the Flash address allocated for the application

If either of these conditions is true, the execution jumps to the user application code without executing the FTP client bootloader.

**Note:** For additional information, refer to this document AN3475.

### 7. References

- The Microchip TCP/IP stack: ww1.microchip.com/downloads/en/appnotes/00833c.pdf
- MPLAB® Harmony v3 TCP/IP Help: microchip-mplab-harmony.github.io/net/frames.html?frmname=topic&frmfile=index.html
- RFC 959: datatracker.ietf.org/doc/html/rfc959
- Harmony v3 Microchip Developer Help: microchipdeveloper.com/harmony3:start
- MPLAB Harmony GitHub wiki: github.com/Microchip-MPLAB-Harmony/Microchip-MPLAB-Harmony.github.io/wiki
- How to create first TCP/IP application: github.com/Microchip-MPLAB-Harmony/net/wiki/Create-your-first-tcpip-application
- MPLAB Harmony v2 to MPLAB Harmony v3 TCP/IP Application Migration Guide: microchip-mplab-harmony.github.io/quick\_docs/source/migration/tcpiip\_harmoy2\_to\_harmony\_3/readme.html
- Application Configuration Settings with Bootloader:
   microchip-mplab-harmony.github.io/bootloader\_apps\_uart/apps/docs/
   readme\_configure\_application\_sam.html#configuring-an-application-to-be-bootloaded-for-cortex-m-based-mcus
- MPLAB Harmony v3 is configurable through MPLAB Code Configurator (MCC). Refer to the below links for specific instructions to use MPLAB Harmony v3 with MCC.
  - Create a new MPLAB Harmony v3 project using MCC
  - Update and Configure an Existing MHC-based MPLAB Harmony v3 Project to MCC-based project
  - Getting Started with MPLAB Harmony v3 Using MPLAB Code Configurator
  - MPLAB Code Configurator Content Manager for MPLAB Harmony v3 Projects
- MPLAB® Code Configurator Overview with MPLAB Harmony Content: microchipdeveloper.com/harmony3:mcc-overview

# **Microchip Information**

# The Microchip Website

Microchip provides online support via our website at <a href="www.microchip.com/">www.microchip.com/</a>. This website is used to make files and information easily available to customers. Some of the content available includes:

- Product Support Data sheets and errata, application notes and sample programs, design resources, user's
  quides and hardware support documents, latest software releases and archived software
- General Technical Support Frequently Asked Questions (FAQs), technical support requests, online discussion groups, Microchip design partner program member listing
- Business of Microchip Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

# **Product Change Notification Service**

Microchip's product change notification service helps keep customers current on Microchip products. Subscribers will receive email notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, go to www.microchip.com/pcn and follow the registration instructions.

# **Customer Support**

Users of Microchip products can receive assistance through several channels:

- · Distributor or Representative
- Local Sales Office
- · Embedded Solutions Engineer (ESE)
- · Technical Support

Customers should contact their distributor, representative or ESE for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in this document.

Technical support is available through the website at: www.microchip.com/support

# Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
- Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code
  protection features of Microchip product is strictly prohibited and may violate the Digital Millennium Copyright
  Act
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code
  protection does not mean that we are guaranteeing the product is "unbreakable". Code protection is constantly
  evolving. Microchip is committed to continuously improving the code protection features of our products.

# **Legal Notice**

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded

by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at <a href="https://www.microchip.com/en-us/support/design-help/client-support-services">www.microchip.com/en-us/support/design-help/client-support-services</a>.

THIS INFORMATION IS PROVIDED BY MICROCHIP "AS IS". MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP'S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

#### **Trademarks**

The Microchip name and logo, the Microchip logo, Adaptec, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, CryptoMemory, CryptoRF, dsPIC, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Kleer, LANCheck, LinkMD, maXStylus, maXTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AgileSwitch, APT, ClockWorks, The Embedded Control Solutions Company, EtherSynch, Flashtec, Hyper Speed Control, HyperLight Load, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, Quiet- Wire, SmartFusion, SyncWorld, Temux, TimeCesium, TimeHub, TimePictra, TimeProvider, TrueTime, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, Anyln, AnyOut, Augmented Switching, BlueSky, BodyCom, Clockstudio, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, Espresso T1S, EtherGREEN, GridTime, IdealBridge, In-Circuit Serial Programming, ICSP, INICnet, Intelligent Paralleling, IntelliMOS, Inter-Chip Connectivity, JitterBlocker, Knob-on-Display, KoD, maxCrypto, maxView, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, RTAX, RTG4, SAM-ICE, Serial Quad I/O, simpleMAP, SimpliPHY, SmartBuffer, SmartHLS, SMART-I.S., storClad, SQI, SuperSwitcher, SuperSwitcher II, Switchtec, SynchroPHY, Total Endurance, Trusted Time, TSHARC, USBCheck, VariSense, VectorBlox, VeriPHY, ViewSpan, WiperLock, XpressConnect, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, and Symmcom are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2022, Microchip Technology Incorporated and its subsidiaries. All Rights Reserved.

ISBN: 978-1-6683-1675-7

# **Quality Management System**

For information regarding Microchip's Quality Management Systems, please visit www.microchip.com/quality.



# **Worldwide Sales and Service**

AMERICAS	ASIA/PACIFIC	ASIA/PACIFIC	EUROPE
Corporate Office	Australia - Sydney	India - Bangalore	Austria - Wels
2355 West Chandler Blvd.	Tel: 61-2-9868-6733	Tel: 91-80-3090-4444	Tel: 43-7242-2244-39
Chandler, AZ 85224-6199	China - Beijing	India - New Delhi	Fax: 43-7242-2244-393
ГеІ: 480-792-7200	Tel: 86-10-8569-7000	Tel: 91-11-4160-8631	Denmark - Copenhagen
Fax: 480-792-7277	China - Chengdu	India - Pune	Tel: 45-4485-5910
Technical Support:	Tel: 86-28-8665-5511	Tel: 91-20-4121-0141	Fax: 45-4485-2829
www.microchip.com/support	China - Chongqing	Japan - Osaka	Finland - Espoo
Web Address:	Tel: 86-23-8980-9588	Tel: 81-6-6152-7160	Tel: 358-9-4520-820
www.microchip.com	China - Dongguan	Japan - Tokyo	France - Paris
Atlanta	Tel: 86-769-8702-9880	Tel: 81-3-6880- 3770	Tel: 33-1-69-53-63-20
Ouluth, GA	China - Guangzhou	Korea - Daegu	Fax: 33-1-69-30-90-79
el: 678-957-9614	Tel: 86-20-8755-8029	Tel: 82-53-744-4301	Germany - Garching
ax: 678-957-1455	China - Hangzhou	Korea - Seoul	Tel: 49-8931-9700
Austin, TX	Tel: 86-571-8792-8115	Tel: 82-2-554-7200	Germany - Haan
Tel: 512-257-3370	China - Hong Kong SAR	Malaysia - Kuala Lumpur	Tel: 49-2129-3766400
Boston	Tel: 852-2943-5100	Tel: 60-3-7651-7906	Germany - Heilbronn
Vestborough, MA	China - Nanjing	Malaysia - Penang	Tel: 49-7131-72400
Tel: 774-760-0087	Tel: 86-25-8473-2460	Tel: 60-4-227-8870	Germany - Karlsruhe
ax: 774-760-0088	China - Qingdao	Philippines - Manila	Tel: 49-721-625370
Chicago	Tel: 86-532-8502-7355	Tel: 63-2-634-9065	Germany - Munich
tasca, IL	China - Shanghai	Singapore	Tel: 49-89-627-144-0
el: 630-285-0071	Tel: 86-21-3326-8000	Tel: 65-6334-8870	Fax: 49-89-627-144-44
Fax: 630-285-0075	China - Shenyang	Taiwan - Hsin Chu	Germany - Rosenheim
)allas	Tel: 86-24-2334-2829	Tel: 886-3-577-8366	Tel: 49-8031-354-560
Addison, TX	China - Shenzhen	Taiwan - Kaohsiung	Israel - Ra'anana
el: 972-818-7423	Tel: 86-755-8864-2200	Tel: 886-7-213-7830	Tel: 972-9-744-7705
Fax: 972-818-2924	China - Suzhou	Taiwan - Taipei	Italy - Milan
Detroit	Tel: 86-186-6233-1526	Tel: 886-2-2508-8600	Tel: 39-0331-742611
lovi, MI	China - Wuhan	Thailand - Bangkok	Fax: 39-0331-466781
el: 248-848-4000	Tel: 86-27-5980-5300	Tel: 66-2-694-1351	Italy - Padova
louston, TX	China - Xian	Vietnam - Ho Chi Minh	Tel: 39-049-7625286
el: 281-894-5983	Tel: 86-29-8833-7252	Tel: 84-28-5448-2100	Netherlands - Drunen
ndianapolis	China - Xiamen	161. 04-20-3440-2100	Tel: 31-416-690399
loblesville, IN	Tel: 86-592-2388138		Fax: 31-416-690340
el: 317-773-8323	China - Zhuhai		Norway - Trondheim
Eax: 317-773-5453	Tel: 86-756-3210040		Tel: 47-72884388
el: 317-536-2380	161. 00-7 30-32 10040		Poland - Warsaw
os Angeles			Tel: 48-22-3325737
Mission Viejo, CA			Romania - Bucharest
el: 949-462-9523			Tel: 40-21-407-87-50
Fax: 949-462-9608			
			<b>Spain - Madrid</b> Tel: 34-91-708-08-90
el: 951-273-7800			
Raleigh, NC			Fax: 34-91-708-08-91
el: 919-844-7510			Sweden - Gothenberg
lew York, NY			Tel: 46-31-704-60-40
el: 631-435-6000			Sweden - Stockholm
San Jose, CA			Tel: 46-8-5090-4654
el: 408-735-9110			UK - Wokingham
Tel: 408-436-4270			Tel: 44-118-921-5800
Canada - Toronto			Fax: 44-118-921-5820
Геl: 905-695-1980			
Fax: 905-695-2078			