
16-Bit Digital Signal Controller with High-Speed PWM, Op Amps, Advanced Analog, MOSFET Driver and LIN Transceiver

Operating Conditions

- Host dsPIC® DSC Core:
 - 3.0V to 3.6V, -40°C to +125°C, DC to 100 MIPS
- MOSFET Gate Driver module:
 - 6.25V to 29.0V, -40°C to +125°C
 - Fixed output linear regulator, 3.3V @ 70mA
- LIN Transceiver module:
 - 5.0V to 28V supply voltage
 - Up to 40.0V LIN bus voltage

Core: 16-Bit dsPIC33C CPU

- 64 Kbytes of Program Flash with ECC and 8K RAM Memory with Built-In Self-Test (MBIST)
- Fast Six-Cycle Divide
- Code Efficient (C and Assembly) Architecture
- 40-Bit Wide Accumulators
- Single-Cycle (MAC/MPY) with Dual Data Fetch
- Single-Cycle, Mixed-Sign MUL Plus Hardware Divide
- 32-Bit Multiply Support
- Four Sets of Interrupt Context Saving Registers which Include Accumulator and STATUS for Fast Interrupt Handling
- Zero Overhead Looping

Clock Management

- 2% Internal Oscillator
- Programmable PLLs and Oscillator Clock Sources
- Reference Clock Output
- Fail-Safe Clock Monitor (FSCM)
- Fast Wake-up and Start-up
- Backup Internal Oscillator

Power Management

- Low-Power Management Modes (Sleep, Idle, Doze)
- Integrated Power-on Reset and Brown-out Reset

High-Speed PWM

- Four PWM Pairs
- Up to 2 ns PWM Resolution
- Dead Time for Rising and Falling Edges
- Dead-Time Compensation
- Clock Chopping for High-Frequency Operation
- PWM Support for:
 - BLDC, PMSM, IPM, ACIM, SRM and stepper motors
 - DC/DC, AC/DC, inverters, PFC, lighting
- Fault and Current Limit Inputs
- Flexible Trigger Configuration for ADC Triggering

Timers/Output Compare/Input Capture

- One General Purpose Timer:
 - Two 16-bit or one 32-bit timer/counter
- Peripheral Trigger Generator (PTG):
 - Up to 15 trigger sources to other peripheral modules
 - CPU independent state machine-based instruction sequencer
- Four SCCP modules which Include Timer, Capture/Compare and PWM:
 - 16 or 32-bit time base
 - 16 or 32-bit capture
 - 4-deep capture buffer
 - One PWM output
- Fully Asynchronous Operation, Available in Sleep Modes

Input/Output

- Sink/Source: 12 mA or 6 mA, Pin-Specific for Standard VOH/VOL, Up to 22 or 14 mA, respectively, for Non-Standard VOH1
- 5V Tolerant Pins
- Peripheral Pin Select (PPS) to allow Digital Function Remapping
- Selectable Open-Drain Pull-ups and Pull-Downs
- Up to 5 mA Overvoltage Clamp Current
- Change Notification Interrupts on All I/O Pins
- Programmable Cyclic Redundancy Check (CRC)

dsPIC33CDVL64MC106

Advanced Analog Features

- High-Speed ADC module:
 - 12-bit with dedicated SAR ADC core
 - Configurable resolution (up to 12-bit)
 - Up to 3.5 Msps conversion rate per channel at 12-bit resolution
 - Up to 15 input channels
 - Dedicated result buffer for each analog channel
 - Flexible and independent ADC trigger sources
 - Four digital comparators
 - Four oversampling filters for increased resolution
- One Analog Comparator with PDM DAC with Slope Compensation:
 - 15 ns analog comparator
- 12-Bit DAC:
 - Hardware slope compensation
- Up to Three Op Amps

Communication Interfaces

- Three Protocol UARTs with Automated Protocol Handling Support for:
 - LIN 2.2
 - DMX
- Two Four-Wire SPI/I²S modules
- I²C module with SMBus Support
- SENT module

Direct Memory Access (DMA)

- Four DMA Channels

Debugger Development Support

- In-Circuit and In-Application Programming and Debugging
- Three Complex, Five Simple Breakpoints
- IEEE 1149.2 Compatible (JTAG) Boundary Scan
- Trace Buffer and Run-Time Watch

Safety Features

- Clock Monitor System with Backup Oscillator
- DMT (Deadman Timer)
- ECC (Error Correcting Code)
- WDT (Watchdog Timer)
- CodeGuard™ Security
- CRC (Cyclic Redundancy Check)
- ICSP™ Write Inhibit
- RAM Memory Built-In Self-Test (MBIST)
- Two-Speed Start-up
- Fail-Safe Clock Monitoring (FSCM)
- Backup FRC (BFRC)
- Capless Internal Voltage Regulator
- Virtual Pins for Redundancy and Monitoring

MOSFET Gate Driver Module (Based on MCP8021 Device)

- Three Half-Bridge Drivers Configured to Drive External High-Side NMOS and Low-Side NMOS MOSFETs:
 - Peak output current: 0.5A @ 12V
 - Shoot-through protection
 - Overcurrent and short-circuit protection

Fixed Output Linear Regulator

- 3.3V @ 70 mA
- True Current Foldback

Protection Features

- Gate Drive Undervoltage Lockout: 4.5V
- Supply Voltage Undervoltage Shutdown: 4.5V
- Supply Voltage Undervoltage Lockout (UVLO): 6.25V
- Overvoltage Lockout (OVLO): 32V
- Transient (100 ms) Voltage Tolerance: 40V
- Power Module Thermal Shutdown

LIN Transceiver Module (Based on ATA663211 Device)

- LIN_BUS Voltage up to 40V
- LIN_VDD Voltage = 5V to 28V
- Very Low Supply Current:
 - Sleep mode: typically 9 μ A
 - Fail-Safe mode: typically 80 μ A
 - Normal mode: typically 250 μ A
- Fully Compatible with 3.3V and 5V Devices
- LIN Physical Layer According to LIN 2.0, 2.1, 2.2, 2.2A and SAEJ2602-2
- Wake-up Capability via LIN_BUS Activity (100 μ s dominant)
- External Wake-up via LIN_WKIN Pin (100 μ s low level)

Functional Safety

- Class B Safety Library – IEC 60730
- For ASIL B and Beyond Applications – ISO 26262
- FMEDA Computation Spreadsheet (Evaluation of Random Hardware Failures Metric)
- Functional Safety Manual
- Functional Safety Diagnostics Suite

Qualification Support

- AEC-Q100 REV-H (Grade 1: -40°C to +125°C) Compliant

dsPIC33CDVL64MC106

dsPIC33CDVL64MC106

The dsPIC33CDVL64MC106 device features are listed in [Table 1](#).

TABLE 1: dsPIC33CDVL64MC106 DEVICE FEATURES


Device	Pins	Flash (Kbytes)	SRAM (Kbytes)	DMA # of Ch	GPIO/PPS	16-Bit Timer	SCCP	UART	SPI	I ² C	SENT	MC PWM	PWM Res (nS)	QEI	12-Bit ADC Module	ADC Channels	OP Amp	Analog Comp w/12-Bit DAC	PTG	CLC	REFO	CRC	WDT/DMT	Package
dsPIC33CDVL64MC106	64	64	8	4	27/22	1	4	3	2	1	1	4x2	2	1	1	15	3	1	1	4	1	1	1/1	QFN

dsPIC33CDVL64MC106

Pin Diagram

64-Pin QFN

■ = 5.5 Vdc Tolerant



- Note 1:** These pins are specific to the MOSFET gate driver module.
- Note 2:** These pins are specific to the LIN transceiver module.
- Note 3:** Pin is connected to a device interconnect; see [Table 3](#) for more information.
- Note 4:** Pin has no electrical connection to the device, but is recommended to be connected to Vss/LIN_Vss in the PCB design to improve thermal dissipation.

dsPIC33CDVL64MC106

TABLE 2: dsPIC33CDVL64MC106 COMPLETE PIN FUNCTIONS

Pin	Function	Pin	Function
1	LSA	35	RP56 /ASDA1/SCK2/RC8
2	LSB	36	RP57 /ASCL1/SDI2/RC9
3	LSC	37	RP72 /PCI19/SDO2/RD8
4	VBOOT	38	Vss
5	HVss	39	VDD
6	VREG	40	PGD3/ RP37 /RB5
7	HVDD	41	PGC3/ RP38 /RB6
8	CAP2	42	TDO/AN2/ RP39 /RB7
9	CAP1	43	PGD1/AN10/ RP40 /SCL1/RB8
10	N/C ⁽¹⁾	44	PGC1/AN11/ RP41 /SDA1/RB9
11	MCLR	45	RP52 /RC4
12	Vss	46	LIN_RXD ⁽¹⁾
13	ANN0/ RP77 /RD13	47	LIN_WKIN
14	AN12/ RP48 /RC0	48	LIN_Vss
15	OA1OUT/AN0/CMP1A/IBIAS0/RA0	49	LIN_BUS
16	OA1IN-/RA1	50	LIN_VDD
17	OA1IN+/AN9/RA2	51	LIN_INH
18	DACOUT/AN3/CMP1C/RA3	52	VDD
19	OA3OUT/AN4/IBIAS3/RA4	53	N/C ⁽¹⁾
20	AVDD	54	N/C ⁽¹⁾
21	AVss	55	WAKE
22	OA3IN-/AN13/CMP1B/ISRC0/ RP49 /RC1	56	PHA
23	OA3IN+/AN14/ISRC1/ RP50 /RC2	57	HSA
24	IBIAS1/ RP54 /RC6	58	VBA
25	VDD	59	PHB
26	Vss	60	HSB
27	AN15/IBIAS2/ RP51 /RC3	61	VBB
28	OSCI/CLKI/AN5/ RP32 /RB0	62	PHC
29	OSCO/CLKO/AN6/ RP33 /RB1	63	HSC
30	ISRC3/ RP74 /RD10	64	VBC
31	ISRC2/ RP55 /RC7	65	Vss ⁽²⁾
32	OA2OUT/AN1/AN7/CMP1D/ RP34 /INT0/RB2	66	HVss ⁽²⁾
33	PGD2/OA2IN-/AN8/ RP35 /RB3	67	N/C ⁽³⁾
34	PGC2/OA2IN+/ RP36 /RB4		

Legend: **RPn** represents remappable pins for the Peripheral Pin Select (PPS) function.


Note 1: Pin is connected to a device interconnect; see [Table 3](#) for more information.

2: Pin is connected to a device exposed pad.

3: Pin has no electrical connection to the device, but is recommended to be connected to Vss/LIN_Vss in the PCB design to improve thermal dissipation.

dsPIC33CDVL64MC106

FIGURE 1: dsPIC33CDVL64MC106 DEVICE INTERNAL CONNECTIONS BLOCK DIAGRAM⁽¹⁾



dsPIC33CDVL64MC106

TABLE 3: dsPIC33CDVL64MC106 DEVICE INTERCONNECTIONS

Host dsPIC® DSC to MOSFET Gate Driver	I/O	Interconnect Description
RB10/PWM3H to PWMCH ⁽¹⁾	O I	Digital output, configured when PWM output is enabled; Digital input, Phase C high-side control, internal 47 kΩ pull-down
RB11/PWM3L to PWMCL	O I	Digital output, configured when PWM output is enabled; Digital input, Phase C low-side control, internal 47 kΩ pull-down
RB12/PWM2H to PWMBH ⁽¹⁾	O I	Digital output, configured when PWM output is enabled; Digital input, Phase B high-side control, internal 47 kΩ pull-down
RB13/PWM2L to PWMBL	O I	Digital output, configured when PWM output is enabled; Digital input, Phase B low-side control, internal 47 kΩ pull-down
RD1 to FAULT	I O	Configure as digital input, use internal pull-up; Digital output, active-low Fault, open-drain
RC12/RP60 to DE2	I/O I/O	Configure as half-duplex UART, use PPS and internal pull-up; Digital communications port, open-drain
RB14/PWM1H to PWMAH ⁽¹⁾	O I	Digital output, configured when PWM output is enabled; Digital input, Phase A high-side control, internal 47 kΩ pull-down
RB15/PWM1L to PWMAL	O I	Digital output, configured when PWM output is enabled; Digital input, Phase A low-side control, internal 47 kΩ pull-down
RC13 to OE	O I	Configure as digital output; Digital input, output enable, Fault clearing, internal 47 kΩ pull-down
Host dsPIC® DSC to LIN Transceiver	I/O	Interconnect Description
RC10 to LIN_EN	O I	Configure as digital output; Digital input, enable signal
RC5/RP53 to LIN_TXD	O I	Configure as UART TX, use PPS; Transmit data input from microcontroller
RC11/RP59 to LIN_RXD ⁽¹⁾	I O	Configure as UART RX, use PPS; Receive data output to microcontroller, use 4.7 kΩ external pull-up and 20 pF load capacitor


Note 1: Interconnect is also bonded to an external device pin.

dsPIC33CDVL64MC106

Package Details

64-Lead Very Thin Grid Array Quad Flat Pack No-Lead (M8) - 9x9x0.927 mm Body [VGQFN] With Multiple Exposed Pads and Stepped Wettable Flanks

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Microchip Technology Drawing C04-530-M8 Rev B Sheet 1 of 2

dsPIC33CDVL64MC106

64-Lead Very Thin Grid Array Quad Flat Pack No-Lead (M8) - 9x9x0.927 mm Body [VGQFN] With Multiple Exposed Pads and Stepped Wettable Flanks

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N	64		
Pitch	e	0.50 BSC		
Overall Height	A	0.827	0.877	0.927
Standoff	A1	0.00	0.02	0.05
Terminal Thickness	A3	0.127 REF		
Overall Length	D	9.00 BSC		
Exposed Pad Length	D2	1.99	2.09	2.19
Exposed Pad Length	D3	2.40	2.50	2.60
Exposed Pad Length	D4	1.73	1.83	1.93
Overall Width	E	9.00 BSC		
Exposed Pad Width	E2	3.33	3.43	3.53
Exposed Pad Width	E3	2.40	2.50	2.60
Exposed Pad Width	E4	1.20	1.30	1.40
Terminal Width	b	0.20	0.25	0.30
Terminal Length	L	0.30	0.40	0.50
Exposed Pad Corner Chamfer	CH	0.35 REF		
Wettable Flank Step Cut Length	D5	0.03	0.07	0.11
Wettable Flank Step Cut Height	A4	0.05	-	-

Notes:


1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package is saw singulated
3. Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-530-M8 Rev B Sheet 2 of 2

dsPIC33CDVL64MC106

64-Lead Very Thin Grid Array Quad Flat Pack No-Lead (M8) - 9x9x0.927 mm Body [VGQFN] With Multiple Exposed Pads and Stepped Wettable Flanks

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



Dimension Limits	Units	MILLIMETERS		
		MIN	NOM	MAX
Contact Pitch	E	0.50 BSC		
Center Pad Width	X2			2.19
Center Pad Length	Y2			3.53
Center Pad Width	X3			2.60
Center Pad Length	Y3			2.60
Center Pad Width	X4			1.93
Center Pad Length	Y4			1.40
Contact Pad Spacing	C1		8.90	
Contact Pad Spacing	C2		8.90	
Contact Pad Width (Xnn)	X1			0.30
Contact Pad Length (Xnn)	Y1			0.85
Contact Pad to Center Pad	G1	0.53		
Contact Pad to Center Pad	G2	0.53		
Contact Pad to Center Pad	G3	0.50		
Contact Pad to Center Pad	G4	0.86		
Contact Pad to Center Pad	G5	1.38		
Contact Pad to Center Pad	G6	1.67		
Contact Pad to Contact Pad	G7	0.20		
Thermal Via Diameter	V		0.30	
Thermal Via Pitch	EV		1.00	

Notes:


- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-2530-M8 Rev B

dsPIC33CDVL64MC106

64-Lead Very Thin Grid Array Quad Flat Pack No-Lead (PSX) - 9x9x0.927 mm Body [VGQFN] With Multiple Exposed Pads and Stepped Wettable Flanks

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>




Microchip Technology Drawing C04-530-PSX Rev B Sheet 1 of 2

dsPIC33CDVL64MC106

64-Lead Very Thin Grid Array Quad Flat Pack No-Lead (PSX) - 9x9x0.927 mm Body [VGQFN] With Multiple Exposed Pads and Stepped Wettable Flanks

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N	64		
Pitch	e	0.50 BSC		
Overall Height	A	0.827	0.877	0.927
Standoff	A1	0.00	0.02	0.05
Terminal Thickness	A3	0.127 REF		
Overall Length	D	9.00 BSC		
Exposed Pad Length	D2	1.99	2.09	2.19
Exposed Pad Length	D3	2.40	2.50	2.60
Exposed Pad Length	D4	1.73	1.83	1.93
Overall Width	E	9.00 BSC		
Exposed Pad Width	E2	3.33	3.43	3.53
Exposed Pad Width	E3	2.40	2.50	2.60
Exposed Pad Width	E4	1.20	1.30	1.40
Terminal Width	b	0.20	0.25	0.30
Terminal Length	L	0.30	0.40	0.50
Exposed Pad Corner Chamfer	CH	0.35 REF		
Wettable Flank Step Cut Length	D5	0.03	0.07	0.11
Wettable Flank Step Cut Height	A4	0.05	-	-

Notes:


- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package is saw singulated
- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-530-PSX Rev B Sheet 2 of 2

dsPIC33CDVL64MC106

64-Lead Very Thin Grid Array Quad Flat Pack No-Lead (PSX) - 9x9x0.927 mm Body [VGQFN] With Multiple Exposed Pads and Stepped Wettable Flanks

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E	0.50 BSC		
Center Pad Width	X2			2.19
Center Pad Length	Y2			3.53
Center Pad Width	X3			2.60
Center Pad Length	Y3			2.60
Center Pad Width	X4			1.93
Center Pad Length	Y4			1.40
Contact Pad Spacing	C1		8.90	
Contact Pad Spacing	C2		8.90	
Contact Pad Width (Xnn)	X1			0.30
Contact Pad Length (Xnn)	Y1			0.85
Contact Pad to Center Pad	G1	0.53		
Contact Pad to Center Pad	G2	0.53		
Contact Pad to Center Pad	G3	0.50		
Contact Pad to Center Pad	G4	0.86		
Contact Pad to Center Pad	G5	1.38		
Contact Pad to Center Pad	G6	1.67		
Contact Pad to Contact Pad	G7	0.20		
Thermal Via Diameter	V		0.30	
Thermal Via Pitch	EV		1.00	

Notes:

- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-2530-PSX Rev B

dsPIC33CDVL64MC106

NOTES:

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
 - Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
 - Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip product is strictly prohibited and may violate the Digital Millennium Copyright Act.
 - Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is “unbreakable”. Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.
-

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at <https://www.microchip.com/en-us/support/design-help/client-support-services>.

THIS INFORMATION IS PROVIDED BY MICROCHIP “AS IS”. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP’S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer’s risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

For information regarding Microchip’s Quality Management Systems, please visit www.microchip.com/quality.

Trademarks

The Microchip name and logo, the Microchip logo, Adaptec, AnyRate, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, CryptoMemory, CryptoRF, dsPIC, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Klear, LANCheck, LinkMD, maxStylus, maxTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AgileSwitch, APT, ClockWorks, The Embedded Control Solutions Company, EtherSynch, Flashtec, Hyper Speed Control, HyperLight Load, IntelliMOS, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, Quiet-Wire, SmartFusion, SyncWorld, Temux, TimeCesium, TimeHub, TimePictra, TimeProvider, TrueTime, WinPath, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, Augmented Switching, BlueSky, BodyCom, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, Espresso T1S, EtherGREEN, GridTime, IdealBridge, In-Circuit Serial Programming, ICSP, INICnet, Intelligent Paralleling, Inter-Chip Connectivity, JitterBlocker, Knob-on-Display, maxCrypto, maxView, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, NVM Express, NVMe, Omniscent Code Generation, PICDEM, PICDEM.net, PICKit, PICTail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, RTAX, RTG4, SAM-ICE, Serial Quad I/O, simpleMAP, SimpliPHY, SmartBuffer, SmartHLS, SMART-I.S., storClad, SQL, SuperSwitcher, SuperSwitcher II, Switchtec, SynchroPHY, Total Endurance, TSHARC, USBCheck, VariSense, VectorBlox, VeriPHY, ViewSpan, WiperLock, XpressConnect, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, Symmcom, and Trusted Time are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2020-2021, Microchip Technology Incorporated and its subsidiaries.

All Rights Reserved.

ISBN: 978-1-5224-9184-2

Worldwide Sales and Service

AMERICAS

Corporate Office
2355 West Chandler Blvd.
Chandler, AZ 85224-6199
Tel: 480-792-7200
Fax: 480-792-7277
Technical Support:
<http://www.microchip.com/support>
Web Address:
www.microchip.com

Atlanta
Duluth, GA
Tel: 678-957-9614
Fax: 678-957-1455

Austin, TX
Tel: 512-257-3370

Boston
Westborough, MA
Tel: 774-760-0087
Fax: 774-760-0088

Chicago
Itasca, IL
Tel: 630-285-0071
Fax: 630-285-0075

Dallas
Addison, TX
Tel: 972-818-7423
Fax: 972-818-2924

Detroit
Novi, MI
Tel: 248-848-4000

Houston, TX
Tel: 281-894-5983

Indianapolis
Noblesville, IN
Tel: 317-773-8323
Fax: 317-773-5453
Tel: 317-536-2380

Los Angeles
Mission Viejo, CA
Tel: 949-462-9523
Fax: 949-462-9608
Tel: 951-273-7800

Raleigh, NC
Tel: 919-844-7510

New York, NY
Tel: 631-435-6000

San Jose, CA
Tel: 408-735-9110
Tel: 408-436-4270

Canada - Toronto
Tel: 905-695-1980
Fax: 905-695-2078

ASIA/PACIFIC

Australia - Sydney
Tel: 61-2-9868-6733

China - Beijing
Tel: 86-10-8569-7000

China - Chengdu
Tel: 86-28-8665-5511

China - Chongqing
Tel: 86-23-8980-9588

China - Dongguan
Tel: 86-769-8702-9880

China - Guangzhou
Tel: 86-20-8755-8029

China - Hangzhou
Tel: 86-571-8792-8115

China - Hong Kong SAR
Tel: 852-2943-5100

China - Nanjing
Tel: 86-25-8473-2460

China - Qingdao
Tel: 86-532-8502-7355

China - Shanghai
Tel: 86-21-3326-8000

China - Shenyang
Tel: 86-24-2334-2829

China - Shenzhen
Tel: 86-755-8864-2200

China - Suzhou
Tel: 86-186-6233-1526

China - Wuhan
Tel: 86-27-5980-5300

China - Xian
Tel: 86-29-8833-7252

China - Xiamen
Tel: 86-592-2388138

China - Zhuhai
Tel: 86-756-3210040

ASIA/PACIFIC

India - Bangalore
Tel: 91-80-3090-4444

India - New Delhi
Tel: 91-11-4160-8631

India - Pune
Tel: 91-20-4121-0141

Japan - Osaka
Tel: 81-6-6152-7160

Japan - Tokyo
Tel: 81-3-6880-3770

Korea - Daegu
Tel: 82-53-744-4301

Korea - Seoul
Tel: 82-2-554-7200

Malaysia - Kuala Lumpur
Tel: 60-3-7651-7906

Malaysia - Penang
Tel: 60-4-227-8870

Philippines - Manila
Tel: 63-2-634-9065

Singapore
Tel: 65-6334-8870

Taiwan - Hsin Chu
Tel: 886-3-577-8366

Taiwan - Kaohsiung
Tel: 886-7-213-7830

Taiwan - Taipei
Tel: 886-2-2508-8600

Thailand - Bangkok
Tel: 66-2-694-1351

Vietnam - Ho Chi Minh
Tel: 84-28-5448-2100

EUROPE

Austria - Wels
Tel: 43-7242-2244-39
Fax: 43-7242-2244-393

Denmark - Copenhagen
Tel: 45-4485-5910
Fax: 45-4485-2829

Finland - Espoo
Tel: 358-9-4520-820

France - Paris
Tel: 33-1-69-53-63-20
Fax: 33-1-69-30-90-79

Germany - Garching
Tel: 49-8931-9700

Germany - Haan
Tel: 49-2129-3766400

Germany - Heilbronn
Tel: 49-7131-72400

Germany - Karlsruhe
Tel: 49-721-625370

Germany - Munich
Tel: 49-89-627-144-0
Fax: 49-89-627-144-44

Germany - Rosenheim
Tel: 49-8031-354-560

Israel - Ra'anana
Tel: 972-9-744-7705

Italy - Milan
Tel: 39-0331-742611
Fax: 39-0331-466781

Italy - Padova
Tel: 39-049-7625286

Netherlands - Drunen
Tel: 31-416-690399
Fax: 31-416-690340

Norway - Trondheim
Tel: 47-7288-4388

Poland - Warsaw
Tel: 48-22-3325737

Romania - Bucharest
Tel: 40-21-407-87-50

Spain - Madrid
Tel: 34-91-708-08-90
Fax: 34-91-708-08-91

Sweden - Gothenberg
Tel: 46-31-704-60-40

Sweden - Stockholm
Tel: 46-8-5090-4654

UK - Wokingham
Tel: 44-118-921-5800
Fax: 44-118-921-5820