



Pushing Performance  
Since 1945

# Han Q5/0\_I\_F\_PIT\_0.5-2.5mm²



Image is for illustration purposes only. Please refer to product description.

Part number	09 12 005 5101
Specification	Han Q5/0_I_F_PIT_0.5-2.5mm²
HARTING eCatalogue	<a href="https://b2b.harting.com/09120055101">https://b2b.harting.com/09120055101</a>

## Identification

Category	Inserts
Series	Han® Q
Identification	5/0

## Version

Termination method	Push-In
Gender	Female
Size	3 A
Number of contacts	5
PE contact	Yes

## Technical characteristics

Conductor cross-section	0.5 ... 2.5 mm²
Rated current	16 A
Rated voltage conductor-earth	230 V
Rated voltage conductor-conductor	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Insulation resistance	>10 <sup>10</sup> Ω
Limiting temperature	-40 ... +125 °C
Mating cycles	≥500



**Pushing Performance**  
Since 1945

## Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

## Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
----------------	--------------------------

## Commercial data

Packaging size	10
Net weight	21 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140447905
eCl@ss	27440205 Contact insert for industrial connectors

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HARTING:](#)

[09120055101](#)