

**AEC-Q200**

### Wire-wound Common Mode Choke VFB4532 V Series


#### ■ Features

- Operating temperature -40°C~150°C
- Suitable for lead-free reflow soldering
- Compliance with RoHS and Halogen Free
- Bifilar winding
- AEC-Q200 qualified



#### ■ Application

- Used radiation noise suppression for automotive CAN-BUS / CAN-FD / Flex Ray systems
- Used for Industrial field bus systems


#### ■ Outline Dimensions




Code	Dimensions (mm)
A	5.2 Max
B	4.5 ± 0.2
C	0.8 ± 0.2
D	0.9 ± 0.2
E	2.6 ± 0.2
F	3.2 ± 0.2



#### ■ Schematic



■ Recommend Land Pattern Dimensions



A	4.0
B	5.9
C	2.2
D	0.6

Unit : mm

■ Marking and Date Code

Marking

The inductor is marked with a 3-digit code

Example -- 100.0 $\mu$ H → 101

Date Code

X    XX    XXX  
 (1)    (2)    (3)

Where (1) Year Code


Ex : 2021 = 1

(2) Weekly Code

Serial number : 01 ~ 53

(3) Taping No.

Serial number : 001 ~ ZZZ



### Specifications

Part Number	Common Mode Inductance (μH) Note2 ◇	Stray Inductance (μH) Note2	Common Mode Impedance (Ω) Note3		DCR (Ω) ◇	Rated current (mA)	Rated voltage (Vdc)	Insulation Resistance (MΩ)
			Typ.	Min.				
VFB4532-101V	100.0	0.2	2000	5000	2.0	150	80	10

◇ : Significant Characteristic

\*Inductance Tolerance : ±40%

Note 1. : All test data is referenced to 25°C ambient.

Note 2. : Test Condition:100KHz, 0.1Vrms

Note 3. : Test Condition:10MHz, 0.1Vrms

Note 4. : Operating Temperature Range -40°C to + 150°C

Note 5. : Cleaning Process Note


(a) If this power choke is dipped in the cleaning agent, such as toluene, xylene, ketone, and ether system, there is a possibility that the performance decreases greatly

(b) The high power ultrasonic washing may damage the choke body.

(c) Please contact us if you need the cleaning via the above agents or ultrasonic washing.


Note 6. : Moisture Sensitivity Level: MSL1 (unlimited floor life at<30°C/85% relative humidity).

### Impedance VS. Frequency Characteristic



### ■ Packaging


#### (1) Tape packaging dimensions




Dimensions Code (mm)				UNITS/REEL
A0	B0	K0	t	
3.5 ± 0.1	5.1 ± 0.1	3.1 ± 0.1	0.40 ± 0.05	2,500

#### (2) Tape Direction

The direction shall be seen from the top cover tape side.




(3) Reel dimensions




(4) Peel force of top cover tape

The peel speed shall be about 300 mm/minute.

The peel force of top cover tape shall be between 0.1 to 1.3N.



■ Reflow profile



(1) Reflow Soldering Method :

Reflow Soldering	Tp:255~260°C	Max.30 seconds ( tp )
	≥ 217°C	60~150 seconds
Pre-Heat	150 ~ 200°C	60~120 seconds
Time 25°C to peak temperature	8 minutes max.	

(2) Soldering iron Method : 350 ± 5°C max.3 seconds

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Cyntec:](#)

[VFB4532-101V](#)