

Zeta Plus™ H Series

Depth Filter Cartridges & Capsules

Zeta Plus™ H Series is a charge-modified depth filter constructed with high-tensile strength media to perform efficiently even under operating conditions requiring elevated operating temperatures or repeated hot water sanitation cycles. Zeta Plus H series filters are available in either standard sheet or easy to use, labor saving cartridges.

Zeta Plus Cartridges and Housings to Fit Every Need

Zeta Plus H Series filters are available in 8, 12 and 16 inch diameter cartridges, providing filtration surface areas from 2.8 ft² to 39.7 ft² (0.26 m² to 3.7 m²) per cartridge. This broad range of cartridge configurations allows for easy scale-up from the bench top to pilot scale to full production. A wide variety of industrial and sanitary Zeta Plus housings are available to provide totally enclosed liquid filtration. Refer to Purification Inc. literature number 70-0201-8762-4.

Zeta Plus Cartridge System Vs. Plate & Frame Filter Economics

The Zeta Plus cartridge system has a number of advantages over conventional plate and frame filters. Since the cartridge system utilizes a totally enclosed housing, there is no product leakage and no exposure of the filter media to external contamination allowing for effective use of the media, higher throughputs,

and low operating costs. The plate and frame filter press design is open to the environment making both filter media and product susceptible to external contamination. The “open” design requires more frequent media change-out cycles, typically every few days. This results in lower throughputs and higher operating costs.



Applications

The Zeta Plus™ H Series is ideally suited for clarification and pre-filtration in food and beverage, cosmetic, and general applications where the exceptional high wet-tensile strength media provides extended service life.

Features & Benefits

High wet-strength filter media design to withstand multiple hot water sanitation cycles

- Extended filter life resulting in high throughputs, fewer cartridge change-outs, and reduced operating costs.

Combined depth filtration and electrokinetic adsorption

- Efficient haze and particle removal at micron ratings smaller than the mechanical rating alone.

Easy-to-install cartridges for rapid change-out

- Reduced labor cost

Totally enclosed, sanitary systems and housings

- Zero edge leakage and external contamination

Variety of cartridge sizes and filtration surface areas

- Flexible options for all flow requirements

All components FDA CFR Title 21 listed

- Safe for food & beverage filter applications

Zeta Plus™ H Series Depth Filter Cartridges & Capsules

Plate and frame filters are labor intensive, requiring two people four to eight hours to change out the media. Zeta Plus cartridges are easy to install and remove, usually taking about 15 minutes, resulting in significant labor cost reductions. Coupled with the floor space reduction of the vertical Zeta Plus housing design and a typical 50% or greater decrease in initial capital cost when compared to a comparable plate and frame filter, the savings become substantial.

Table 1 highlights the economic advantages in capital and operating costs that the Zeta Plus system provides over conventional sheet filtration using a plate and frame filter. To complete this analysis, a generic process line running at 350 HI/hr (1,000,000 HI/yr) was used. A two stage Zeta Plus configuration is compared to a standard plate and frame system. Discounted cash flow was determined using a 10-year life period.

Table 1: Zeta Plus™ Cartridges vs. Plate & Frame Filters

	Plate & Frame Filter (U.S. Cents/HL)	Zeta Plus™ Cartridge System (U.S. Cents/HL)
Capital Cost	8.5	1.3
Media Cost	6.8	12.2
Labor-Media Change-out	1.1	0.1
Loss-Leakage	1.3	-
Regeneration & Sanitization Costs	2.8	0.4
Spare Parts & Maintenance	1.5	0.2
Total Costs/HL	22.0	14.0


Superior Particle Removal

Zeta Plus filter media offers unique advantages in contamination removal because of its electrokinetic properties. In addition to the mechanical exclusion of particles by its depth loading feature, Zeta Plus filter media adsorbs contaminants too small for removal by mechanical straining alone. Since most particles in suspension have been shown to exhibit a negative charge, virtually all contaminants can be removed with proper grade selection.


Grade Selection

Zeta Plus™ H Series filter media are available in a broad range of grades. Mechanical straining alone, as determined by mean-flow pore analysis, is indicated in Figure 1. Particles smaller than the rated pore size will be removed by Zeta Plus H Series filter media because of electrokinetic adsorption. Actual operating conditions and the product to be filtered should be considered in grade selection. Technical support in optimal grade selection is provided by your local Master Representative/Distributor or by the 3M Purification Inc. Application Engineering.


Figure 1: Grade Selection



Graph 1: 90°C Water Exposure



Graph 2: 135°C Steam Exposure



Superior Strength and Resistance

Zeta Plus H Series filters are specifically designed for applications requiring numerous hot water sanitization cycles or extended exposure to high service temperatures. The superior wet tensile strength of Zeta Plus H Series media combined with a highly durable cartridge design ensures integrity under flow and pressure variations where poorly designed competitive products suffer media erosion, deformation and bypass.

High Performance in Microbial Reduction

Zeta Plus H Series media demonstrate excellent microbial reduction as noted in Table 2 below. No organisms were detected downstream of the Zeta Plus media after filtration. This confirms the effectiveness of Zeta Plus H Series media in protection of final membrane filters and in producing a microbiologically stable product when used alone.

Table 2: Zeta Plus™ H Series Microbial Reduction

Media Grade	Microorganism used for challenge	Removal (CFU/cm ² of media)	Organisms in Filtrate
30H	<i>Saccharomyces cerevisiae</i> (ATCC-36026)	4.1 × 10 ⁸	0
50H		6.8 × 10 ⁸	0
60H		6.0 × 10 ⁸	0
60H	<i>Oenococcus oeni</i> (ATCC-23279)	5.5 × 10 ⁸	0
90H		7.2 × 10 ⁸	0

Challenge conditions used in these tests: microbial concentration: 10⁶ - 10⁷ organisms/ml flow rate: 0.25 gpm/ft² (10 lpm/m²)

Zeta Plus™ H Series Depth Filter Cartridges & Capsules

Low Extractables

Calcium and iron extractable concentrations of Zeta Plus™ H media in a variety of solutions are shown in Table 3 below. The data represent a static soak of the media in the listed fluid at a ratio of 10 ml of fluid/1 gram of media (approximately 1.2 liter/ft²). Even at this high ratio of media weight to soak volume, the results show extremely low extractable levels. As a Good Manufacturing Practice, 3M Purification Inc. recommends a 1.25 gallon/ft² (50 l/m²) flush of Zeta Plus H Series media with either filtered water or product prior to use. Moreover, specific rinsing procedures can be developed on-site for special applications to reduce these levels even further.

Table 3: Extractables

Media Grade		10H	30H	50H	60H	90H
D.I. Water	Calcium (ppm)	<0.05	0.1	0.12	0.13	0.15
	Iron (ppm)	<0.015	<0.015	<0.015	<0.015	<0.015
8% Ethanol	Calcium (ppm)	<0.05	0.9	<0.08	<0.08	0.09
	Iron (ppm)	<0.015	<0.015	<0.015	<0.015	<0.015
50% Ethanol	Calcium (ppm)	<0.05	<0.08	<0.08	<0.08	<0.08
	Iron (ppm)	<0.015	<0.015	<0.015	<0.015	<0.015


Recommended Operating Parameters	
Cartridge Max. Temp.	180°F (80°C)
BC25 Max. Temp.	100°F (40°C)
Change-out Differential Pressure	35 psid (2.4 bar)
Rec. Flow Rate*	0.25-0.5 gpm/ft ² (10-20 lpm/m ²)
Max. Flow Rate	1.0 gpm/ft ² (40 lpm/m ²)
Pre-use Rinse Volume	1.25 gallons/ft ² (50 liters/m ²)

*Consult 3M Purification Inc. for the best flow rate for your application.

Cartridge Construction

A single Zeta Plus™ cartridge is composed of an assembly of Zeta Plus cells. Each cell is composed of two Zeta Plus H Series media discs on either side of a polypropylene “stiff cell” separator. The stiff-cell separator, as depicted in Figure 2, is a 3M Purification Inc. innovation. It provides a more durable cartridge with enhanced flow characteristics resulting in longer service life. The discs are sealed together at the circumference by an injection molded polypropylene edge seal. The cells are then unitized into a cartridge using set compression that results in a rugged, durable cartridge (Figure 2). The cells are held in place by three stainless steel bands in the core of the cartridge. All components of Zeta Plus H Series filter cartridges are listed in CFR 21 by the US Food and Drug Administration as safe for food contact.

Figure 2: Cartridge Construction



Cartridge Configurations

Zeta Plus cartridges are available in a variety of size and number of cell combinations. Table 4 lists information about Zeta Plus H Series configurations.


Table 4: H Series Cartridge Configurations

Catalog Number	Nominal Diameter	Height	Effective Filtration Area	Number of Cells
45109	8 in (203 mm)	6 11/16 in (170 mm)	2.8 ft ² (0.26 m ²)	8
45167	8 in (203 mm)	6 5/8 in (168 mm)	2.5 ft ² (0.23 m ²)	7
45237	12 in (304 mm)	10 3/4 in (273 mm)	12.3 ft ² (1.1 m ²)	12
45245	12 in (304 mm)	10 3/4 in (273 mm)	16.4 ft ² (1.5 m ²)	16
Z16P	16 in (406 mm)	10 3/4 in (273 mm)	34.7 ft ² (3.2 m ²)	14

Flow Characteristics

Graphs 3 and 4 show initial differential pressure values for Zeta Plus™ H Series media versus specific flow rates in water and a 10 cst viscosity oil, respectively.

Graph 3 and 4: Zeta Plus™ Flow Characteristics



Zeta Plus™ H Series Ordering Guide

BC25 Disposable Capsules

Cartridge Number	Nominal Filter Area	Connection Options	Media Grade	Media Formulation
BC Capsule	0025 3.9 in ² (25 cm ²)	S (Sanitary)	05, 10, 30, 50, 60,90	H - Inorganic Filter Aid & Cellulose

8" Diameter Cartridges

Cartridge Number	Gasket	Media Grade	Media Formulation
45109 (8" 8 cell)	11 - Nitrile 14 - EPR	05, 10, 30, 50, 60,90	H - Inorganic Filter Aid & Cellulose
45167 (8" 7 cell O-ring Plug in)	01 - Nitrile 02 - EPR	05, 10, 30, 50, 60,90	H - Inorganic Filter Aid & Cellulose

12" Diameter Cartridges

Cartridge Number	Geometric Variation	Gasket	Media Grade	Media Formulation
45237 (12" 12 cell) 45245 (12" 16 cell)	01 - Standard Polypropylene	A - Silicone C - EPR D - Nitrile	05, 10, 30, 50, 60,90	H - Inorganic Filter Aid & Cellulose

16" Diameter Cartridges

Cartridge Number	Gasket	Media Grade	Media Formulation
Z16P (16" 14 cell)	A - Silicone C - EPR D - Nitrile	05, 10, 30, 50, 60,90	H - Inorganic Filter Aid & Cellulose

PLEASE NOTE: The Order Guide above is for reference only. Not all combinations are available.

Please consult with your 3M representative to determine the appropriate part number for your application.

Technical Information

The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer

Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



Your local distributor:

3M Purificaton Inc.
3M Separation and Purification
Sciences Division
400 Research Parkway
Meriden, CT 06450 USA
Phone 1-800-243-6894
1-203-237-5541
Fax 1-203-630-4530
Web www.3Mpurification.com

Zeta Plus is a trademark of 3M Company.
All other trademarks are the property of their respective owners.
© 2018 3M Company. All rights reserved.
70020188564 REV 0318sr

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[3M:](#)

[7000050599](#) [7000050600](#) [7000125362](#) [7000125516](#) [7000125517](#) [7000125518](#) [7000125726](#) [7000148456](#)
[7010314608](#) [7010338490](#) [7010339345](#) [7010339489](#) [7010379275](#) [7010379618](#) [7010379621](#) [7010380798](#)
[7010381555](#) [7100074377](#) [7100101269](#)