



NOTES:

- 1) PRODUCT DESCRIPTION: 23 GAUGE/3 CONDUCTOR; 1 CONDUCTOR SHIELDED/2 UNSHIELDED. 5 STRANDS TINNED COPPER-COVERED STEEL, 16 STRANDS TINNED COPPER. RUBBER INSULATED, CONDUCTIVE TEXTILE WRAP SHIELD PLUS VOLEX ALUMINUM-POLYESTER SHIELD WITH DRAIN WIRE SAME AS CONDUCTORS. 100% SHIELD COVERAGE. PAPER TAPE, BLACK NEOPRENE JACKET.
- 2) 90V/90°C
- 3) APPROVALS: NONE
- 4) CORDAGE O.D. : .250' (REF.)
- 5) PRACTICAL EXTENDED LENGTH IS APPROX. 5 FT
- 6) 50 CORDS / CARTON.
- 7) COLOR CODE: WHITE, BLACK, RED.
- 8) ALL DIMENSIONS IN INCHES UNLESS OTHERWISE NOTED.

VOLEX RESERVES THE RIGHT TO ALTER NON-CRITICAL DIMENSIONS WITHOUT NOTICE.

REV	DESCRIPTION	DATE
1	C.U.D - FIRST ISSUE	01/26/05

	<input checked="" type="checkbox"/> Indianapolis, IN <input type="checkbox"/> Conover, N.C. <input type="checkbox"/> Fremont, CA <input type="checkbox"/> Aguascalientes, MX <input type="checkbox"/> Tijuana, Mexico <input type="checkbox"/> Hermosillo, MX <input type="checkbox"/> Clinton, AR <input type="checkbox"/> Kanata, Canada	Proprietary Notice: This document is the property of Volex Incorporated. The information contained herein is not to be disclosed to anyone without the express written consent of Volex Inc.	MATERIAL: JACKET: NEOPRENE COLOR: BLACK	SCALE: NOT TO SCALE	ECD: N/A	ITEM DESCRIPTION CORDSET - NORTH AMERICAN RETRACTILE		
	FINISH: JACKET: SMOOTH		TOLERANCE UNLESS OTHERWISE SPECIFIED .XXX ± .005 .XX ± .02 .X ± .03 FRACT. ± 1/32 ANGULAR ± 1/2°	APPROVED LW	DRAWN BY MAF	DATE 01/26/05	PART NO. 8497 10 50	