

## Specification Sheet

Part Number: 133-03427



Can be easily assembled to convoluted tubing and reliably remain in position

Internal rib prevents movement or rattling

Multiple configurations to mount to a variety of surfaces

Releaseable to allow for maintenance

Conduit Clamps, Size 10, Mounting Hole 10.6 mm, Offset 40.5 mm, PA66, Black, 850/carton

Article Number 133-03427

Type CDC10S40.5M10

Color Black (BK)

Quantity Per carton

Product Description The Convoluted Tubing Clamp provides a quick method for securing and routing convoluted tubing. The clamp has an internal rib that prevents movement of the tubing and rattling. Living hinge allows placement and positioning of tubing before locking in place. Convoluted tubing clamps are available in various tubing diameters.

Short Description Conduit Clamps, Size 10, Mounting Hole 10.6 mm, Offset 40.5 mm, PA66, Black, 850/carton

Global Part Name CDC10S40.5M10-PA66-BK

Length L (Imperial) 2.58

Length L (Metric) 65.5

Offset Length (Imperial) 1.59

Offset Length (Metric) 40.5

Fixation Method screwable

Width W (Imperial) 0.9

Width W (Metric) 23

Bundle Diameter Max (Imperial) 0.39

Bundle Diameter Max (Metric) 10.0

Height H (Imperial) 2.0

Height H (Metric) 50.7

Diameter D (Imperial) 0.43

Diameter D (Metric) 11.0

Mounting Hole Diameter D (Imperial) 0.42 "

Mounting Hole Diameter D (Metric) 10.6 mm

Stud Diameter (Metric)	M10
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
Halogen Free	No
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	850
Package Quantity (Metric)	850
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224

Phone: (800) 537-1512 | Email: [corp@htamericas.com](mailto:corp@htamericas.com)

© 2025 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)