



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided Equipment	All required connectors Battery recycling guide Installation guide Reusable packaging
--------------------	--

Physical

Depth	18.94 in (48.1 cm)
Height	8.86 in (22.5 cm)
Product Weight	49.10 lb(US) (22.27 kg)
Width	10.98 in (27.9 cm)

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 %

Batteries & Runtime

Battery blocks per string	10
Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Enclosed battery cartridge
Battery Voltage	120 V
Battery Type	Lead-Acid battery
RBC Quantity	1

Ordering and shipping details

Package weight(Lbs)	55.51 lb(US) (25.18 kg)
---------------------	-------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Package 1 Height	9.96 in (25.3 cm)
Package 1 width	11.54 in (29.3 cm)
Package 1 Length	19.49 in (49.5 cm)
Number of Units in Package 3	32

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Take-back	Take-back program available

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------