

# Low Voltage Quad 2-Input Multiplexer

With 5 V Tolerant Inputs

## 74LCX157

The LCX157 is a high-speed quad 2-input multiplexer. Four bits of data from two sources can be selected using the common Select and Enable inputs. The four outputs present the selected data in the true (non-inverted) form.

The LCX157 can also be used as a function generator.

The 74LCX157 is fabricated with advanced CMOS technology to achieve high speed operation while maintaining CMOS low power dissipation.

### Features

- 5 V Tolerant Inputs
- 1.65 V to 5.5 V,  $V_{CC}$  Specifications Provided
- 5.8 ns  $t_{PD}$  Max. ( $V_{CC} = 3.3$  V), 10  $\mu$ A  $I_{CC}$  Max.
- Power Down High Impedance Inputs and Outputs
- $\pm 24$  mA Output Drive ( $V_{CC} = 3.0$  V)
- Implements Patented Noise/EMI Reduction Circuitry
- Latch-up Performance Exceeds 100 mA
- ESD Performance: Human Body Model >2000 V
- These are Pb-Free Devices







Figure 1. Logic Symbols


### MARKING DIAGRAMS



SOIC-16, 150 mils  
CASE 751BG



TSSOP-16  
CASE 948AH




A = Assembly Location  
 WL, L = Wafer Lot  
 Y = Year  
 WW, W = Work Week  
 G or ■ = Pb-Free Package

(Note: Microdot may be in either location)

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 7 of this data sheet.

# 74LCX157



**Figure 2. Connection Diagram**

## Functional Description

The LCX157 is a quad 2-input multiplexer. It selects four bits of data from two sources under the control of a common Select input (S). The Enable input ( $\bar{E}$ ) is active-LOW. When  $\bar{E}$  is HIGH, all of the outputs (Z) are forced LOW regardless of all other inputs. The LCX157 is the logic implementation of a 4-pole, 2-position switch where the position of the switch is determined by the logic levels supplied to the Select input. The logic equations for the outputs are shown below:

$$Z_a = \bar{E} \cdot (I_{1a} \cdot S + I_{0a} \cdot \bar{S})$$

$$Z_b = \bar{E} \cdot (I_{1b} \cdot S + I_{0b} \cdot \bar{S})$$

$$Z_c = \bar{E} \cdot (I_{1c} \cdot S + I_{0c} \cdot \bar{S})$$

$$Z_d = \bar{E} \cdot (I_{1d} \cdot S + I_{0d} \cdot \bar{S})$$

A common use of the LCX157 is the moving of data from two groups of registers to four common output busses. The particular register from which the data comes is determined

## PIN DESCRIPTIONS


| Pin Names       | Description          |
|-----------------|----------------------|
| $I_{0a}-I_{0d}$ | Source 0 Data Inputs |
| $I_{1a}-I_{1d}$ | Source 1 Data Inputs |
| $\bar{E}$       | Enable Input         |
| S               | Select Inputs        |
| $Z_a-Z_d$       | Outputs              |

by the state of the Select input. A less obvious use is as a function generator. The LCX157 can generate any four of the sixteen different functions of two variables with one variable common. This is useful for implementing gating functions.

## TRUTH TABLE

| Inputs    |   |       |       | Outputs |
|-----------|---|-------|-------|---------|
| $\bar{E}$ | S | $I_0$ | $I_1$ | Z       |
| H         | X | X     | X     | L       |
| L         | H | X     | L     | L       |
| L         | H | X     | H     | H       |
| L         | L | L     | X     | L       |
| L         | L | H     | X     | H       |

H = HIGH Voltage Level  
L = LOW Voltage Level  
X = Immaterial



NOTE: Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

**Figure 3. Logic Diagram**

## ABSOLUTE MAXIMUM RATINGS

| Symbol                | Parameter                                                                                                            | Value                                                  | Unit |
|-----------------------|----------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|------|
| $V_{CC}$              | DC Supply Voltage                                                                                                    | -0.5 to +6.5                                           | V    |
| $V_I$                 | DC Input Voltage (Note 1)                                                                                            | -0.5 to +6.5                                           | V    |
| $V_O$                 | DC Output Voltage (Note 1)<br>Active-Mode (High or Low State)<br>Tri-State Mode<br>Power-Down Mode ( $V_{CC} = 0$ V) | -0.5 to $V_{CC} + 0.5$<br>-0.5 to +6.5<br>-0.5 to +6.5 | V    |
| $I_{IK}$              | DC Input Diode Current<br>$V_I < GND$                                                                                | -50                                                    | mA   |
| $I_{OK}$              | DC Output Diode Current<br>$V_O < GND$                                                                               | -50                                                    | mA   |
| $I_O$                 | DC Output Source/Sink Current                                                                                        | $\pm 50$                                               | mA   |
| $I_{CC}$ or $I_{GND}$ | DC Supply Current per Supply Pin or Ground Pin                                                                       | $\pm 100$                                              | mA   |
| $T_{STG}$             | Storage Temperature Range                                                                                            | -65 to +150                                            | °C   |
| $T_L$                 | Lead Temperature, 1 mm from Case for 10 secs                                                                         | 260                                                    | °C   |
| $T_J$                 | Junction Temperature Under Bias                                                                                      | +150                                                   | °C   |
| $\theta_{JA}$         | Thermal Resistance (Note 1)<br>SOIC-16<br>TSSOP-16                                                                   | 126<br>159                                             | °C/W |
| $P_D$                 | Power Dissipation in Still Air at 125°C<br>SOIC-16<br>TSSOP-16                                                       | 995<br>787                                             | mW   |
| MSL                   | Moisture Sensitivity                                                                                                 | Level 1                                                | -    |
| $F_R$                 | Flammability Rating<br>Oxygen Index: 28 to 34                                                                        | UL 94 V-0 @ 0.125 in                                   | -    |
| $V_{ESD}$             | ESD Withstand Voltage (Note 3)<br>Human Body Model<br>Charged Device Model                                           | 2000<br>N/A                                            | V    |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1.  $I_O$  absolute maximum rating must be observed.
2. Measured with minimum pad spacing on an FR4 board, using 76 mm-by-114 mm, 2-ounce copper trace no air flow per JESD51-7.
3. HBM tested to EIA / JESD22-A114-A. CDM tested to JESD22-C101-A. JEDEC recommends that ESD qualification to EIA/JESD22-A115A (Machine Model) be discontinued.

## RECOMMENDED OPERATING CONDITIONS

| Symbol     | Parameter                                                                                                                                                          | Min              | Typ              | Max                    | Unit |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|------------------|------------------------|------|
| $V_{CC}$   | Supply Voltage<br>Operating<br>Data Retention Only                                                                                                                 | 1.65<br>1.5      | 3.3<br>3.3       | 5.5<br>5.5             | V    |
| $V_I$      | Digital Input Voltage                                                                                                                                              | 0                | -                | 5.5                    | V    |
| $V_O$      | Output Voltage<br>Active Mode (High or Low State)<br>Tri-State Mode<br>Power Down Mode ( $V_{CC} = 0$ V)                                                           | 0<br>0<br>0      | -<br>-<br>-      | $V_{CC}$<br>5.5<br>5.5 | V    |
| $T_A$      | Operating Free-Air Temperature                                                                                                                                     | -40              | -                | +125                   | °C   |
| $t_r, t_f$ | Input Rise or Fall Rate<br>$V_{CC} = 1.65$ V to 1.95 V<br>$V_{CC} = 2.3$ V to 2.7 V<br>$V_{IN}$ from 0.8 V to 2.0 V, $V_{CC} = 3.0$ V<br>$V_{CC} = 4.5$ V to 5.5 V | 0<br>0<br>0<br>0 | -<br>-<br>-<br>- | 20<br>20<br>10<br>5    | nS/V |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

4. Unused inputs must always be tied to an appropriate logic voltage level (e.g., either GND or  $V_{CC}$ ). Unused outputs must be left open.

# 74LCX157

## DC ELECTRICAL CHARACTERISTICS

| Symbol           | Parameter                             | Conditions                                                                                                                                                                                                                                             | V <sub>CC</sub> (V)                                   | T <sub>A</sub> = -40°C to +85°C                                  |                                                 | T <sub>A</sub> = -40°C to +125°C                                 |                                                 | Unit |
|------------------|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|------------------------------------------------------------------|-------------------------------------------------|------------------------------------------------------------------|-------------------------------------------------|------|
|                  |                                       |                                                                                                                                                                                                                                                        |                                                       | Min                                                              | Max                                             | Min                                                              | Max                                             |      |
| V <sub>IH</sub>  | HIGH Level Input Voltage              |                                                                                                                                                                                                                                                        | 1.65 – 1.95                                           | 0.65 x V <sub>CC</sub>                                           | –                                               | 0.65 x V <sub>CC</sub>                                           | –                                               | V    |
|                  |                                       |                                                                                                                                                                                                                                                        | 2.3 – 2.7                                             | 1.7                                                              | –                                               | 1.7                                                              | –                                               |      |
|                  |                                       |                                                                                                                                                                                                                                                        | 3.0 – 3.6                                             | 2.0                                                              | –                                               | 2.0                                                              | –                                               |      |
|                  |                                       |                                                                                                                                                                                                                                                        | 4.5 – 5.5                                             | 0.70 x V <sub>CC</sub>                                           | –                                               | 0.70 x V <sub>CC</sub>                                           | –                                               |      |
| V <sub>IL</sub>  | LOW Level Input Voltage               |                                                                                                                                                                                                                                                        | 1.65 – 1.95                                           | –                                                                | 0.35 x V <sub>CC</sub>                          | –                                                                | 0.35 x V <sub>CC</sub>                          | V    |
|                  |                                       |                                                                                                                                                                                                                                                        | 2.3 – 2.7                                             | –                                                                | 0.7                                             | –                                                                | 0.7                                             |      |
|                  |                                       |                                                                                                                                                                                                                                                        | 3.0 – 3.6                                             | –                                                                | 0.8                                             | –                                                                | 0.8                                             |      |
|                  |                                       |                                                                                                                                                                                                                                                        | 4.5 – 5.5                                             | –                                                                | 0.30 x V <sub>CC</sub>                          | –                                                                | 0.30 x V <sub>CC</sub>                          |      |
| V <sub>OH</sub>  | High-Level Output Voltage             | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>I <sub>OH</sub> = -100 μA<br>I <sub>OH</sub> = -4 mA<br>I <sub>OH</sub> = -8 mA<br>I <sub>OH</sub> = -12 mA<br>I <sub>OH</sub> = -16 mA<br>I <sub>OH</sub> = -24 mA<br>I <sub>OH</sub> = -32 mA | 1.65 – 5.5<br>1.65<br>2.3<br>2.7<br>3.0<br>3.0<br>4.5 | V <sub>CC</sub> – 0.1<br>1.29<br>1.8<br>2.2<br>2.4<br>2.2<br>3.7 | –<br>–<br>–<br>–<br>–<br>–<br>–                 | V <sub>CC</sub> – 0.1<br>1.29<br>1.8<br>2.2<br>2.4<br>2.2<br>3.7 | –<br>–<br>–<br>–<br>–<br>–<br>–                 | V    |
| V <sub>OL</sub>  | Low-Level Output Voltage              | V <sub>I</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>I <sub>OL</sub> = 100 μA<br>I <sub>OL</sub> = 4 mA<br>I <sub>OL</sub> = 8 mA<br>I <sub>OL</sub> = 12 mA<br>I <sub>OL</sub> = 16 mA<br>I <sub>OL</sub> = 24 mA<br>I <sub>OL</sub> = 32 mA        | 1.65 – 5.5<br>1.65<br>2.3<br>2.7<br>3.0<br>3.0<br>4.5 | –<br>–<br>–<br>–<br>–<br>–<br>–                                  | 0.1<br>0.24<br>0.3<br>0.4<br>0.4<br>0.55<br>0.6 | –<br>–<br>–<br>–<br>–<br>–<br>–                                  | 0.1<br>0.24<br>0.3<br>0.4<br>0.4<br>0.55<br>0.6 | V    |
| I <sub>I</sub>   | Input Leakage Current                 | V <sub>I</sub> = 0 to 5.5 V                                                                                                                                                                                                                            | 1.65 – 5.5                                            | –                                                                | ±5.0                                            | –                                                                | ±5.0                                            | μA   |
| I <sub>OFF</sub> | Power Off Leakage Current             | V <sub>I</sub> = 5.5 V or<br>V <sub>O</sub> = 5.5 V                                                                                                                                                                                                    | 0                                                     | –                                                                | 10                                              | –                                                                | 10                                              | μA   |
| I <sub>CC</sub>  | Quiescent Supply Current              | V <sub>I</sub> = 5.5 V or GND                                                                                                                                                                                                                          | 1.65 – 5.5                                            | –                                                                | 10                                              | –                                                                | 10                                              | μA   |
| ΔI <sub>CC</sub> | Increase in I <sub>CC</sub> per Input | V <sub>IH</sub> = V <sub>CC</sub> – 0.6 V                                                                                                                                                                                                              | 2.3 – 3.6                                             | –                                                                | 500                                             | –                                                                | 500                                             | μA   |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

# 74LCX157

## AC ELECTRICAL CHARACTERISTICS

| Symbol                                   | Parameter                                              | Test Condition      | V <sub>CC</sub> (V) | T <sub>A</sub> = -40°C to +85°C |      | T <sub>A</sub> = -40°C to +125°C |      | Unit |
|------------------------------------------|--------------------------------------------------------|---------------------|---------------------|---------------------------------|------|----------------------------------|------|------|
|                                          |                                                        |                     |                     | Min                             | Max  | Min                              | Max  |      |
| t <sub>PLH</sub> , t <sub>PHL</sub>      | Propagation Delay,<br>S to Z <sub>n</sub>              | See Figures 4 and 5 | 1.65 to 1.95        | –                               | 11.6 | –                                | 11.6 | ns   |
|                                          |                                                        |                     | 2.3 to 2.7          | –                               | 8.4  | –                                | 8.4  |      |
|                                          |                                                        |                     | 2.7                 | –                               | 8.0  | –                                | 8.0  |      |
|                                          |                                                        |                     | 3.0 to 3.6          | –                               | 7.0  | –                                | 7.0  |      |
|                                          |                                                        |                     | 4.5 to 5.5          | –                               | 5.8  | –                                | 5.8  |      |
| t <sub>PLH</sub> , t <sub>PHL</sub>      | Propagation Delay,<br>E to Z <sub>n</sub>              | See Figures 4 and 5 | 1.65 to 1.95        | –                               | 11.6 | –                                | 11.6 | ns   |
|                                          |                                                        |                     | 2.3 to 2.7          | –                               | 8.4  | –                                | 8.4  |      |
|                                          |                                                        |                     | 2.7                 | –                               | 8.0  | –                                | 8.0  |      |
|                                          |                                                        |                     | 3.0 to 3.6          | –                               | 7.0  | –                                | 7.0  |      |
|                                          |                                                        |                     | 4.5 to 5.5          | –                               | 5.8  | –                                | 5.8  |      |
| t <sub>PLH</sub> , t <sub>PHL</sub>      | Propagation Delay,<br>I <sub>n</sub> to Z <sub>n</sub> | See Figures 4 and 5 | 1.65 to 1.95        | –                               | 11.2 | –                                | 11.2 | ns   |
|                                          |                                                        |                     | 2.3 to 2.7          | –                               | 7.0  | –                                | 7.0  |      |
|                                          |                                                        |                     | 2.7                 | –                               | 6.3  | –                                | 6.3  |      |
|                                          |                                                        |                     | 3.0 to 3.6          | –                               | 5.8  | –                                | 5.8  |      |
|                                          |                                                        |                     | 4.5 to 5.5          | –                               | 4.8  | –                                | 4.8  |      |
| t <sub>OSSL</sub> ,<br>t <sub>OSLH</sub> | Output to Output Skew<br>(Note 5)                      |                     | 1.65 to 1.95        | –                               | –    | –                                | –    | ns   |
|                                          |                                                        |                     | 2.3 to 2.7          | –                               | –    | –                                | –    |      |
|                                          |                                                        |                     | 2.7                 | –                               | –    | –                                | –    |      |
|                                          |                                                        |                     | 3.0 to 3.6          | –                               | 1.0  | –                                | 1.0  |      |
|                                          |                                                        |                     | 4.5 to 5.5          | –                               | –    | –                                | –    |      |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

5. Skew is defined as the absolute value of the difference between the actual propagation delay for any two separate outputs of the same device. The specification applies to any outputs switching in the same direction, either HIGH-to-LOW (t<sub>OSSL</sub>) or LOW-to-HIGH (t<sub>OSLH</sub>).


## DYNAMIC SWITCHING CHARACTERISTICS

| Symbol           | Parameter                                   | Conditions                                                             | V <sub>CC</sub> (V) | T <sub>A</sub> = 25°C | Unit |
|------------------|---------------------------------------------|------------------------------------------------------------------------|---------------------|-----------------------|------|
|                  |                                             |                                                                        |                     | Typical               |      |
| V <sub>OLP</sub> | Quiet Output Dynamic Peak V <sub>OL</sub>   | C <sub>L</sub> = 50 pF, V <sub>IH</sub> = 3.3 V, V <sub>IL</sub> = 0 V | 3.3                 | 0.8                   | V    |
|                  |                                             | C <sub>L</sub> = 30 pF, V <sub>IH</sub> = 2.5 V, V <sub>IL</sub> = 0 V | 2.5                 | 0.6                   |      |
| V <sub>OLV</sub> | Quiet Output Dynamic Valley V <sub>OL</sub> | C <sub>L</sub> = 50 pF, V <sub>IH</sub> = 3.3 V, V <sub>IL</sub> = 0 V | 3.3                 | –0.8                  | V    |
|                  |                                             | C <sub>L</sub> = 30 pF, V <sub>IH</sub> = 2.5 V, V <sub>IL</sub> = 0 V | 2.5                 | –0.6                  |      |

## CAPACITANCE

| Symbol           | Parameter                     | Condition                                                                     | Typical | Units |
|------------------|-------------------------------|-------------------------------------------------------------------------------|---------|-------|
| C <sub>IN</sub>  | Input Capacitance             | V <sub>CC</sub> = Open, V <sub>I</sub> = 0 V or V <sub>CC</sub>               | 7       | pF    |
| C <sub>OUT</sub> | Output Capacitance            | V <sub>CC</sub> = 3.3 V, V <sub>I</sub> = 0 V or V <sub>CC</sub>              | 8       | pF    |
| C <sub>PD</sub>  | Power Dissipation Capacitance | V <sub>CC</sub> = 3.3 V, V <sub>I</sub> = 0 V or V <sub>CC</sub> , f = 10 MHz | 25      | pF    |


## 74LCX157



$C_L$  includes probe and jig capacitance  
 $R_T$  is  $Z_{OUT}$  of pulse generator (typically 50  $\Omega$ )  
 $f = 1$  MHz

| Test                | Switch Position |
|---------------------|-----------------|
| $t_{PLH} / t_{PHL}$ | Open            |
| $t_{PLZ} / t_{PZL}$ | $V_{LOAD}$      |
| $t_{PHZ} / t_{PZH}$ | GND             |

Figure 4. Test Circuit



| $V_{CC}$ , V | $R_L$ , $\Omega$ | $C_L$ , pF | $V_{LOAD}$        | $V_m$ , V  | $V_Y$ , V |
|--------------|------------------|------------|-------------------|------------|-----------|
| 1.65 to 1.95 | 500              | 30         | $2 \times V_{CC}$ | $V_{CC}/2$ | 0.15      |
| 2.3 to 2.7   | 500              | 30         | $2 \times V_{CC}$ | $V_{CC}/2$ | 0.15      |
| 2.7          | 500              | 50         | 6 V               | 1.5        | 0.3       |
| 3.0 to 3.6   | 500              | 50         | 6 V               | 1.5        | 0.3       |
| 4.5 to 5.5   | 500              | 50         | $2 \times V_{CC}$ | $V_{CC}/2$ | 0.3       |

Figure 5. Switching Waveforms

# 74LCX157




Figure 6. Schematic Diagram (Generic for LCX Family)


## ORDERING INFORMATION

| Device       | Marking    | Package               | Shipping <sup>†</sup>    |
|--------------|------------|-----------------------|--------------------------|
| 74LCX157MX   | LCX157G    | SOIC-16<br>(Pb-Free)  | 2500 Units / Tape & Reel |
| 74LCX157MTCX | LCX<br>157 | TSSOP-16<br>(Pb-Free) | 2500 Units / Tape & Reel |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, [BRD8011/D](#).


**SOIC-16, 150 mils**  
CASE 751BG  
ISSUE O

DATE 19 DEC 2008




| SYMBOL | MIN      | NOM  | MAX   |
|--------|----------|------|-------|
| A      | 1.35     |      | 1.75  |
| A1     | 0.10     |      | 0.25  |
| b      | 0.33     |      | 0.51  |
| c      | 0.19     |      | 0.25  |
| D      | 9.80     | 9.90 | 10.00 |
| E      | 5.80     | 6.00 | 6.20  |
| E1     | 3.80     | 3.90 | 4.00  |
| e      | 1.27 BSC |      |       |
| h      | 0.25     |      | 0.50  |
| L      | 0.40     |      | 1.27  |
| θ      | 0°       |      | 8°    |

**TOP VIEW**



**SIDE VIEW**



**END VIEW**

**Notes:**

- (1) All dimensions are in millimeters. Angles in degrees.
- (2) Complies with JEDEC MS-012.


|                         |                          |                                                                                                                                                                                     |
|-------------------------|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON34275E</b>       | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SOIC-16, 150 mils</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                                  |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.



**TSSOP 16**  
CASE 948AH  
ISSUE O

DATE 19 SEP 2008




THIS TABLE FOR 0.65mm PITCH

| SYMBOL         | COMMON DIMENSIONS |       |      | NOTE VARIATIONS | D        | N  |
|----------------|-------------------|-------|------|-----------------|----------|----|
|                | MIN.              | NOM.  | MAX. |                 |          |    |
| A              | —                 | —     | 1.10 | AA/AAT          | 3.00 BSC | 8  |
| A <sub>1</sub> | 0.05              | —     | 0.15 | AB-1/ABT        | 5.00 BSC | 14 |
| A <sub>2</sub> | 0.85              | 0.90  | 0.95 | AB/ABT          | 5.00 BSC | 16 |
| b              | 0.19              | —     | 0.30 | AD/ADT          | 7.80 BSC | 24 |
| b <sub>1</sub> | 0.19              | 0.22  | 0.25 |                 |          |    |
| c              | 0.09              | —     | 0.20 |                 |          |    |
| c <sub>1</sub> | 0.09              | 0.127 | 0.16 |                 |          |    |
| D              | SEE VARIATIONS    |       |      |                 |          |    |
| E <sub>1</sub> | 4.30              | 4.40  | 4.50 |                 |          |    |
| e              | 0.65 BSC          |       |      |                 |          |    |
| E              | 6.40 BSC          |       |      |                 |          |    |
| L              | 0.50              | 0.60  | 0.70 |                 |          |    |
| L <sub>1</sub> | 1.00 REF          |       |      |                 |          |    |
| N              | SEE VARIATIONS    |       |      |                 |          |    |
| X              | 0°                | —     | 8°   |                 |          |    |

ALL DIMENSIONS IN MILLIMETERS

SECTION "B-B"



MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED 0.15mm ON D PER SIDE

|                         |                    |                                                                                                                                                                                     |
|-------------------------|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON34923E</b> | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>TSSOP 16</b>    | <b>PAGE 1 OF 1</b>                                                                                                                                                                  |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)