

# TinyLogic UHS Dual 2-Input NAND Gate with Schmitt Trigger Inputs

## NC7WZ132

### Description

The NC7WZ132 is a dual 2-Input NAND Gate with Schmitt-trigger inputs from onsemi's Ultra High Speed Series of TinyLogic. The device is fabricated with advanced CMOS technology to achieve ultra high speed with high output drive while maintaining low static power dissipation over a broad  $V_{CC}$  operating range. The device is specified to operate over the 1.65 V to 5.5 V  $V_{CC}$  operating range. The inputs and output are high impedance when  $V_{CC}$  is 0 V. Inputs tolerate voltages up to 5.5 V independent of  $V_{CC}$  operating voltage. Schmitt trigger inputs achieve typically 1 V hysteresis between the positive-going and negative-going input threshold voltage at 5 V  $V_{CC}$ .

### Features

- Space Saving US8 Surface Mount Package
- MicroPak™ Leadless Package
- Ultra High Speed:  $t_{PD} = 3.1$  ns Typ. into 50 pF at 5 V  $V_{CC}$
- High Output Drive:  $\pm 24$  mA at 3 V  $V_{CC}$
- Broad  $V_{CC}$  Operating Range: 1.65 V to 5.5 V
- Matches the Performance of LCX when Operated at 3.3 V  $V_{CC}$
- Power Down High Impedance Inputs / Output
- Overvoltage Tolerant Inputs Facilitate 5 V to 3 V Translation
- Proprietary Noise / EMI Reduction Circuitry Implemented
- Schmitt Trigger Inputs are Tolerant of Slow Changing Input Signals
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant






Figure 1. Logic Symbol


### MARKING DIAGRAMS



UQFN8  
1.6X1.6, 0.5P  
CASE 523AY



US8  
CASE 846AN



T5, WZD2 = Specific Device Code  
KK = 2-Digit Lot Run Traceability Code  
XY = 2-Digit Date Code Format  
Z = Assembly Plant Code

### ORDERING INFORMATION

See detailed ordering, marking and shipping information in the package dimensions section on page 6 of this data sheet.

NOTE: Some of the devices on this data sheet have been **DISCONTINUED**. Please refer to the table on page 6.

Connection Diagram




Figure 2. Connection Diagram (Top View)





Figure 4. Pad Assignments for MicroPak (Top Thru View)



AAA represents Product Code Top Mark – see ordering code  
NOTE: Orientation of Top Mark determines Pin One location.  
Read the top product code mark left to right, Pin One is the lower left pin (see diagram).

Figure 3. Pin One Orientation Diagram

PIN DESCRIPTION

| Pin Names  | Description |
|------------|-------------|
| $A_n, B_n$ | Inputs      |
| $Y_n$      | Output      |

FUNCTION TABLE ( $Y = \overline{AB}$ )

| Inputs |   | Output |
|--------|---|--------|
| A      | B | Y      |
| L      | L | H      |
| L      | H | H      |
| H      | L | H      |
| H      | H | L      |

H = HIGH Logic Level  
L = LOW Logic Level

**ABSOLUTE MAXIMUM RATINGS**

| Symbol             | Parameter                                         |                        | Min  | Max       | Unit |
|--------------------|---------------------------------------------------|------------------------|------|-----------|------|
| $V_{CC}$           | Supply Voltage                                    |                        | -0.5 | 6.5       | V    |
| $V_{IN}$           | DC Input Voltage                                  |                        | -0.5 | 6.5       | V    |
| $V_{OUT}$          | DC Output Voltage                                 |                        | -0.5 | 6.5       | V    |
| $I_{IK}$           | DC Input Diode Current                            | $V_{IN} < 0\text{ V}$  | -    | -50       | mA   |
| $I_{OK}$           | DC Output Diode Current                           | $V_{OUT} < 0\text{ V}$ | -    | -50       | mA   |
| $I_{OUT}$          | DC Output Current                                 |                        | -    | $\pm 50$  | mA   |
| $I_{CC} / I_{GND}$ | DC $V_{CC}$ / GND Current                         |                        | -    | $\pm 100$ | mA   |
| $T_{STG}$          | Storage Temperature                               |                        | -65  | +150      | °C   |
| $T_J$              | Junction Temperature under Bias                   |                        | -    | 150       | °C   |
| $T_L$              | Junction Lead Temperature (Soldering, 10 Seconds) |                        | -    | 260       | °C   |
| $P_D$              | Power Dissipation in Still Air                    | US8                    | -    | 500       | mW   |
|                    |                                                   | MicroPak-8             | -    | 539       | mW   |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

**RECOMMENDED OPERATING CONDITIONS**

| Symbol        | Parameter                     |            | Min  | Max      | Unit |
|---------------|-------------------------------|------------|------|----------|------|
| $V_{CC}$      | Supply Voltage Operating      |            | 1.65 | 5.5      | V    |
|               | Supply Voltage Data Retention |            | 1.5  | 5.5      |      |
| $V_{IN}$      | Input Voltage                 |            | 0    | 5.5      | V    |
| $V_{OUT}$     | Output Voltage                |            | 0    | $V_{CC}$ | V    |
| $T_A$         | Operating Temperature         |            | -40  | +85      | °C   |
| $\theta_{JA}$ | Thermal Resistance            | US8        | -    | 250      | °C/W |
|               |                               | MicroPak-8 | -    | 232      | °C/W |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

1. Unused inputs must be held HIGH or LOW. They may not float.



## DC ELECTRICAL CHARACTERISTICS


| Symbol           | Parameter                  | V <sub>CC</sub> (V) | Conditions                                              |                           | T <sub>A</sub> = +25°C       |                                                         |                          | T <sub>A</sub> = –40 to +85°C |      | Unit |
|------------------|----------------------------|---------------------|---------------------------------------------------------|---------------------------|------------------------------|---------------------------------------------------------|--------------------------|-------------------------------|------|------|
|                  |                            |                     |                                                         |                           | Min                          | Typ                                                     | Max                      | Min                           | Max  |      |
| V <sub>P</sub>   | Positive Threshold Voltage | 1.65                |                                                         |                           | –                            | 0.99                                                    | 1.4                      | –                             | 1.4  | V    |
|                  |                            | 2.3                 |                                                         |                           | –                            | 1.39                                                    | 1.8                      | –                             | 1.8  |      |
|                  |                            | 3.0                 |                                                         |                           | –                            | 1.77                                                    | 2.2                      | –                             | 2.2  |      |
|                  |                            | 4.5                 |                                                         |                           | –                            | 2.49                                                    | 3.1                      | –                             | 3.1  |      |
|                  |                            | 5.5                 |                                                         |                           | –                            | 2.96                                                    | 3.6                      | –                             | 3.6  |      |
| V <sub>N</sub>   | Negative Threshold Voltage | 1.65                |                                                         |                           | 0.2                          | 0.53                                                    | –                        | 0.2                           | –    | V    |
|                  |                            | 2.3                 |                                                         |                           | 0.4                          | 0.78                                                    | –                        | 0.4                           | –    |      |
|                  |                            | 3.0                 |                                                         |                           | 0.6                          | 1.02                                                    | –                        | 0.6                           | –    |      |
|                  |                            | 4.5                 |                                                         |                           | 1.0                          | 1.48                                                    | –                        | 1.0                           | –    |      |
|                  |                            | 5.5                 |                                                         |                           | 1.2                          | 1.76                                                    | –                        | 1.2                           | –    |      |
| V <sub>H</sub>   | Hysteresis Voltage         | 1.65                |                                                         |                           | 0.15                         | 0.46                                                    | 0.9                      | 0.15                          | 0.9  | V    |
|                  |                            | 2.3                 |                                                         |                           | 0.25                         | 0.61                                                    | 1.1                      | 0.25                          | 1.1  |      |
|                  |                            | 3.0                 |                                                         |                           | 0.4                          | 0.75                                                    | 1.2                      | 0.4                           | 1.2  |      |
|                  |                            | 4.5                 |                                                         |                           | 0.6                          | 1.01                                                    | 1.5                      | 0.6                           | 1.5  |      |
|                  |                            | 5.5                 |                                                         |                           | 0.7                          | 1.20                                                    | 1.7                      | 0.7                           | 1.7  |      |
| V <sub>OH</sub>  | HIGH Level Output Voltage  | 1.65                | V <sub>IN</sub> = V <sub>IH</sub><br>or V <sub>IL</sub> | I <sub>OH</sub> = –100 μA | 1.55                         | 1.65                                                    | –                        | 1.55                          | –    | V    |
|                  |                            | 2.3                 |                                                         |                           | 2.2                          | 2.3                                                     | –                        | 2.2                           | –    |      |
|                  |                            | 3.0                 |                                                         |                           | 2.9                          | 3.0                                                     | –                        | 2.9                           | –    |      |
|                  |                            | 4.5                 |                                                         |                           | 4.4                          | 4.5                                                     | –                        | 4.4                           | –    |      |
|                  |                            | 1.65                |                                                         |                           | I <sub>OH</sub> = –4 mA      | 1.29                                                    | 1.52                     | –                             | 1.29 |      |
|                  |                            | 2.3                 |                                                         | I <sub>OH</sub> = –8 mA   | 1.9                          | 2.15                                                    | –                        | 1.9                           | –    |      |
|                  |                            | 3.0                 |                                                         | I <sub>OH</sub> = –16 mA  | 2.4                          | 2.80                                                    | –                        | 2.4                           | –    |      |
|                  |                            | 3.0                 |                                                         | I <sub>OH</sub> = –24 mA  | 2.3                          | 2.68                                                    | –                        | 2.3                           | –    |      |
|                  |                            | 4.5                 |                                                         | I <sub>OH</sub> = –32 mA  | 3.8                          | 4.20                                                    | –                        | 3.8                           | –    |      |
|                  |                            | V <sub>OL</sub>     |                                                         | LOW Level Output Voltage  | 1.65                         | V <sub>IN</sub> = V <sub>IH</sub><br>or V <sub>IL</sub> | I <sub>OL</sub> = 100 μA | –                             | 0.0  |      |
| 2.3              | –                          |                     | 0.0                                                     |                           | 0.10                         |                                                         |                          | –                             | 0.10 |      |
| 3.0              | –                          |                     | 0.0                                                     |                           | 0.10                         |                                                         |                          | –                             | 0.10 |      |
| 4.5              | –                          |                     | 0.0                                                     |                           | 0.10                         |                                                         |                          | –                             | 0.10 |      |
| 1.65             | I <sub>OL</sub> = 4 mA     |                     | –                                                       |                           | 0.08                         |                                                         |                          | 0.24                          | –    | 0.24 |
| 2.3              | I <sub>OL</sub> = 8 mA     |                     | –                                                       |                           | 0.10                         |                                                         | 0.3                      | –                             | 0.3  |      |
| 3.0              | I <sub>OL</sub> = 16 mA    |                     | –                                                       |                           | 0.15                         |                                                         | 0.4                      | –                             | 0.4  |      |
| 3.0              | I <sub>OL</sub> = 24 mA    |                     | –                                                       |                           | 0.22                         |                                                         | 0.55                     | –                             | 0.55 |      |
| 4.5              | I <sub>OL</sub> = 32 mA    |                     | –                                                       |                           | 0.22                         |                                                         | 0.55                     | –                             | 0.55 |      |
| I <sub>IN</sub>  | Input Leakage Current      |                     | 1.65 to 5.5                                             |                           | V <sub>IN</sub> = 5.5 V, GND |                                                         | –                        | –                             | ±0.1 | –    |
| I <sub>OFF</sub> | Power Off Leakage Current  | 0.0                 | V <sub>IN</sub> or V <sub>OUT</sub> = 5.5 V             |                           | –                            | –                                                       | 1                        | –                             | 10   | μA   |
| I <sub>CC</sub>  | Quiescent Supply Current   | 1.65 to 5.5         | V <sub>IN</sub> = 5.5 V, GND                            |                           | –                            | –                                                       | 1                        | –                             | 10   | μA   |

## AC ELECTRICAL CHARACTERISTICS

| Symbol             | Parameter                                   | $V_{CC}$ (V)   | Conditions                                          | $T_A = +25^{\circ}\text{C}$ |     |      | $T_A = -40 \text{ to } +85^{\circ}\text{C}$ |      | Unit |
|--------------------|---------------------------------------------|----------------|-----------------------------------------------------|-----------------------------|-----|------|---------------------------------------------|------|------|
|                    |                                             |                |                                                     | Min                         | Typ | Max  | Min                                         | Max  |      |
| $t_{PLH}, t_{PHL}$ | Propagation Delay<br>(Figure 5, 7)          | $1.8 \pm 0.15$ | $C_L = 15 \text{ pF},$<br>$R_L = 1 \text{ M}\Omega$ | –                           | 7.1 | 13.0 | –                                           | 13.5 | ns   |
|                    |                                             | $2.5 \pm 0.2$  |                                                     | –                           | 4.5 | 7.5  | –                                           | 8.0  |      |
|                    |                                             | $3.3 \pm 0.3$  |                                                     | –                           | 3.4 | 5.0  | –                                           | 5.5  |      |
|                    |                                             | $5.0 \pm 0.5$  |                                                     | –                           | 2.6 | 3.8  | –                                           | 4.2  |      |
|                    |                                             | $3.3 \pm 0.3$  | $C_L = 50 \text{ pF},$<br>$R_L = 500 \Omega$        | –                           | 4.0 | 5.8  | –                                           | 6.3  | ns   |
|                    |                                             | $5.0 \pm 0.5$  |                                                     | –                           | 3.1 | 4.5  | –                                           | 4.9  |      |
| $C_{IN}$           | Input Capacitance                           | 0              |                                                     | –                           | 2.5 | –    | –                                           | –    | pF   |
| $C_{PD}$           | Power Dissipation Capacitance<br>(Figure 6) | 3.3            | (Note 2)                                            | –                           | 15  | –    | –                                           | –    | pF   |
|                    |                                             | 5.0            |                                                     | –                           | 18  | –    | –                                           | –    |      |


2.  $C_{PD}$  is defined as the value of the internal equivalent capacitance which is derived from dynamic operating current consumption ( $I_{CCD}$ ) at no output loading and operating at 50% duty cycle. (see Figure 6)  $C_{PD}$  is related to  $I_{CCD}$  dynamic operating current by the expression:  
 $I_{CCD} = (C_{PD}) (V_{CC}) (f_{IN}) + (I_{CCstatic})$ .

## AC Loading and Waveforms



$C_L$  includes load and stray capacitance  
 Input PRR = 1.0 MHz,  $t_W = 500 \text{ ns}$

Figure 5. AC Test Circuit



Input = AC Waveform;  $t_r = t_f = 1.8 \text{ ns}$ ;  
 PRR = 10 MHz; Duty Cycle = 50%.


Figure 6.  $I_{CCD}$  Test Circuit

Figure 7. AC Waveforms

## NC7WZ132

### ORDERING INFORMATION

| Order Number | Top Mark | Package                                               | Shipping <sup>†</sup> |
|--------------|----------|-------------------------------------------------------|-----------------------|
| NC7WZ132K8X  | WZD2     | 8-Lead US8, JEDEC MO-187, Variation CA<br>3.1 mm Wide | 3000 / Tape & Reel    |
| NC7WZ132L8X  | T5       | 8-Lead MicroPak, 1.6 mm Wide                          | 5000 / Tape & Reel    |

### DISCONTINUED (Note 4)

|                    |      |                                                       |                    |
|--------------------|------|-------------------------------------------------------|--------------------|
| NC7WZ132K8X-L22236 | WZD2 | 8-Lead US8, JEDEC MO-187, Variation CA<br>3.1 mm Wide | 3000 / Tape & Reel |
| NC7WZ132L8X-L22185 | T5   | 8-Lead MicroPak, 1.6 mm Wide                          | 5000 / Tape & Reel |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.



3. All packages are lead free per JEDEC: J-STD-020B standard.

4. **DISCONTINUED:** These devices are not recommended for new design. Please contact your **onsemi** representative for information. The most current information on these devices may be available on [www.onsemi.com](http://www.onsemi.com).

MicroPak is a trademark of Semiconductor Components Industries, LLC dba "onsemi" or its affiliates and/or subsidiaries in the United States and/or other countries.

**UQFN8 1.6X1.6, 0.5P**  
CASE 523AY  
ISSUE O


DATE 31 AUG 2016



**RECOMMENDED  
LAND PATTERN**

**NOTES:**

- A. PACKAGE CONFORMS TO JEDEC MO-255 VARIATION UAAD.
- B. DIMENSIONS ARE IN MILLIMETERS.
- C. DIMENSIONS AND TOLERANCES PER ASME Y14.5M, 2009.
- D. LAND PATTERN RECOMMENDATION IS EXISTING INDUSTRY LAND PATTERN.





|                         |                            |                                                                                                                                                                                  |
|-------------------------|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON13591G</b>         | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>UQFN8 1.6X1.6, 0.5P</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                               |


onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**US8**  
CASE 846AN  
ISSUE O


DATE 31 DEC 2016



## RECOMMENDED LAND PATTERN




## SIDE VIEW



## DETAIL A

**NOTES:**

- A. CONFORMS TO JEDEC REGISTRATION MO-187**
- B. DIMENSIONS ARE IN MILLIMETERS.**
- C. DIMENSIONS ARE EXCLUSIVE OF BURRS,  
MOLD FLASH, AND TIE BAR EXTRUSIONS.**
- D. DIMENSIONS AND TOLERANCES PER  
ANSI Y14.5M, 1994.**



|                         |                    |                                                                                                                                                                                     |
|-------------------------|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON13778G</b> | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>US8</b>         | <b>PAGE 1 OF 1</b>                                                                                                                                                                  |

**onsemi** and **onsemi** are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)