




Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Housing**
Connector & Housing Type: **Plug**
Connector System: **Wire-to-Wire**
Number of Positions: **4**
Centerline (Pitch): **6.35 mm [.25 in]**

Features

Product Type Features

Rectangular Power Connector Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	4
Number of Rows	1

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Contact Features

Multiple Contact Types	Without
Contact Layout	Inline
Contact Retention Within Housing	Without



Contact Type	Socket
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	6.35 mm [.25 in]
Housing Color	White
Housing Material	Nylon GF
Dimensions	
Product Width	22.99 mm
Product Length	26.67 mm
Usage Conditions	
Operating Temperature Range	-55 – 120 °C [-67 – 248 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
CSA Rating	Certified, LR 7189
UL Rating	Recognized
Compatible With Agency/Standards Products	CSA, UL, VDE
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire
Packaging Features	
Packaging Quantity	1
Packaging Method	Package
Product Compliance	
For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant




China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 350793-1 04P UMNL PIN HDR ASSY 94VO	 TE Part # 770253-3 UMNL II SOK PTPPHBZ LP 24-18	 TE Part # 770247-3 UMNL II SOK PTPPHBZ LP 12-10	 TE Part # 350826-4 04P UMNL HDR ASSY PC 94VO LF
 TE Part # 1-770251-0 UMNLII SOK PTPPHBZ LP LF 20-14	 TE Part # 350833-1 04P UMNL HDR ASSY PC 94VO	 TE Part # 770252-1 UMNL II PIN PTPBR LP 24-18	 TE Part # 173926-1 4 P ACTION PIN UMNL



TE Part # 1-770250-0
UMNL II PIN SN/AUNI/BR LP20-14



TE Part # 770250-1
UMNL II PIN PTPBR LP 20-14



TE Part # 770251-3
UMNL II SOK PTPPHBZ LP 20-14



TE Part # 350793-3
04P UMNL PIN HDR ASSY 94VO LF



TE Part # 1-770005-0
UMNL II PIN AUSN/NI/BR



TE Part # 194010-1
PIN ASSY..070



TE Part # 1-350944-0
04P UMNL HDR ASSY R/A 94VO



TE Part # 350792-1
04P UMML PIN HDR ASSY 94VO



TE Part # 770026-1
04P UMNLII IN-LINE CAP HSG KIT



TE Part # 641968-1
04P UMNL PIN HDR ASSY POL 94VO



TE Part # 350826-1
04P UMNL HDR ASSY PC 94VO



TE Part # 643230-1
04P UMNL HDR ASSY R/A 94VO

Also in the Series | Universal MATE-N-LOK



Circular Power Connectors(2)



Connector Caps & Covers(34)



Connector Contacts(209)




Connector Hardware(12)



Connector Seals & Cavity Plugs(27)



Connector Strain Relief(7)



Insertion & Extraction Tools(4)



Rectangular Connector Housings(1)



Rectangular Power Connectors(664)



Standard Circular Connectors(1)

Customers Also Bought



TE Part #770022-1
12P UMNLI IN-LINE PLUG HSG KIT



TE Part #770028-1
09P UMNLI IN-LINE CAP HSG KIT



TE Part #770024-1
02P UMNLI IN-LINE CAP HSG KIT



TE Part #770029-1
12P UMNLI IN-LINE CAP HSG KIT



TE Part #770030-1
15P UMNLI IN-LINE CAP HSG KIT




TE Part #770018-1
03P UMNLI IN-LNE PLUG HSG KIT



TE Part #770027-1
06P UMNLI IN-LINE CAP HSG KIT



TE Part #770023-1
15P UMNLI IN-LNE PLUG HSG KIT



TE Part #770003-3
UMNLI PIN PTPPHBZ



TE Part #770004-3
UMNLI SOK PTPPHBZ

Documents

Product Drawings

04P UMNLI IN-LNE PLUG HSG KIT

English

CAD Files

Customer View Model

ENG_CVM_CVM_770019-1_F.2d_dxf.zip

English

3D PDF



3D

Customer View Model

[ENG_CVM_CVM_770019-1_F.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_770019-1_F.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[SOFT_SHELL_PIN_SOCKET_CONNECTORS_STANDARD_DENSITY](#)

English

Product Specifications

[Application Specification](#)

English

Instruction Sheets

[Instruction Sheet \(U.S.\)](#)

English

Agency Approvals

[VDE Certificate](#)

English

[VDE Certificate](#)

English