




Terminals & Splices > Automotive Terminals > TIMER, RECEPTACLE AND TAB



Terminal Type: **Receptacle**
Mating Tab Width: **2.8 mm [.11 in]**
Mating Tab Thickness: **.8 mm [.031 in]**
Terminal Transmits: **25 – 40 A (Power)**
Wire Size: **24 – 20 AWG**

[All TIMER, RECEPTACLE AND TAB \(323\)](#)

Features

Product Type Features

Receptacle Style	180°
Sealable	Yes
Primary Locking Feature	Locking Lance

Body Features

Terminal Seal Type	Single Wire Seal (SWS)
--------------------	------------------------

Contact Features

Contact Size	2.8mm
Contact Fabrication	Stamped & Formed
Wire Contact Termination Area Plating Material	Tin
Typical Current Rating	30 A
Crimp Type	F-Crimp
Terminal Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.8 mm[.031 in]
Interface Plating	Tin (Sn)

Termination Features

Termination Method to Wire & Cable	Crimp
------------------------------------	-------



Product Terminates To	Wire
-----------------------	------

Dimensions

Compatible Insulation Diameter Range	1.15 – 1.6 mm, 3.4 mm[.134 in]
Wire Size	.2 – .5 mm ²
Wire Size Search	20 AWG, 21 AWG, 22 AWG, 23 AWG, 24 AWG

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature (Max)	80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C, 130 °C[176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F][266 °F]
Operating Temperature Range	-40 – 130 °C[-40 – 266 °F]

Operation/Application

Compatible With Wire Base Material	Copper
------------------------------------	--------

Industry Standards

Compatible With Agency/Standards Products	DIN 72 551 Part 6, DIN ISO 6722 part 3
---	--

Packaging Features

Packaging Quantity	3500
Packaging Method	Reel

Other

Terminal Transmits	25 – 40 A (Power)
--------------------	-------------------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC



Free

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 4-1579007-3
EXTRACTION TOOL KIT



TE Part # 1-1579007-6
EXTRACTION TOOL



TE Part # CAT-T4827-CH8172
Timer Connector Housing



TE Part # 828904-1
SINGLE WIRE SEAL FOR J.P.T.CON




TE Part # 2151268-1
OCEAN_2.0_APPLICATOR-S-062F155O-RSM



TE Part # 2151268-2
OCEAN_2.0_APPLICATOR-S-062F155O-RSA



TE Part # 2305570-1
Strip Terminal Cutter-Side Feed-No Crimp



TE Part # 7-2151268-7
OCEAN_2.0_SPARE_PART_KIT-062F155O



TE Part # 444248-1
ASS'Y 3 POSN JPT RE

Also in the Series | Junior Timer



Automotive Housings(55)



Automotive Terminals(15)



Busbars & Terminals(1)



Connector Seals & Cavity Plugs(1)

Customers Also Bought



TE Part #2050052-1
4POS 2.8MM SENSOR PLUG ASSY.



TE Part #2005431-1
025/090 HYB 34P PLUG ASSY




TE Part #1-2379006-1
52POS, HYBRID, REC HSG ASSY




TE Part #2050049-1
3POS 2.8MM SENSOR PLUG ASSY



TE Part #2278584-2
67 POS, MIXED, REC HSG, ASSY,
SEALED TYPE45



TE Part #1-2435164-1
4POS, HYBRID, REC HSG



TE Part #2394733-1
4POS, 0.63X0.63, TAB HSG ASSY,
UNSLD



TE Part #2434766-3
AMP MCP 6.3/4.8K, TERMINAL



TE Part #2437419-1
2 POS. PLUG ASSY, KEY M, BLACK,
CONN KIT



TE Part #2435015-5
6POS, MCON 1.2, REC HSG ASSY, SLD

Documents

Product Drawings

JPT REC 2.8 Contact SWS Sn

English

CAD Files

Customer View Model

ENG_CVM_927772-1_A9.3d_igs.zip

English

Customer View Model



[ENG_CVM_927772-1_A9.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_927772-1_A9.2d_dxf.zip](#)

English

3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

German

Application Specification

English

Application Specification

English